

LCD Commercial EV Charger

NA



LCD Commercial EV Charger



Model: EVC48-N3



Bluetooth



Wi-Fi



OCPP 1.6J



RFID

Features

- OTA Remote Firmware Updates
- 4.3" LCD Screen
- OCPP 1.6J Fully Compliance
- Enclosure Rating: NEMA Enclosure Type 4

Application

- Commercial Area
- Public Parking Garage
- Residential Area

Suitable for NA



	32A Max	40A Max	48A Max	80A Max
Electrical Parameter	Single phase input: 208-240VAC 60 Hz			
	7.6kW at 240 VAC	9.6kW at 240 VAC	11.5kW at 240 VAC	19.2kW at 240VAC
Input Cord	Hardwired			
Output Cable & Connector	18 FT/5.5 m cable (25 FT/7.5m optional)			
	SAE J1772, NACS standard compliance			
Environmental Parameter	NEMA Enclosure Type4: Weatherproof, dust-tight			
	IK08: Resistant polycarbonate case			
	Operating Temperature: -22°F to 122°F (-30°C to 50°C)			
Dimension	Main enclosure:12.8in × 9.7in × 3.8in (326mm × 247mm × 97mm)			
Standards	NEC625, UL2231, UL2594, OCPP1.6J, ISO15118, CTEP compliance			
Certification	ETL, FCC, Energy Star compliance			

Optional

- 4G Module
- Power balance EMS
- Color customization