



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR231100237407

Page: 1 of 10

1 Cover Page

RF Exposure Evaluation Report

Application No.: SHCR2311002374EV
Applicant: CSE Energy&Technology Co.,Ltd
Address of Applicant: Building S4, No.777, Sizhuan Road, Shanghai, China
Manufacturer: CSE Energy&Technology Co.,Ltd
Address of Manufacturer: Building S4, No.777, Sizhuan Road, Shanghai, China
Equipment Under Test (EUT):
EUT Name: AC charging pile of electric vehicle
Model No.: CSE-BCG-AS32-K01-3-CE
Add Model No.: CSE-BCG-AS32-K01-1-CE
Trade Mark: CSE
Standard(s) : EN IEC 62311:2020
Date of Receipt: 2023-10-09
Date of Test: 2023-10-23 to 2023-10-24
Date of Issue: 2023-11-21

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR231100237407

Page: 2 of 10

Revision Record			
Version	Description	Date	Remark
00	Co-license	2023-11-21	Base on SHCR231000209007

Authorized for issue by:				
Tested By		Bill Wu		
		Bill Wu/Project Engineer		
Approved By		Parlam Zhan		
		Parlam Zhan / Reviewer		



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR231100237407

Page: 3 of 10

2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 GENERAL DESCRIPTION OF E.U.T.....	4
3.2 TECHNICAL SPECIFICATIONS.....	4
3.3 TEST LOCATION.....	5
3.4 TEST FACILITY.....	6
4 TEST STANDARDS AND LIMITS.....	7
5 CALCULATION FORMULA AND TEST RESULT.....	9
5.1 CALCULATION FORMULA.....	9
5.2 CALCULATION RESULTS.....	9

3 General Information

3.1 General Description of E.U.T.

Power supply:	AC 230V 50 32A
---------------	----------------

3.2 Technical Specifications

BLE

Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Receiver Category:	2
Antenna Gain:	2 dBi (Provided by manufacturer)
Antenna Type:	PCB Antenna

2.4GHz WiFi

Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2472MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK), 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Channel Spacing:	5MHz
Number of Channels:	802.11b/g/n(HT20): 13
Receiver Category:	1
Antenna Gain:	2 dBi (Provided by manufacturer)
Antenna Type:	PCB Antenna

NFC

Operation Frequency:	13.56MHz
Modulation Type:	ASK
Antenna Type:	Loop Antenna

GSM

Frequency Band:	Band	Tx (MHz)	Rx (MHz)
	E-GSM900	880-915	925-960
	DCS1800	1710-1785	1805-1880
Type of Modulation:	GMSK(GSM/GPRS/EGPRS), 8PSK (EGPRS)		
Sample Type:	Module equipment		
Antenna Type:	External Antenna		
Antenna Gain:	3dBi (Provided by manufacturer)		

LTE

	LTE BAND	Duplex Mode	Uplink (MHz)	Downlink (MHz)	Supported Channel Bandwidth					
					1.4	3	5	10	15	20
Frequency Band:	1	FDD	1920-1980	2110-2170	---	---	☒	☒	☒	☒
	3	FDD	1710-1785	1805-1880	☒	☒	☒	☒	☒	☒
	7	FDD	2500-2570	2620-2690	---	---	☒	☒	☒	☒
	8	FDD	880-915	925-960	☒	☒	☒	☒	---	---
	20	FDD	791-821	832-862	---	---	☒	☒	☒	☒
	28	FDD	703-748	758-803	---	☒	☒	☒	☒	☒
	Type of Modulation:	UL: QPSK,16QAM DL: QPSK,16QAM,64QAM								
Sample Type:	Module equipment									
Antenna Type:	External Antenna									
Antenna Gain:	3dBi (Provided by manufacturer);									

3.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China.

Tel: +86 21 6191 5666

Fax: +86 21 6191 5678

No tests were sub-contracted.

Note:

1. SGS is not responsible for wrong test results due to incorrect information (e.g. max. clock frequency, highest internal frequency, antenna gain, cable loss, etc) is provided by the applicant. (if applicable).
2. SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (if applicable).
3. Sample source: sent by customer.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6332.01)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the American Association for Laboratory Accreditation(A2LA).

- **FCC (Designation Number: CN1301)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

- **ISED (CAB Identifier: CN0020)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. EMC Laboratory has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory. Company Number: 8617A

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-13868, C-14336, T-12221, G-10830 respectively.

4 Test Standards and Limits

The evaluation has been performed on the EUT, pursuant to the relevant requirements of the following document(s) and the harmonized EN standard(s) covering essential requirements under article 3.1a of the RED Directive (2014/53/EU).

Identity	Document Title	Version
Council Recommendation of 12 July 1999(1999/519/EC)	On the limitation of exposure of the general public to electromagnetic fields (0Hz to 300GHz)	1999
EN IEC 62311	Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz – 300 GHz)	2020

Limit: According to EN IEC 62311, the criteria listed in the below table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified table 2 of Council Recommendation 1999/519/EC.

Table 2
Reference levels for electric, magnetic and electromagnetic fields
(0 Hz to 300 GHz, unperturbed rms values)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (μT)	Equivalent plane wave power density S_{eq} (W/m ²)
0-1 Hz	—	$3,2 \times 10^4$	4×10^4	—
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	—
8-25 Hz	10 000	$4\,000/f$	$5\,000/f$	—
0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	—
0,8-3 kHz	$250/f$	5	6,25	—
3-150 kHz	87	5	6,25	—
0,15-1 MHz	87	$0,73/f$	$0,92/f$	—
1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	—
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f/200$
2-300 GHz	61	0,16	0,20	10

Notes:

1. f as indicated in the frequency range column.
2. For frequencies between 100 kHz and 10 GHz, S_{eq} , E^2 , H^2 , and B^2 are to be averaged over any six-minute period.
3. For frequencies exceeding 10 GHz, S_{eq} , E^2 , H^2 , and B^2 are to be averaged over any $68/f^{1.05}$ -minute period (f in GHz).
4. No E-field value is provided for frequencies < 1 Hz, which are effectively static electric fields. For most people the annoying perception of surface electric charges will not occur at field strengths less than 25 kV/m. Spark discharges causing stress or annoyance should be avoided.



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR231100237407

Page: 8 of 10

Note1: The limit of power density

2.4G is 10W/m^2 ;

13.56MHz is 0.073A/m ;

GSM 900: 4.4 W/m^2 ;

DCS 1800: 8.55 W/m^2

WCDMA band I: 9.6 W/m^2 ;

WCDMA band VIII: 4.4 W/m^2 ;

FDD band 1: 9.25 W/m^2 ;

FDD band 3: 8.55 W/m^2 ;

FDD band 7: 10 W/m^2 ;

FDD band 8: 4.4 W/m^2 ;

FDD band 20: 4.2 W/m^2 ;

FDD band 28: 3.74W/m^2 ;

5 Calculation Formula and Test Result

5.1 Calculation Formula

$$Pd = (Pout * G) / 4\pi R^2$$

Where:

Pd = Power density in W/m²

Pout = Output power to antenna in W

G = Antenna Gain in linear scale

$\pi = 3.14$

R = distance to the center of radiation of antenna (in meter) = 0.2m

NOTE: Pd limit = 10W/m².

5.2 Calculation Results

The EIRP Data is based on the RF Test Report BLE-ETSP-1-2111H032, BLE-ETSP-2-2111H032, 2203RSU066-E1, 2203RSU066-E4

Test Mode	Frequency Band (MHz)	Average EIRP (dBm)	Result of Power Density S (W/m ²)	Limit of Power Density S (W/m ²)
BLE	2402~2480	9.0	0.02	10
2.4GHz WiFi	2412~2472	18.5	0.14	10

Test Mode	Frequency Band (MHz)	Maximum Output Power(dBm)	Average EIRP (dBm)	Result of Power Density S (W/m ²)	Limit of Power Density S (W/m ²)
GSM 900	880~915	26	29	1.58	4.40
GSM 1800	1710~1785	23	26	0.79	8.55

The averaged power calculated method are shown as below:

Averaged power=Maximum burst averaged power (1 Tx Slot) + (10lg(1/8))dB

Averaged power=Maximum burst averaged power (2 Tx Slot) + (10lg(2/8))dB

Averaged power=Maximum burst averaged power (3 Tx Slot) + (10lg(3/8))dB

Averaged power=Maximum burst averaged power (4 Tx Slot) + (10lg(4/8))dB

Average EIRP Power=Average Power + Antenna Gain



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

SHEM-TRF-001 Rev. 02 Sep01, 2023

Report No.: SHCR231100237407

Page: 10 of 10

Test Mode	Frequency Band (MHz)	Maximum Output Power(dBm)	Average EIRP (dBm)	Result of Power Density S (W/m ²)	Limit of Power Density S (W/m ²)
LTE Band 1	1920-1980	25.7	28.7	1.48	9.25
LTE Band 3	1710-1785	25.7	28.7	1.48	8.55
LTE Band 7	2500-2570	25.7	28.7	1.48	10
LTE Band 8	880-915	25.7	28.7	1.48	4.4
LTE Band 20	832-862	25.7	28.7	1.48	4.2
LTE Band 28	703-748	25.7	28.7	1.48	3.74

The averaged power calculated method are shown as below:
Average EIRP Power= Maximum Output Power+ Antenna Gain

For 13.56MHz:

Refer to the test report SHCR231100237404, the measured maximum Magnetic Fields is 2.03dBuA/m (0.000001A/m). This is below the max permitted sending level of 0.073A/m, so the device meets the requirements.

The WiFi and BLE and LTE and 13.56MHz can simultaneous transmitting. But the maximum rate of MPE is $0.14/10+0.02/10+1.48/3.74+0.000001/0.073=0.40 \leq 1$, and then the EUT is not need to conduct SAR measurement.

Then the EUT is not need to conduct SAR measurement.

-The End of Report-