



PRODUCT DETAILS



FRNZBA705



The FRNZBA705 model is made with high-performance rubber compounds, designed for high-intensity work applications and tires that can withstand continuous use all day, ensuring durability. Its classic bullet-shaped tread pattern offers strong adaptability and stability on various terrains.

Eco-friendly colored solid tires and the Linde or Clip Version of the FRNZBA705 are also available for specific sizes.

Size of Tire	Rim Size	Tire Type			Outside Diameter (mm) ±5mm	Section Width (mm) ±5mm	Net(Kg) ±1.5%	Max Load(Kg)					
		Standard (Black)	Linde (Clip)	Green (Color)				10Km/H		16Km/H		25Km/H	
								Driving	Steering	Driving	Steering	Driving	Steering
5.00-8	3.00/3.50/3.75	✓	✓	✓	466	127	18.40	1255	965	1145	880	1060	815
6.00-9	4.00E	✓	✓	✓	533	140	26.80	1975	1520	1805	1390	1675	1290
6.50-10 (560x165x11)	5.00	✓	✓	✓	582	157	36.00	2715	2090	2485	1910	2310	1775
7.00-12	5.00	✓	✓	✓	663	163	47.60	3105	2390	2835	2180	2635	2025
8.25-15	6.50	✓	✓	✓	829	202	90.00	5085	3910	4640	3570	4310	3315
15x4 1/2-8	3.00D	✓	✓	✓	383	107	9.40	1005	775	915	705	850	655
16x6-8 (150/75-8)	4.33	✓	✓	✓	416	156	16.90	1545	1190	1410	1085	1305	1005
18x7-8 (180/70-8)	4.33	✓	✓	✓	452	155	20.80	2430	1870	2215	1705	2060	1585
18x7-9	4.33R	✓	✓	✓	452	155	19.90	2230	1780	2150	1615	2005	1505
21x8-9	6.00E	✓	✓	✓	523	180	34.10	2890	2225	2645	2035	2455	1890
23x9-10	6.50F	✓	✓	✓	595	212	51.00	3730	2870	3405	2620	3160	2430
23x10-12 (250/60-12)	8.00	✓	✓	✓	592	230	51.20	4450	3425	4060	3125	3770	2900
27x10-12 (250/75-12)	8.00	✓	✓	✓	680	236	74.70	4595	3535	4200	3230	3900	3000
28x9-15 (815x15)	7.00	✓	✓	✓	700	230	63.00	4060	3125	3710	2855	3445	2650
28x12.5-15 (355x45/15)	9.75	✓	✓	✓	706	300	86.00	6200	4770	5660	4355	5260	4045
140/55-9	4.00E	✓	✓	✓	380	130	10.50	1380	1060	1260	970	1170	900
200/50-10	6.50	✓	✓	✓	458	198	25.20	2910	2240	2665	2050	2470	1900
250-15 (250/70-15)	7.00/7.50	✓	✓	✓	726	235	73.60	5595	4305	5110	3930	4745	3650
300-15 (315/70-15)	8.00	✓	✓	✓	827	256	112.50	6895	5305	6300	4845	5850	4500