REPT BATTERO

тѕіпоѕнап

JOIN THE GREEN JOURNEY



COMPANY

INTRODUCTION

>> Tsingshan Holding Group

Tsingshan Industry has invested in the new energy field by combining its rich mineral resources. Adhering to the mission of 'Refining a hundred years of stainless steel, building a green future', REPT BATTERO enjoys the unique resource integration ability and synergy advantage of the whole industrial chain conferred by Tsingshan Industry, and has become one of the fastest-growing battery producers in the industry.

N_{0.1}

Global stainless steel crude steel production output

N_{0.1}

Global nickel metal production output

N_{0.265}

Fortune Global 500 companies in 2024

185000+

Total employees in 2025

>> REPT

REPT BATTERO Energy Co., Ltd. was established in 2017. It is the first enterprise that Qingshan Industrial has invested in the new - energy field. REPT BATTERO is mainly engaged in the research and development, production, and sales of lithium - ion batteries, and provides solutions for intelligent energy - storage systems.

The company has R&D centers in Shanghai, Wenzhou, and Jiaxing, as well as production bases in Wenzhou, Jiaxing, uzhou, Foshan, Chongqing, and Indonesia. By the end of 2024, its total production capacity will reach 79GWh. It is expected that the capacity will exceed 90GWh in 2025. In the whole year of 2024, in terms of the shipment volume of energy - storage batteries, the company ranked fifth globally, and in terms of the shipment volume of batteries in the household energy - storage segment, it ranked

BloomberaNEF Tier 1 Energy Storage Manufac-

BNEF Tier1 ¥17.7Billion

Sales revenue in 2024

NO.2

Global Household Energy Storage Battery Shipments to 2024

Global Energy Storage Battery Shipments in

>> Main Business

Supplying power battery systems and services for green transportation networks











Battery Packs

Supplying solutions and services for clean energy storage









Electrical

Energy Storage Systems

Energy Storage Stations

>> Manufacturing Plant



WEN ZHOU, CHINA



JIA XING, CHINA



LIU ZHOU, CHINA



FO SHAN, CHINA



CHONG QING, CHINA



MALUKU, INDONESIA

>>> Energy Storage Cells

Ultility and C&I













Capacity	280Ah	306Ah	314Ah	345Ah	392Ah	587Ah
Nominal Voltage	3.2V	3.2V	3.2V	3.2V	3.2V	3.2V
Voltage Range	2.50-3.65V	2.50-3.65V	2.50-3.65V	2.50-3.65V	2.50-3.65V	2.50-3.65V
Cycle life	10000cycles	1000cycles	12000cycles	10000cycles	10000cycles	10000cycles
Dimension	71.7x174x206.8(mm)	71.7x174x206.8(mm)	71.7x174x206.8(mm)	71.7x174x206.8(mm)	75x182x224.5(mm)	73x275x218(mm)
Mass	5.48±0.15(kg)	5.48±0.15(kg)	5.48±0.15(kg)	5.48±0.15(kg)	6.85±0.15(kg)	10±0.2(kg)
Certificate	UL1973、UL9540A、 IEC62619、UN38.3、 UL1642、GB/T 36276	UL9540A, UL1973, IEC62619, UN38.3, UL1642,GB/T	UL1973、UL9540A、 IEC62619、UN38.3、 UL1642、GB/T 36276	UL1973、UL9540A、 IEC62619、UN38.3、 UL1642、GB/T 36276	UL1973、UL9540A、 IEC62619、UN38.3、 UL1642、GB/T 36276	UL1973、UL9540A、 IEC62619、UN38.3、 UL642

Residential











Capacity	50Ah	72Ah	100Ah	100Ah	100Ah
Nominal Voltage	3.2V	3.2V	3.2V	3.2V	3.2V
Voltage Range	2.50-3.65V	2.50-3.65V	2.50-3.65V	2.50-3.65V	2.50-3.65V
Cycle life	7000cycles	6000cycles	6000cycles	3000cycles	6000cycles
Dimension	39.7x148.6x101(mm)	39.7x148.6x111(mm)	52x148x119(mm)	52x148x119(mm)	27x173x207(mm)
Mass	1.13±0.10(kg)	1.40±0.10(kg)	1.91±0.10(kg)	1.87±0.10(kg)	2.05±0.15(kg)
Certificate	UL9540A, UL1973 , IEC62619,SII, JIS8715-2, UL1642, UN38.3	UL9540A, UL1973, IEC62619,UN38.3	UL9540A, UL1973, IEC62619,UN38.3, JIS8715-2	UL9540A, UL1973, IEC62619, UN38.3	UL9540A, UL1973, IEC62619, UN38.3

>>> Energy Storage System Product Matrix









	Y52 Module	Y104 Module	C&I All-in-One Cabinet	Battery Cabinet
Grouped Configuration	1P52S	1P104S	1P260S	1P416S
Nominal Voltage	166.4Vdc	332.8Vdc	400Vac, 3L/N/PE	1331.2Vdc
Voltage Range	130~189.8(Vdc)	260V~379.6(Vdc)	676-936(Vdc)	1081.6~1497.6(Vdc)
Nominal Energy	46.6kWh	104.5kWh	261.2kWh	372.7kWh
Dimension	1120×810×238(mm)	2150.5×779×250(mm)	1050×2250×1400(mm)	1300×1300×2230(mm)
Mass	330kg	690kg	2.58t	3. 5t









	Powtrix-i(BV) All-in-One ESS	Powtrix 1.0 DC Container	Powtrix 2.0 DC Container	Powtrix 3.0 DC Container
Grouped Configuration	416S10P	416S10P	416S12P	416S12P
Nominal Voltage	DC 1331.2V AC 690V	1331.2V	1331.2V	1331.2V
Battery Voltage Range	1040V~1500V	1040V~1500V	1040V~1500V	1040V~1500V
Nominal Energy	2.09MW, 4.18MWh	3.727MWh	5.016MWh	6.262MWh
Dimension	10080x2440x2940(mm)	6058×2438×2896(mm)	6058×2438×2896(mm)	6058×2438×2896(mm)
Nominal Mass	44.9t	36t	44.5t	49t

>>> Energy Storage Project Highlight



Morowali Industrial Park (IMIP),Indonesia 150 MWh



Texas, USA 226 MWh



Texas, USA 130 MWh



New South Wales, Australia 1,680 MWh



117.5 MWh



Xinjiang, China 800 MWh



Chongqing, China 400 MWh



Ningxia, China 400 MWh











>> ESG Management







We will establish a development system aligned with the United Nations Sustainable Development Goals, creating a safe and healthy workplace for all employees and a green, eco-friendly community environment to ensure sustainable and rapid growth.

>>> Global Industrial Layout



Planned Production Capacity For 2025



R&D Center

Jiaxing | Shanghai Wenzhou Production Base

Wenzhou | Jiaxing | Liuzhou Foshan | Chongqing | Indonesia _|

Indonesia Base
Under Construction

REPT BATTERO Energy Co.,Ltd.

R&D Center

Jiaxing Wenzhou Shanghai, China Email:market@reptbattero.com Production Base

Wenzhou Jiaxing Liuzhou Foshan Chongqing Indonesia, China Email:market@reptbattero.com

American Subsidiary

REPT Battero American Corporation Address:California USA Email:market@reptbattero.com German Subsidiary

REPT Battero Energy Germany GmbH Address:Munichen Germany Subsidiary Email:market@reptbattero.com

Indonesia base

Address: Maluku Indonesia Email:market@reptbattero.com



STOCK CODE 0666.HK