



• Application

This cable configuration with 133% insulation level and one third neutral is suitable for applications requiring stable power distribution with reduced electromagnetic interference. Commonly used in industrial and commercial facilities, utility networks, and areas with light load conditions, it efficiently manages unbalanced loads while ensuring reliable power transmission.

• Performance

Operating Voltage: 25kV
 Temperature Rating:
 Normal Operation: Up to 90°C
 Emergency Overload: Up to 130°C
 Short Circuit Conditions: Up to 250°C
 Ambient Temperature Range: Suitable for environments ranging from -40°C to +90°C
 Mechanical Performance:
 Maximum Sidewall Pressure: 1000 lbs./FT
 Bending Radius: 12 times the cable diameter for fixed installations, 15 times for occasional flexing

• Construction

Conductor: Moisture-blocked class B compressed stranded soft drawn bare copper per ASTM B3 and ASTM B8 (Conductor moisture block optional and tinned copper per ASTM B33 optional)
 Conductor Shield: Conventional semi-conducting cross-linked copolymer
 Optional: Supersmooth conductor shield
 Conductor tape is used for cable size larger than or equal to 1500 kcmil
 Insulation: 320 Mils Tree Retardant Cross Linked Polyethylene with 133% insulation level
 Insulation Shield: Strippable semi-conducting cross-linked copolymer
 Concentric Neutral: Helically applied soft drawn bare copper one-third concentric neutral
 Overall Jacket: Linear Low Density Polyethylene (LLDPE) Jacket, black with red extruded stripes

• Specification

-ASTM B3 Soft or Annealed Copper Wire
 -ASTM B8 Concentric-Lay-Stranded Copper Conductors
 -ASTM B33 Standard Specification for Tin-Coated Soft or Annealed Copper Wire
 -ICEA S-94-649 Standard for Concentric Neutral Cables Rated 5 - 46kV
 -AIEC CS-8 Specification for extruded dielectric shielded power cables rated for 5 through 46KV (Qualification Test Requirements)
 -Rural Utility Standard RUS 1728F-U1 or 1728.204 (Electric standards and specifications for materials and construction)
 -UL 1072 Listed as MV 90 When Specified
 -Optional CSA 68.5: -40°C and MV 90°C optional marking available upon request

• Eastful Cable Lab



We have CNAS Accredited Facility to assure conformity assessment services with a focus on quality, expertise, and customer satisfaction.
 CNAS has international mutual recognition among IAF, ILAC, APLAC and PAC.

• Accreditation

We meet the requirements of ISO9001, ISO14001, ISO45001 and ISO50001 and our cables have certificate of CCC, RoHS, CASC, UL, cUL, TÜV Rheinland and CCS.



• National Green Factory



Our facility has been awarded of National Green Factory by Ministry of Industry and Information Technology of China. We are committed to the development of high-end, intelligent and green manufacturing industry.

*The overall energy consumption level of green factories is better than the energy efficiency benchmark level.

Technical Parameters

Weights and Measurements											
Conductor Size	Conductor Overall Dia.	Insulation Overall Dia.	Insul. Thickness	Insulation Shield Overall Dia.	Concentric Neutral	Max. D.C. Resistance 25°C	Jacket Thickness	Approx. Overall Dia.	Approx. Weight	Min. Bending Radius	Max. Pull Tension
AWG/kcmil	inch	inch	mils	inch	No. x AWG	Ω/1000ft	mils	inch	lb/1000ft	inch	lb
1 (Solid)	0.289	0.967	320	1.057	7x14	0.375	50	1.285	894	10.3	669
1 (19)	0.322	1	320	1.11	7x14	0.375	50	1.338	938	10.7	669
1/0 (Solid)	0.324	1.002	320	1.112	9x14	0.292	50	1.34	1033	10.7	844
1/0 (19)	0.361	1.039	320	1.149	9x14	0.292	50	1.377	1060	11	844
2/0 (19)	0.405	1.083	320	1.193	11x14	0.239	50	1.421	1205	11.4	1064
3/0 (19)	0.456	1.134	320	1.244	14x14	0.187	50	1.472	1392	11.8	1342
4/0 (19)	0.512	1.19	320	1.3	18x14	0.146	50	1.528	1623	12.2	1692
250 (37)	0.558	1.244	320	1.354	21x14	0.125	50	1.582	1823	12.7	2000
350 (37)	0.661	1.347	320	1.457	29x14	0.09	75	1.735	2404	13.9	2800
500 (37)	0.789	1.475	320	1.585	26x12	0.063	75	1.897	3122	15.2	4000
750 (61)	0.968	1.664	320	1.804	25x10	0.041	75	2.158	4397	17.3	6000
1000 (61)	1.117	1.813	320	1.953	32x10	0.032	75	2.307	5526	18.5	8000

All dimensions are nominal and subject to normal manufacturing tolerances

-Cable marked with this symbol is a standard stock item

-Pulling tension based on pulling eye directly connected to conductor

Electrical and Engineering Data											
Conductor Size	D.C. Resistance @ 25°C	A.C. Resistance @ 90°C	Capacities Reactance @ 60Hz	Inductive Reactance @ 60Hz	Charging Current	Dielectric Loss	Zero Sequence Impedance	Positive Sequence Impedance	Short Circuit Current @ 30 Cycle	Allowable Ampacity in Duct 90°C	Allowable Ampacity Directly Buried 90°C
AWG/kcmil	Ω/1000ft	Ω/1000ft	MΩ/1000ft	Ω/1000ft	A/1000ft	W/1000ft	Ω/1000ft	Ω/1000ft	A	A	A
1 (Solid)	0.128	0.162	0.082	0.056	0.101	1.46	0.216+j0.755	0.162+j0.054	2441	180	220
1 (19)	0.128	0.162	0.077	0.054	0.108	1.56	0.216+j0.753	0.162+j0.055	2441	180	220
1/0 (Solid)	0.102	0.128	0.076	0.054	0.108	1.56	0.182+j0.750	0.128+j0.052	3138	200	250
1/0 (19)	0.102	0.128	0.071	0.052	0.116	1.67	0.182+j0.749	0.128+j0.053	3138	200	250
2/0 (19)	0.081	0.102	0.066	0.051	0.124	1.79	0.156+j0.745	0.102+j0.051	3836	230	285
3/0 (19)	0.064	0.081	0.061	0.049	0.134	1.93	0.135+j0.741	0.081+j0.049	4882	260	320
4/0 (19)	0.051	0.065	0.057	0.047	0.145	2.09	0.119+j0.736	0.065+j0.047	6277	300	360
250 (37)	0.043	0.056	0.054	0.046	0.152	2.19	0.111+j0.733	0.056+j0.046	7323	325	
350 (37)	0.031	0.041	0.048	0.044	0.172	2.48	0.095+j0.724	0.041+j0.044	10113	390	460
500 (37)	0.022	0.03	0.042	0.042	0.195	2.81	0.084+j0.716	0.030+j0.042	14406	455	525
750 (61)	0.014	0.023	0.036	0.04	0.226	3.26	0.077+j0.705	0.023+j0.040	22019	545	580
1000 (61)	0.011	0.019	0.032	0.038	0.253	3.65	0.073+j0.699	0.019+j0.038	28184		

-Ampacities for Direct Buried are based on ICEA P-117-734-2016 Single-Conductor Solid Dielectric 15-35kV. Single Circuit Flat Direct Buried Figure 3

-Ampacities for Duct are based on ICEA P-117-734-2016 for Single-Conductor Solid Dielectric 15-35kV. Single Circuit Trefoil Conduit Figure 7.

-Sequence Impedance values are based on Rho Earth Resistivity: 100 Ohm-Meter/1000ft.

● Technical Parameters

Weights and Measurements (Metric)											
Conductor Size	Conductor Overall Dia.	Insulation Overall Dia.	Insul. Thickness	Insulation Shield Overall Dia.	Concentric Neutral	Max. D.C. Resistance 25°C	Jacket Thickness	Approx. Overall Dia.	Approx. Weight	Min. Bending Radius	Max. Pull Tension
AWG/kcmil	mm	mm	mm	mm	No. x AWG	Ω/km	mm	mm	kg/km	mm	N
1 (Solid)	7.34	24.56	8.13	26.85	7x14	1.23	1.27	32.64	1330	261.62	2977
1 (19)	8.18	25.4	8.13	28.19	7x14	1.23	1.27	33.99	1396	271.78	2977
1/0 (Solid)	8.23	25.45	8.13	28.24	9x14	0.96	1.27	34.04	1537	271.78	3756
1/0 (19)	9.17	26.39	8.13	29.18	9x14	0.96	1.27	34.98	1577	279.4	3756
2/0 (19)	10.29	27.51	8.13	30.3	11x14	0.78	1.27	36.09	1793	289.56	4735
3/0 (19)	11.58	28.8	8.13	31.6	14x14	0.61	1.27	37.39	2072	299.72	5972
4/0 (19)	13	30.23	8.13	33.02	18x14	0.48	1.27	38.81	2415	309.88	7529
250 (37)	14.17	31.6	8.13	34.39	21x14	0.41	1.27	40.18	2713	322.58	8900
350 (37)	16.79	34.21	8.13	37.01	29x14	0.3	1.91	44.07	3578	353.06	12460
500 (37)	20.04	37.47	8.13	40.26	26x12	0.21	1.91	48.18	4646	386.08	17800
750 (61)	24.59	42.27	8.13	45.82	25x10	0.13	1.91	54.81	6543	439.42	26700
1000 (61)	28.37	46.05	8.13	49.61	32x10	0.1	1.91	58.6	8224	469.9	35600

All dimensions are nominal and subject to normal manufacturing tolerances

-Cable marked with this symbol is a standard stock item

-Pulling tension based on pulling eye directly connected to conductor

Electrical and Engineering Data (Metric)											
Conductor Size	D.C. Resistance @ 25°C	A.C. Resistance @ 90°C	Capacities Reactance @ 60Hz	Inductive Reactance @ 60Hz	Charging Current	Dielectric Loss	Zero Sequence Impedance	Positive Sequence Impedance	Short Circuit Current @ 30 Cycle	Allowable Ampacity in Duct 90°C	Allowable Ampacity Directly Buried 90°C
AWG/kcmil	Ω/km	Ω/km	MΩ/km	Ω/km	A/km	W/km	Ω/1000ft	Ω/1000ft	A	A	A
1 (Solid)	0.4199	0.53	0.025	0.1837	0.331	4.79	0.216+j0.755	0.162+j0.054	2441	180	220
1 (19)	0.4199	0.53	0.0235	0.1772	0.354	5.1181	0.216+j0.753	0.162+j0.055	2441	180	220
1/0 (Solid)	0.3346	0.42	0.0232	0.1772	0.354	5.1181	0.182+j0.750	0.128+j0.052	3138	200	250
1/0 (19)	0.3346	0.42	0.0216	0.1706	0.381	5.479	0.182+j0.749	0.128+j0.053	3138	200	250
2/0 (19)	0.2657	0.33	0.0201	0.1673	0.407	5.8727	0.156+j0.745	0.102+j0.051	3836	230	285
3/0 (19)	0.21	0.27	0.0186	0.1608	0.44	6.332	0.135+j0.741	0.081+j0.049	4882	260	320
4/0 (19)	0.1673	0.21	0.0174	0.1542	0.476	6.857	0.119+j0.736	0.065+j0.047	6277	300	360
250 (37)	0.1411	0.18	0.0165	0.1509	0.499	7.185	0.111+j0.733	0.056+j0.046	7323	325	
350 (37)	0.1017	0.13	0.0146	0.1444	0.564	8.1365	0.095+j0.724	0.041+j0.044	10113	390	460
500 (37)	0.0722	0.1	0.0128	0.1378	0.64	9.2192	0.084+j0.716	0.030+j0.042	14406	455	525
750 (61)	0.0459	0.08	0.011	0.1312	0.741	10.6955	0.077+j0.705	0.023+j0.040	22019	545	580
1000 (61)	0.0361	0.06	0.0098	0.1247	0.83	11.9751	0.073+j0.699	0.019+j0.038	28184		

-Ampacities for Direct Buried are based on ICEA P-117-734-2016 Single-Conductor Solid Dielectric 15-35kV. Single Circuit Flat Direct Buried Figure 3

-Ampacities for Duct are based on ICEA P-117-734-2016 for Single-Conductor Solid Dielectric 15-35kV. Single Circuit Trefoil Conduit Figure 7.

-Sequence Impedance values are based on Rho Earth Resistivity: 100 Ohm-Meter/1000ft.