

3 Port Solenoid Valve

Direct Operated Poppet Type

VT307 Series

Rubber Seal



Note) CE/UKCA compliant: Electrical entry is applicable only for the DIN terminal.



How to Order

V T 307 - 5 G 1 - 01 - F -

Body type

T	Body ported
O	For manifold

Valve option

Nil	Standard type
E*	Continuous duty type
Y*	Energy-saving type
V*	Vacuum specification type
W*	Energy-saving type, Vacuum specification type

* Semi-standard

Pressure specifications

Nil	Standard type (0.7 MPa)
K*	High-pressure type (1 MPa)

* Semi-standard

Rated voltage

	Valve option	Nil	E	Y	V	W
Rated voltage						
1	100 VAC, 50/60 Hz	●	●	—	●	—
2	200 VAC, 50/60 Hz	●	●	—	●	—
3*	110 VAC, 50/60 Hz	●	●	—	—	—
4*	220 VAC, 50/60 Hz	●	●	—	—	—
5	24 VDC	●	●	●	●	●
6*	12 DCV	●	●	●	●	●
7*	240 VAC, 50/60 Hz	●	●	—	—	—

* Semi-standard

Electrical entry

	Grommet	DIN terminal
	G: 300 mm lead wire H: 600 mm lead wire	D: With connector
		DO: Without connector
CE/UKCA-compliant	DC —	●
	AC —	●

CE/UKCA-compliant

Nil	None
Q	CE/UKCA-compliant*

* Electrical entry and light/surge voltage suppressor: D/DO/DZ/DOZ only

Bracket

Nil	None
F	With bracket

Thread type

Nil	Rc
F	G
N	NPT
T	NPTF


Port size

Nil	Without port (For manifold)
01	1/8 (6A)
02	1/4 (8A)


Light/Surge voltage suppressor

Nil	None
S	With surge voltage suppressor (Grommet type only)
Z	With light/surge voltage suppressor (DIN terminal type only)

With surge voltage suppressor



Symbol



Manifold

Model	Applicable manifold type	Accessories
VO307□(-Q)	Common or individual exhaust	Function plate (DXT152-14-1A) ^{Note)} Mounting screw (NXT013-3)

Note) It is not applicable to the continuous duty type. Refer to the accessories on page 1247.

Option

Description	Part no.
Bracket	DXT152-25-1A (With screw)

Note) A gasket must be ordered separately for DO. Refer to page 1245 for gasket part numbers.