

成品订购码 Finished product ordering code



φ6					
AMHZ2	6	D	□	M9BW	□
↓	↓	↓	↓	↓	↓
手指数 Fingers	缸径 Cylinder diameter	动作方式 Action	手指可选品种 Finger optional varieties	磁性开关型号 Magnetic switch model	个数 Number
2:2爪 2:2 claw	6	D:双作用 D: Double acting S:单作用 (常开) S: Single acting (normally open) C:单作用 (常闭) C: Single acting (normally closed)	[标准型][Standard type] 无记号: 基本型 No symbol: Basic type 1: 侧面螺孔安装 1: Side screw hole installation 2: 开闭方向通孔安装 2: Open and close direction through hole installation 3: 扁平手指型 3: Flat finger type	无记号 无磁性开关(内置磁环) No mark No magnetic switch (built-in magnetic ring)	无记号: 2个 No mark: 2 S: 1个 S: 1

φ10-φ25					
AMHZ2	16	D	□	□	M9BW
↓	↓	↓	↓	↓	↓
手指数 Fingers	缸径 Cylinder diameter	动作方式 Action	手指位置[表1] Finger positions [Table 1]	主体可选品种[表2] Optional varieties of the main body [Table 2]	磁性开关型号 Magnetic switch model
2:2爪 2:2 claw	10 16 20 25	D:双作用 D: Double acting S:单作用 (常开) S: Single acting (normally open) C:单作用 (常闭) C: Single acting (normally closed)			无记号 无磁性开关(内置磁环) No mark No magnetic switch (built-in magnetic ring)
					无记号: 2个 No mark: 2 S: 1个 S: 1

[表1]




[Table 1]

手指位置·可选品种 Finger position and available varieties	
标准型[与AMHQ2可互换] Standard type [Interchangeable with AMHQ2]	窄型[与AMHQ2可互换] Narrow type [interchangeable with AMHQ2]
无记号: 基本型 No symbol: Basic type 1: 侧面螺孔安装 1: Side screw hole installation 2: 开闭方向通孔安装 2: Opening and closing direction through hole installation	N: 基本型 N: Basic N1: 侧面螺孔安装 N1: side screw hole installation N2: 开闭方向通孔安装 N2: Open and close direction through hole installation
3: 扁平手指型 扁平型手指没有标准型和窄型可选品种。 3: Flat Finger Type Flat fingers do not have standard and narrow types to choose from.	

[表2]

[Table 2]

手指位置·可选品种 Finger position and available varieties	
无记号: 基本型 No symbol: Basic type	E: 端台型 侧面配管 (双作用/单作用) E: End-stage type Side piping (double acting/single acting)
W: 端台型 轴向配管 带双层管的ø4快速接头 (双作用) W: End plate type, axial piping ø4 quick-change fitting with double tube (double acting)	Port
K: 端台型 轴向配管 带ø4快速接头 (单作用) K: End-stage type Axial piping With ø4 quick-change fitting (single acting)	Port
M: 端台型 轴向配管 M5通口 (单作用) M: End plate type Axial piping M5 port (single acting)	Port

φ32-φ40					
AMHZ2 ↓	32 ↓	D ↓	□ ↓	M9BW ↓	□ ↓
手指数 Fingers	缸径 Cylinder diameter	动作方式 Action	手指可选品种 Finger optional varieties	磁性开关型号 Magnetic switch model	磁性开关个数 Number of magnetic switches
2:2爪 2:2 claw	32 40	D:双作用 D: Double acting	1: 侧面螺孔安装 1: Side screw hole installation  2: 开闭方向通孔安装 2: Open and close direction through hole installation 	无记号 无磁性开关(内置磁环) No mark No magnetic switch (built-in magnetic ring)	无记号: 2个 No mark: 2
		S:单作用 (常开) S: Single acting (normally open)			S: 1个 S: 1
		C:单作用 (常闭) C: Single acting (normally closed)			n: n个 n: n
			3: 扁平手指型 : Flat standard type  【标准型】 无记号: 基本型 [Standard type] No symbol: Basic type 