





产品型号规格定义

Product Model Specification Definition



BTN350/450/550/650GC/E BLU 低氮燃气燃烧器


技术性能及结构特征

Technical performance and structural characteristics

1. 低氮燃气燃烧器。
 2. 二段渐进式/比例式/电子式运行。
 3. 空气和燃气在燃烧头内混合。
 4. 通过调节燃烧空气和燃烧头，可以获得最佳的燃烧参数。
 5. 铰链式连接，可左右自然打开，维修保养方便。
 6. 用伺服电动机来进行第一、二段最小和最大空气流量调节；燃烧器暂停时，风门关闭以减少炉内热量损失。
 7. GC带有凸轮的伺服电机可以同时调节空气和燃料的供应。GE采用两个伺服电机。
 8. 采用一个法兰和耐高温隔热垫与锅炉联接固定。
 9. 带流量调节装置的燃烧空气进口。
 10. 三相电机带动风机。
 11. 电离电极检测火焰，紫外线光电管检测火焰。
 12. 标准配置的电气防护等级IP40。
1. Low NOx Emission Gas Burner.
 2. Two Stage Progressive/Modulation/Electronic Modulation Operation
 3. Air and gas are mixed in the combustion head.
 4. By adjusting the combustion air and combustion head, the best combustion parameters can be obtained.
 5. Hinged connection, can be opened naturally, easy maintenance.
 6. Use servo motor to adjust the minimum and maximum air flow in the first and second stages; When the burner is suspended, the damper is closed to reduce heat loss in the furnace.
 7. Servo motor with cam could adjust air and fuel supply simultaneously in the GC burner. GE burner adopt 2 servo motors.
 8. A flange and high temperature insulation pad are used to connect the boiler.
 9. Combustion air intake with throttle damper.
 10. 3phase Motor Drives Fan Motor.
 11. Flame detection by ionisation electrode, ultraviolet photocell detects flame.
 12. Standard configuration of electrical protection class IP40.

功率 Power (kW)	型号 Model	订货编号 Article No.	电源 Power supply	电机功率 Motor power (kW)	包装尺寸 package size (L*W*H/mm)	重量 weight (kg)
1200~3600	BTN350GC BLU	203 22 504	380V 50Hz	7.5	1950x1120x1100	250
	BTN350GE BLU	203 22 500				
1500~4450	BTN450GC BLU	203 22 505	380V 50Hz	9.2	1950x1120x1100	250
	BTN450GE BLU	203 22 501				
1800~5250	BTN550GC BLU	203 22 506	380V 50Hz	12	1950x1120x1100	250
	BTN550GE BLU	203 22 502				
2200~6250	BTN650GC BLU	203 22 507	380V 50Hz	15	1950x1120x1100	280
	BTN650GE BLU	203 22 503				

外观尺寸图 Overall dimensions



型 号 model	A1	A2	B1	B2	C	C1	D	E	F	G	H	I	L	M	N
	mm	mm	mm	mm	mm	mm	mm	Φmm	mm	mm	mm	mm	Φmm	M	Φmm
BTN350GC BLU	556	400	519	239	1775	698	534	313	178	DN65	528	400	452	4-M16	350
BTN350GE BLU	556	400	519	335	1775	698	534	313	178	DN65	528	400	452	4-M16	350
BTN450GC BLU	556	400	519	239	1775	698	534	313	178	DN65	528	400	452	4-M16	350
BTN450GE BLU	556	400	519	335	1775	698	534	313	178	DN65	528	400	452	4-M16	350
BTN550GC BLU	583	400	519	239	1775	698	534	313	178	DN65	528	400	452	4-M16	350
BTN550GE BLU	583	400	519	335	1775	698	534	313	178	DN65	528	400	452	4-M16	350
BTN650GC BLU	583	400	519	239	1775	698	534	336	178	DN65	528	400	452	4-M16	350
BTN650GE BLU	583	400	519	335	1775	698	534	336	178	DN65	528	400	452	4-M16	350

BTN350/450/550/650GC/E BLU Low NO_x Gas Burner

baite

备选功能

Alternative function

加长的燃烧筒，可定制60Hz

Longer blast tube and 60HZ motor is customized.

使用LPG燃气时，需在燃烧头上安装该特殊组件

When using LPG gas, this special component is installed on the burner

阀组-与锅炉配套的组件

Valve block - Component for boiler

比例调节功能

Proportional control function

另外订购比例仪RWF40或DC1020与调节组件，燃烧器即可实现比例调节运行。

In addition, order the proportioner RWF40 or DC1020 and the regulating assembly, and the burner can be proportionally regulated.

备注


remark

配有空气关闭装置。

Equipped with air closing device.


曲线图

curve graph




锅炉燃烧器功率(kW)

Burner Output (kW)




锅炉燃烧器功率(kW)

Burner Output (kW)




锅炉燃烧器功率(kW)

Burner Output (kW)



锅炉燃烧器功率(kW)

Burner Output (kW)



BTN350GC/E BLU

天然气 natural gas

曲线 (型号) Curve (model)	阀组编号 Valve group number	检漏 Leakage control	最大压力** Maximum pressure value (mbar)	图号 figure number
① QF-MVD220/5+MVDLE220/5-DN65	222 25 454	-	200	QF2
② QF-DMV-D5065/11-DN65	222 25 128	-	500	QF1
② QF-DMV-D5065/11-LDU-DN65	222 25 145	-	560	QF1
① QF-MB-DLE420 B01 S20-RC2*	222 25 233	-	700	QF4
② QF-VGD40.065-LDU-DN65	222 25 247	GW150A5	700	QF4

BTN450GC/E BLU

天然气 natural gas

曲线 (型号) Curve (model)	阀组编号 Valve group number	检漏 Leakage control	最大压力** Maximum pressure value (mbar)	图号 figure number
① QF-MVD220/5+MVDLE220/5-DN65	222 25 454	-	200	QF2
② QF-DMV-D5065/11-DN65	222 25 128	-	500	QF1
② QF-DMV-D5065/11-LDU-DN65	222 25 145	-	560	QF1
① QF-MB-DLE420 B01 S20-RC2*	222 25 233	-	700	QF4
② QF-VGD40.065-LDU-DN65	222 25 247	GW150A5	700	QF4

BTN550GC/E BLU

天然气 natural gas

曲线 (型号) Curve (model)	阀组编号 Valve group number	检漏 Leakage control	最大压力** Maximum pressure value (mbar)	图号 figure number
① QF-DMV-D5065/11-DN65	222 25 128	-	500	QF1
① QF-DMV-D5065/11-LDU-DN65	222 25 145	GW150A5	500	QF1
① QF-VGD40.065-DN65	222 25 233	-	700	QF4
① QF-VGD40.065-LDU-DN65	222 25 247	GW150A5	700	QF4

BTN650GC/E BLU

天然气 natural gas

曲线 (型号) Curve (model)	阀组编号 Valve group number	检漏 Leakage control	最大压力** Maximum pressure value (mbar)	图号 figure number
① QF-DMV-D5065/11-DN65	222 25 128	-	500	QF1
① QF-DMV-D5065/11-LDU-DN65	222 25 145	GW150A5	500	QF1
① QF-VGD40.065-DN65	222 25 233	-	700	QF4
① QF-VGD40.065-LDU-DN65	222 25 247	GW150A5	700	QF4



浙江百特燃烧器有限公司

ZHEJIANG BAITE BURNERS MANUFACTURE CO., LTD

地址/ADD: 浙江省乐清市象阳工业区百特路2号

NO.2 BAITE RD.XIANGYANG INDUSTRIAL PARK ,YUEQING CITY ,ZHEJIANG PROVINCE

电话/TEL: 0086-577-62655355 62652355

传真/FAX: 0086-577-62653955

服务热线/Hotline:

400 001 5556

网址/Web: www.baite.cn

邮箱/Mail: bt@baite.cn



请用微信扫一扫
进入公司官方网站

© 浙江百特燃烧器有限公司版权所有 2024 珍惜资源，善待环境

本目录所载产品尺寸、规格仅供参考，若有变更，恕不另行通知！以本公司提供的产品为准！

BAITE BURNERS KEEPS THE REVISION RIGHT WITHOUT INFORM IN ADVANCE.INCLUDING THE PRODUCT DIMENSION,SPECIFICATION!