




产品型号规格定义

Product Model Specification Definition



BX210/250GE全预混表面燃烧超低氮燃气燃烧器

技术性能及结构特征

Technical performance and structural characteristics

1. 金属纤维表面燃烧，燃烧均匀。

2. 燃气与空气预先混合。

3. 全预混燃烧，燃烧速度快，火焰短，抑制NOx的生成。

4. NOx排放最低可达到18mg/m³。

5. 电子比例调节运行。

6. 由两个伺服电机分别控制燃气与空气量的配比。

7. 助燃空气带有过滤装置，防止燃烧头长时间运行时造成堵塞。

8. 电离电极检测火焰。

9. 标准配置的电气防护等级IP40。
1. Metal fiber surface burning, burning evenly.

2. Pre-mix gas and air.

3. Full premixed combustion, fast combustion speed, short flame, inhibit Nox generation.

4. The minimum NOx emission can reach 18mg/m3.

5. Single stage operation/electronic proportional adjustment operation.

6. Electronic proportional regulation is controlled by two servo motors respectively to control the ratio of gas and air volume.

7. There has filter device in supporting combustion air .to avoid of block during long time operation in burner head.


8. Flame detection by ionisation electrode.

9. Electric protection rating:IP40.

功率 Power (KW)	型号 Model	订货编号 Article No.	电源 Power supply	电机功率 Motor power (KW)	包装尺寸 package size (L*W*H/mm)	重量 weight (kg)
350 ~ 1410	BX210GE	202 22 114	380V 50Hz	4.5	1030x640x735 1590x520x545	142.5
370 ~ 1750	BX250GE	202 22 116	380V 50Hz	5.5	1030x640x735 1840x520x545	157.5

外观尺寸图

Overall dimensions



型 号 model	A1	A2	B1	B2	C	C1	D	E	F	G	H	I	L	M	N
	mm	mm	mm	mm	mm	mm	mm	φmm	mm	mm	mm	mm	φmm	M	φmm
BX210GE	405	545	428	237	2050	1250	400	185	153	G2"	279	321	290-370	4-M16	225
BX250GE	405	545	428	237	2300	1500	400	185	153	G2"	279	321	290-370	4-M16	225

BX210/250GE Full Premix Surface Combustion Extremely Low NOx Burner



备选功能

Alternative function

加长的燃烧筒，可定制60Hz

Can lengthen the blast tube, Can books the 60Hz.

使用LPG燃气时，需在燃烧头上安装该特殊组件

When using LPG gas, this special component is installed on the burner

阀组-与锅炉配套的组件

Valve block - Component for boiler

比例调节功能


Proportional control function

另外订购比例仪RWF40或DC1020与调节组件，燃烧器即可实现比例调节运行。

In addition, order the proportioner RWF40 or DC1020 and the regulating assembly, and the burner can be proportionally regulated.


曲线图

curve graph



锅炉燃烧器功率(kW)

Boiler Output (kW)




BX210GE

天然气 natural gas

曲线 (型号) Curve (model)	阀组编号 Valve group number	检漏 Leakage control	最大压力** Maximum pressure value (mbar)	图号 figure number
① QF-MVD215/5+MVDLE215/5-PLC-RC2"	222 25 482	GW50A6	200	QF7
② QF-MVD220/5+MVDLE220/5-PLC-RC2"	222 25 485	GW50A6	200	QF7
③ QF-DMV-D520/11-PLC-RC2"	222 25 207	GW50A5	360	QF5
④ QF-DMV-D525/11-PLC-RC2"	222 25 209	GW50A5	360	QF5

锅炉燃烧器功率(kW)

Boiler Output (kW)



BX250GE

天然气 natural gas

曲线 (型号) Curve (model)	阀组编号 Valve group number	检漏 Leakage control	最大压力** Maximum pressure value (mbar)	图号 figure number
① QF-MVD215/5+MVDLE215/5-PLC-RC2"	222 25 482	GW50A6	200	QF7
② QF-MVD220/5+MVDLE220/5-PLC-RC2"	222 25 485	GW50A6	200	QF7
③ QF-DMV-D520/11-PLC-RC2"	222 25 207	GW50A5	360	QF5
④ QF-DMV-D525/11-PLC-RC2"	222 25 209	GW50A5	360	QF5



浙江百特燃烧器有限公司

ZHEJIANG BAITE BURNERS MANUFACTURE CO., LTD

地址/ADD: 浙江省乐清市象阳工业区百特路2号

NO.2 BAITE RD.XIANGYANG INDUSTRIAL PARK ,YUEQING CITY ,ZHEJIANG PROVINCE

电话/TEL: 0086-577-62655355 62652355

传真/FAX: 0086-577-62653955

服务热线/Hotline:

400 001 5556

网址/Web: www.baite.cn

邮箱/Mail: bt@baite.cn



请用微信扫一扫
进入公司官方网站

© 浙江百特燃烧器有限公司版权所有 2024 珍惜资源，善待环境

本目录所载产品尺寸、规格仅供参考，若有变更，恕不另行通知！以本公司提供的产品为准！

BAITE BURNERS KEEPS THE REVISION RIGHT WITHOUT INFORM IN ADVANCE.INCLUDING THE PRODUCT DIMENSION,SPECIFICATION!