



公差表MT5(mm)	
基本尺寸范围	公差值
Basic size	Tolerance value
<3	±0.1
3~10	±0.15
10~24	±0.20
24~65	±0.35
65~140	±0.50
140~250	±0.80
250~450	±1.2
>450	±2.0

技术要求:

- 1、未注圆角及拔模斜度按3D图。
  - 2、未注尺寸公差按右表。
  - 3、表面无飞边，缩水，气泡等缺陷。

\*4、灯具采用胶圈防水时：要求散热器与胶圈的接触面的粗糙度： $R_a < 3.2 \mu\text{m}$

Technical remark:

1. Fillet and inclination not indicated according to 3D drawing.
  2. Dimensional tolerances not indicated are shown in the right list.
  3. The surface has no flash, shrinkage, bubbles and other defects.
  - \*4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required:  $R_a < 3.2\mu m$

2					4				
1					3				
序号 Item	更改标记 Change mark	更改内容 Change content	更改日期 Change date	签名 Signature	序号 Item	更改标记 Change mark	更改内容 Change content	更改日期 Change date	签名 Signature
光学设计 Optical design			Title:  HK 黑光25@13-36度透镜  HK Dark 25@13-36°lens			Drawing No. HK-HG-25@13-36-D4-21-1g-1  Part No. 1.01.92065			
结构设计 Structural design									
审核 Verify									
审定 Approval			材料 Material:	PMMA			CDHK		