




技术要求:
1、未注圆角及拔模斜度按3D图。
2、未注尺寸公差按右表。
3、表面无飞边，缩水，气泡等缺陷。
*4、灯具采用胶圈防水时：要求散热器与胶圈的接触面的粗糙度：Ra<3.2μm

Technical remark:
1.Fillet and inclination not indicated according to 3D drawing.
2. Dimensional tolerances not indicated are shown in the right list.
3. The surface has no flash, shrinkage, bubbles and other defects.
*4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required: Ra<3.2μm

表	
基本尺寸范围	公差值
Basic size	Tolerance value
<3	±0.1
3~10	±0.15
10~24	±0.20
24~65	±0.35
65~140	±0.50
140~250	±0.80
250~450	±1.2
>450	±2.0

出光角度范围		透过率	
Beam angle range		Transmittance	
最小K值		点胶类型	
Min K value		Gel type	
模具等级	见图面	备注	
Mold level	见图面	Remark	

2					4					
1					3					
序号 Item	更改标记 Change mark	更改内容 Change content		更改日期 Change date	签 名 Signature	序号 Item	更改标记 Change mark	更改内容 Change content	更改日期 Change date	签 名 Signature
光学设计 Optical design				Title: HK KA_Pro 35@16-24度透镜 HK KA_Pro 35@16-24° lens			Drawing No. HK-KAP-35@16-24-D6-21-1g-1			
结构设计 Structural design							Part No. 1.01.33935			
审 核 Verify				材 料 Material:	PMMA	CDHK				
审 定 Approval										