




LED基板上表面
Top surface of LED substrate

基本尺寸范围	公差值
Basic size	Tolerance value
<3	±0.1
3~10	±0.15
10~24	±0.20
24~65	±0.35
65~140	±0.50
140~250	±0.80
250~450	±1.2
>450	±2.0

技术要求:
1、未注圆角及拔模斜度按3D图。
2、未注尺寸公差按右表。
3、表面无飞边, 缩水, 气泡等缺陷。
*4、灯具采用胶圈防水时: 要求散热器与胶圈的接触面的粗糙度: Ra<3.2μm

Technical remark:
1.Fillet and inclination not indicated according to 3D drawing.
2. Dimensional tolerances not indicated are shown in the right list.
3. The surface has no flash, shrinkage, bubbles and other defects.
*4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required: Ra<3.2μm

序号 Item	物 料 编 码 Part No.	产 品 名 称 Title		产 品 编 号 Drawing No.		材 料 Material:		数 量 quantity		
①	1.01.44028_01	HK 萤火-星空-10-7合1-80度线性灯透镜_01 HK Firefly-Starry-10-7in1-80° Linear lamp lens_01		HK-YH XK-59@07-1254-0		PMMA		1		
②	1.01.43968_02	HK 萤火-星空-10-7合1-线性灯反光杯_02 HK Firefly-Starry-10-7in1-Linear lamp reflector cup_02		HK-YH XK-59@08-1222-0		PC 镀铝 PC aluminizing		1		
③										
				出光角度范围 Beam angle range		透 过 率 Transmittance				
				最小 K 值 Min K value		点胶类型 Gel type				
				模 具 等 级 Mold level		备 注 Remark				
2					4					
1					3					
序号 Item	更改标记 Change mark	更 改 内 容 Change content		更 改 日 期 Change date	签 名 Signature	序号 Item	更改标记 Change mark	更 改 内 容 Change content	更 改 日 期 Change date	签 名 Signature
光 学 设 计 Optical design				Title: HK 萤火-星空-10-7合1-80度线性灯光学组件 HK Firefly-Starry-10-7in1-80° Linear lamp optical module		Drawing No. HK-YH XK-59@12-80-3030-#0-1g-7_ASM				
结 构 设 计 Structural design						Part No. 1.01.44028				
审 核 Verify						CDHK				
审 定 Approval				材 料 Material:	组 件 component					