



技术要求:
 1、未注圆角及拔模斜度按3D图。
 2、未注尺寸公差按右表。
 3、表面无飞边, 缩水, 气泡等缺陷。
 *4、灯具采用胶圈防水时: 要求散热器与胶圈的接触面的粗糙度: Ra<3.2μm

Technical remark:
 1. Fillet and inclination not indicated according to 3D drawing.
 2. Dimensional tolerances not indicated are shown in the right list.
 3. The surface has no flash, shrinkage, bubbles and other defects.
 *4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required: Ra<3.2μm

表 List	
基本尺寸 Basic size	公差值 Tolerance value
<3	±0.10
3~10	±0.15
10~24	±0.20
24~65	±0.35
65~140	±0.50
140~250	±0.80
250~450	±1.20
>450	±2.00

序号 Item	更改标记 Change mark	更改内容 Change content	更改日期 Change date	签名 Signature	序号 Item	更改标记 Change mark	更改内容 Change content	更改日期 Change date	签名 Signature	
2					4					
1					3					
Title:			Drawing No. HK-WY-30@15-36-D6-21-1g-1			Part No. 1.01.23139				
HK 无影30@15-36度透镜 (D6)			HK Peak 30@15-36 °lens (D6)			图纸数目 Number of drawings		数量 quantity		重量 Weight
审核 Verify			材料 Material:			1		CDHK		
审定 Approval			PMMA							