




技术要求:
1、未注圆角及拔模斜度按3D图。
2、未注尺寸公差按右表。
3、表面无飞边, 缩水, 气泡等缺陷。
*4、灯具采用胶圈防水时: 要求散热器与胶圈的接触面的粗糙度: Ra<3.2μm

Technical remark:
1.Fillet and inclination not indicated according to 3D drawing.
2. Dimensional tolerances not indicated are shown in the right list.
3. The surface has no flash, shrinkage, bubbles and other defects.
*4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required: Ra<3.2μm

基本尺寸		公差值											
Basic size		Tolerance value		2				4					
<3		±0.1		1				3					
3~10		±0.15		序号		更改日期		签 名		序号		更改日期	
10~24		±0.20		Item		Change date		Signature		Item		Change date	
24~65		±0.35		更改内容		更改日期		签 名		更改内容		更改日期	
65~140		±0.50		Change content		Change date		Signature		Change content		Change date	
140~250		±0.80		光学设计		Title:		Drawing No.		HK-JZ-50@07-90-5050-#0-1g-8			
250~450		±1.2		结构设计		HK 矩阵8合1-90度工矿灯透镜		Part No.		1.02.33518			
>450		±2.0		Structural design		HK Matrix 8in1-90°							
				审 核		Mining lamp lens							
				Verify		材料		PC		CDHK			
				Approval		Material:							