



- 技术要求:
- 1、未注圆角及拔模斜度按3D图。
 - 2、未注尺寸公差按右表。
 - 3、表面无飞边，缩水，气泡等缺陷。
 - *4、灯具采用胶圈防水时：要求散热器与胶圈的接触面的粗糙度：Ra<3.2μm

- Technical remark:
- 1.Fillet and inclination not indicated according to 3D drawing.
 2. Dimensional tolerances not indicated are shown in the right list.
 - 3, The surface has no flash, shrinkage, bubbles and other defects.
 - *4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required: Ra<3.2μm

基本尺寸	公差值
Basic size	Tolerance value
<3	±0.1
3~10	±0.15
10~24	±0.20
24~65	±0.35
65~140	±0.50
140~250	±0.80
250~450	±1.2
>450	±2.0

2					4				
1					3				
序号	更改标记	更改内容	更改日期	签名	序号	更改标记	更改内容	更改日期	签名
Item	Change mark	Change content	Change date	Signature	Item	Change mark	Change content	Change date	Signature
光学设计					Title:				
Optical design					HK 黑光45@21透镜支架				
结构设计					HK Dark 45@21 lens holder				
Structural design					Drawing No.				
审核					HK-HG-45@23-0335-S				
Verify					Part No.				
审定					1.07.91892				
Approval					CDHK				
材料			PC 白色 (PC White)						
Material:			PC White (PC White)						