



- 技术要求:
- 1、未注圆角及拔模斜度按3D图。
 - 2、未注尺寸公差按右表。
 - 3、表面无飞边，缩水，气泡等缺陷。
 - *4、灯具采用胶圈防水时：要求散热器与胶圈的接触面的粗糙度：Ra<3.2μm

- Technical remark:
- 1.Fillet and inclination not indicated according to 3D drawing.
 2. Dimensional tolerances not indicated are shown in the right list.
 - 3, The surface has no flash, shrinkage, bubbles and other defects.
 - *4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required: Ra<3.2μm

基本尺寸	公差值
Basic size	Tolerance value
<3	±0.1
3~10	±0.15
10~24	±0.20
24~65	±0.35
65~140	±0.50
140~250	±0.80
250~450	±1.2
>450	±2.0

2					4				
1					3				
序号	更改标记	更改内容	更改日期	签名	序号	更改标记	更改内容	更改日期	签名
Item	Change mark	Change content	Change date	Signature	Item	Change mark	Change content	Change date	Signature
光学设计 Optical design					Title:				
结构设计 Structural design					HK 黑光45@21透镜支架 HK Dark 45@21 lens holder				
审核 Verify					Drawing No. HK-HG-45@23-0335-S-H				
审定 Approval					Part No. 1.07.91892H				
					材料 Material: PC 黑色(PC Black)				
					CDHK				