




技术要求:
1、未注圆角及拔模斜度按3D图。
2、未注尺寸公差按右表。
3、表面无飞边，缩水，气泡等缺陷。
*4、灯具采用胶圈防水时：要求散热器与胶圈的接触面的粗糙度：Ra<3.2μm

Technical remark:
1.Fillet and inclination not indicated according to 3D drawing.
2. Dimensional tolerances not indicated are shown in the right list.
3. The surface has no flash, shrinkage, bubbles and other defects.
*4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required: Ra<3.2μm

表	
基本尺寸范围	公差值
Basic size	Tolerance value
<3	±0.1
3~10	±0.15
10~24	±0.20
24~65	±0.35
65~140	±0.50
140~250	±0.80
250~450	±1.2
>450	±2.0

序号 Item	物 料 编 码 Part No.	产 品 名 称 Title	产 品 编 号 Drawing No.	材 料 Material:	数 量 quantity				
①	1.07.33501_01	HK 黑光D30防眩罩3_01	HK-HG-50@14-0965-S	PC 电镀	1				
②	1.07.33501_02	HK 黑光D30防眩罩3反射部件_02	HK-HG-33@13-0966-S	PC 镀铝（无底）	1				
③	1.07.33501_03	HK 黑光D30洗墙片1	HK-HG-30@02-0967-O	PC	1				
装配图			出光角度范围 Beam angle range	透 过 率 Transmittance					
			最小K值 Min K value	点胶类型 Gel type					
			模 具 等 级 Mold level	备 注 Remark					
			见附图						
2			4						
1			3						
序号 Item	更改标记 Change mark	更改内容 Change content	更改日期 Change date	签 名 Signature	序号 Item	更改标记 Change mark	更改内容 Change content	更改日期 Change date	签 名 Signature
光 学 设 计 Optical design			Title: HK 黑光D30防眩罩3			Drawing No. HK-HG-50@14-0965-S_ASM			
结 构 设 计 Structural design						Part No. 1.07.33501 S			
审 核 Verify						CDHK			
审 定 Approval			材 料 Material:	组件					