



透镜上表面(防眩角30度(不偏转))  
On the surface of the lens  
(Anti glare angle 30 degrees)  
(No deflection))

技术要求:

- 1、未注圆角及拔模斜度按3D图。
- 2、未注尺寸公差按右表。
- 3、表面无飞边，缩水，气泡等缺陷。
- \*4、灯具采用胶圈防水时：要求散热器与胶圈的接触面的粗糙度：Ra<3.2μm

Technical remark:

- 1.Fillet and inclination not indicated according to 3D drawing.
2. Dimensional tolerances not indicated are shown in the right list.
3. The surface has no flash, shrinkage, bubbles and other defects.
- \*4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required: Ra<3.2μm

基本尺寸范围	公差值
Basic size	Tolerance value
<3	±0.1
3~10	±0.15
10~24	±0.20
24~65	±0.35
65~140	±0.50
140~250	±0.80
250~450	±1.2
>450	±2.0

序号 Item	物料编码 Part No.	产品名称 Title	产品编号 Drawing No.	材料 Material:	数量 quantity
①	1.07.23295_01	HK 黑光D35防眩罩_01	HK-HG-50@16-0886-S	PC 电镀	1
②	1.07.23295_02	HK 黑光D35防眩罩13反射部件_02	HK-HG-38@14-0887-O	PC 电镀	1
③	1.07.23295_03	HK 黑光D35洗墙片A	HK-HG-35@02-0888-O	PC	1

装配图		出光角度范围 Beam angle range	透过率 Transmittance
2	4	最小K值 Min K value	点胶类型 Gel type
1	3	模具等级 Mold level	备注 Remark
		见视图	

序号 Item	更改标记 Change mark	更改内容 Change content	更改日期 Change date	签名 Signature	序号 Item	更改标记 Change mark	更改内容 Change content	更改日期 Change date	签名 Signature
光学设计 Optical design					Title:				
结构设计 Structural design					HK 黑光D35防眩罩13_A				
审核 Verify					Drawing No. HK-HG-50@16-0886-S_ASM_A				
审定 Approval					Part No. 1.07.23295_A				
材料 Material:			组件		CDHK				