




技术要求:
1、未注圆角及拔模斜度按3D图。
2、未注尺寸公差按右表。
3、表面无飞边, 缩水, 气泡等缺陷。
*4、灯具采用胶圈防水时: 要求散热器与胶圈的接触面的粗糙度: Ra<3.2μm

Technical remark:
1.Fillet and inclination not indicated according to 3D drawing.
2. Dimensional tolerances not indicated are shown in the right list.
3. The surface has no flash, shrinkage, bubbles and other defects.
*4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required: Ra<3.2μm

表 List	
基本尺寸范围	公差值
Basic size	Tolerance value
<3	±0.1
3~10	±0.15
10~24	±0.20
24~65	±0.35
65~140	±0.50
140~250	±0.80
250~450	±1.2
>450	±2.0

				出光角度范围 Beam angle range				透 过 率 Transmittance			
				最小 K 值 Min K value				点胶类型 Gel type			
				模 具 等 级 Mold level		见 图 面		备 注 Remark			
2						4					
1						3					
序号 Item	更改标记 Change mark	更改内容 Change content		更改日期 Change date	签 名 Signature	序号 Item	更改标记 Change mark	更改内容 Change content		更改日期 Change date	签 名 Signature
光学设计 Optical design				Title: HK 萤火-星空-30G-2合1线性灯格栅 HK Firefly-Starry-30G-2in1-Linear lamp grille			Drawing No. HK-YH XK-60@13-1089-0				
结构设计 Structural design							Part No. 1.07.33787				
审 核 Verify											
审 定 Approval				材料 Material:	PC 黑色 (black)			CDHK			