



注意：该透镜靠安装边定上下位置（底部悬空）

技术要求：

- 1、未注圆角及拔模斜度按3D图。
- 2、未注尺寸公差按右表。
- 3、表面无飞边，缩水，气泡等缺陷。
- *4、灯具采用胶圈防水时：要求散热器与胶圈的接触面的粗糙度：Ra<3.2μm

Technical remark:

- 1.Fillet and inclination not indicated according to 3D drawing.
2. Dimensional tolerances not indicated are shown in the right list.
3. The surface has no flash, shrinkage, bubbles and other defects.
- *4. When the lamp adopts rubber ring for waterproofing: the roughness of the contact surface between the radiator and the rubber ring is required: Ra<3.2μm

基本尺寸	公差值
Basic size	Tolerance value
<3	±0.1
3~10	±0.15
10~24	±0.20
24~65	±0.35
65~140	±0.50
140~250	±0.80
250~450	±1.2
>450	±2.0

序号	更改标记	更改内容	更改日期	签名	序号	更改标记	更改内容	更改日期	签名
Item	Change mark	Change content	Change date	Signature	Item	Change mark	Change content	Change date	Signature
2					4				
1					3				
光学设计 Optical design					Title:				
结构设计 Structural design					HK 光子 35@10-单偏洗墙透镜 HK Photon 35@10- Unilateralism Wall-washing lens				
审核 Verify					Drawing No.				
审定 Approval					HK-GZ-35@10-30X40-D6-02-1g-1 Part No.				
					1.01.23460				
					CDHK				
					材料 Material: PC				

出光角度范围	透过率
Beam angle range	Transmittance
最小K值	点胶类型
Min K value	Gel type
模具等级	备注
Mold level	Remark