

www.xcmg.com

XGC260履带起重机

XGC260 CRAWLER CRANE

徐工集团工程机械股份有限公司

XCMG CONSTRUCTION MACHINERY CO.,LTD.

地址(Add): 中国江苏省徐州市金山桥经济开发区桃山路19号 邮编(Post Code): 221001
No.19 Taoshan Road, Economic development zone of jinshanqiao,Xuzhou,Jiangsu Province,China
销售电话(Sale Tel): 86 0516-87892094 销售传真(Sale Fax): 86 0516-87892015
服务电话(Service Tel): 86 400-001-5678 服务传真(Service Fax): 86 0516-87892080
备件电话(Service Tel): 86 0516-87892086 备件传真(Service Fax): 86 0516-87892083
服务质量投诉电话(Quality Supervision Tel): 86 0516-87892587
统一服务热线(Unified service hotline): 86 400-110-9999



XGC260 履带起重机

XGC260 CRAWLER CRANE



技术性能参数/整机基本尺寸
Technical Specification/Overall Dimension

主要零部件
Main Parts

目 录 CONTENTS

技性能参数/整机基本尺寸
Technical Specification/Overall Dimension

主要零部件
Main Parts

详细介绍
Brief Introduction

完全自拆装功能
Self-Assembly/Disassembly

主臂工况工作范围图
Boom Working Area Diagram

主臂工况臂节组合
Boom Combinations

主臂工况起臂表
Boom Raising Table

主臂工况(HB)载荷表
Boom (HB) Lifting Load Chart

主臂臂端单滑轮工况工作范围图
Boom Head Single Top Working Area Diagram

主臂臂端单滑轮工况臂节组合
Boom Combinations for Boom Head Single Top

主臂臂端单滑轮工况起臂表
Boom Raising Table for Boom Head Single Top

主臂臂端单滑轮工况(HBS)载荷表
Boom Head Single Top (HBS) Lifting Load Chart

轻型主臂工况工作范围图
Light Boom Working Area

轻型主臂工况起臂表
Light Boom Raising Table

轻型主臂工况臂节组合
Light Boom Combinations

轻型主臂工况(LB)载荷表
Light Boom (LB) Lifting Load Chart

固定副臂工况工作范围图
Fixed Jib Working Area Diagram

固定副臂工况臂节组合
Fixed Jib Combinations

固定副臂工况起臂表
Fixed Jib Raising Table

固定副臂工况(HF)载荷表
Fixed Jib (HF) Lifting Load Chart

盾构工况工作范围图
TBM Working Area Diagram

盾构工况臂节组合
TBM Boom Combinations

盾构工况起臂表
TBM Boom Raising Table

盾构工况(HBF)载荷表
TBM (HBF) Lifting Load Chart

盾构工况(HBF)主副钩复合吊装载荷表
TBM Combination

塔式工况工作范围图
Tower Jib Working Area Diagram


塔式工况臂节组合
Tower Jib Combinations

塔式工况起臂表
Tower Jib Raising Table


塔式工况(HW)载荷表
Tower Jib (HW) Lifting Load Chart

项目Items	单位Unit	数值Data	
		进口配置	国产配置
主臂工况 Boom	t	260	
轻型主臂工况 Light-duty boom	t	85	
最大额定起重量 Max. lifting capacity	塔式副臂工况 Tower jib	95	
	固定副臂工况 Fixed jib	105	
	盾构工况(双钩交替复合)TBM (with auxiliary hook block)	150.2	
	主臂臂端单滑轮工况 Boom single top	28	
最大起重力矩 Max. load moment		1450	
	主臂长度 Boom length	24~93	
尺寸参数 Max. load moment	轻型主臂长度 Light-duty boom length	67.5~100.5	
	主臂变幅角度 Boom luffing angle	-3~85	
	塔式副臂长度 Tower jib lengt	24~66	
	塔臂变幅角度 Tower jib luffing angle	20~75	
	固定副臂长度 Fixed jib length	9、12~36	
	主臂与固定副臂夹角 Angle between boom and fixed jib	10、30	
	主臂臂端单滑轮长度 boom single pulley arm length	1.8	
	起升机构最大单绳速度 Host winch max. single line speed	103	108
速度参数 Max. load moment	主臂变幅机构最大单绳速度 Boom luffing winch max. single line speed	2×42	2×42.5
	塔臂变幅机构最大单绳速度 Tower jib luffing winch max. single line speed	129	135
	最大回转速度 Max. slewing speed	1.1	1.1
	最高行驶速度 Max. travel speed	1.1	1.2
发动机 Max. load moment	发动机型号 Model	-	康明斯QSL9 潍柴WP10.336N
	发动机额定功率及转速 Rated output power and speed	kW/rpm	242/2100 247/1900
	排放标准 Emission standard	-	欧 III 国 III
	整机质量(含260吨钩、H824、转台配重)Total mass (with 260t hook, H824, turntable ballast 80t)	t	239
	平均接地比压 Mean ground pressure	MPa	0.116
	爬坡能力 Grade-ability	%	30
	车身配重 Car-body counterweight	t	30
	转台配重 (可选装, 可独立使用(选配重量表)) Turntable counterweight(option, with independent load chart)	t	80、90、100三种选一
	运输状态单件最大质量 Max. mass of single unit in transport state	t	43.0 (若拆解可小于35.7)
	运输状态单件(转台)最大尺寸 (长×宽×高) Max. dimension of single unit (turntable) in transport state (L×W×H)	m	13.2×3.0×3.2


注: 1. 钢丝绳速指卷筒最外工作层, 发动机空载转动时的计算值, 会依载荷与操作条件不同而变化。
2. 行走速度与回转速度是基于水平光滑坚实地面, 机重239t的理论计算值。
3. 除特别说明, 此表基于100t转台配重、30t车身配重的全臂架配置参数。
4. 本公司保留对技术参数的更新更改权, 如有变更恕不另行通知。



本印刷品所包含的数据, 会随着产品的不断升级而改变, 请以实际产品为准
Pictures and data in this catalog will change with the update and modification of products,
so please take the actual vehicle as reference.



主机运输方案A Basic machine transport plan I ×1	
长L	13.20m
宽W	3.00m
高H	3.25m
重量Weight	41.70t



主机运输方案B Basic machine transport plan II ×1	
长L	11.10m
宽W	3.00m
高H	3.20m
重量Weight	35.70t



桅杆单独运输部件 Mast transport parts ×1	
长L	10.30m
宽W	2.20m
高H	1.42m
重量Weight	7.50t



左履带梁 Left track frame ×1	
长L	9.55m
宽W	1.45m
高H	1.35m
重量Weight	22.00t



右履带梁 Right track frame ×1	
长L	9.55m
宽W	1.45m
高H	1.35m
重量Weight	22.00t







车身配重块 I Car-body counterweight I ×2	
长L	5.60m
宽W	1.63m
高H	0.72m
重量Weight	15.00t








转台配重托盘 Turntable counterweight tray ×1	
长L	6.90m
宽W	2.38m
高H	0.57m
重量Weight	10.00t







主要零部件
Main Parts

	转台配重块I Turntable counterweight I ×6 长L 2.10m 宽W 2.38m 高H 0.58m 重量Weight 10.00t
	转台配重块II Turntable counterweight I ×6 长L 2.10m 宽W 2.38m 高H 0.40m 重量Weight 5.00t
	主臂底节 Boom base ×1 长L 11.25m 宽W 2.77m 高H 2.95m 重量Weight 13.00t
	主臂3m节 Boom 6m insert ×1 长L 3.18m 宽W 2.77m 高H 2.45m 重量Weight 1.20t
	主臂6m节 Boom 6m insert ×1 长L 6.18m 宽W 2.77m 高H 2.45m 重量Weight 1.90t
	主臂12mA节 Boom 12mA insert ×3 长L 12.18m 宽W 2.77m 高H 2.45m 重量Weight 3.50t
	主臂12mB节 Boom 12mB insert ×2 长L 12.18m 宽W 2.77m 高H 2.45m 重量Weight 3.00t







主要零部件
Main Parts

	主臂变径节及连接节 Boom tapered section and connection section ×1 长L 14.75m 宽W 2.77m 高H 3.15m 重量Weight 6.50t
	主臂滑轮组 Boom sheave block ×1 长L 1.68m 宽W 1.35m 高H 0.96m 重量Weight 1.00t
	主臂臂端单滑轮 Boom single top ×1 长L 2.40m 宽W 1.20m 高H 1.05m 重量Weight 0.40t
	塔臂三件套 Tower jib 3-part assembly ×1 长L 10.81m 宽W 2.78m 高H 3.19m 重量Weight 6.60t
	塔臂6mA节 Tower jib 6mA insert ×1 长L 6.18m 宽W 2.15m 高H 1.95m 重量Weight 1.30t
	塔臂6mB节 Tower jib 6mB insert ×1 长L 6.18m 宽W 2.15m 高H 1.95m 重量Weight 1.10t
	塔臂12m节 Tower jib 12m insert ×3 长L 12.18m 宽W 2.15m 高H 1.95m 重量Weight 1.90t

主要零部件
Main Parts

	塔臂顶节 Tower jib top	×1
	长L	9.57m
	宽W	2.15m
	高H	2.25m
	重量Weight	2.20t
	起臂小车 Boom trolley	×1
	长L	1.25m
	宽W	1.15m
	高H	0.70m
	重量Weight	0.20t
	固定副臂基本臂(9m) Fixed jib base	×1
	长L	10.73m
	宽W	2.77m
	高H	2.95m
	重量Weight	3.70t
	固定副臂3m节 Fixed jib 3m insert	×1
	长L	3.18m
	宽W	1.51m
	高H	1.45m
	重量Weight	0.50t
	固定副臂6m节 Fixed jib 6m insert	×2
	长L	6.18m
	宽W	1.51m
	高H	1.45m
	重量Weight	0.80t
	固定副臂12m节 Fixed jib 12m insert	×1
	长L	12.18m
	宽W	1.51m
	高H	1.45m
	重量Weight	1.50t
	下车走台 Undercarriage catwalk	×2
	长L	3.64m
	宽W	0.97m
	高H	0.28m
	重量Weight	0.14t


主要零部件
Main Parts

	260t起重钩总成 (选配) 260t Hook block	×1
	长L	1.07m
	宽W	1.07m
	高H	2.35m
	重量Weight	4.60t
	200t起重钩总成 200t Hook block	×1
	长L	0.95m
	宽W	0.99m
	高H	2.25m
	重量Weight	4.20t
	160t起重钩总成 (选配) 160t Hook block	×1
	长L	0.85m
	宽W	0.87m
	高H	2.12m
	重量Weight	3.90t
	100t起重钩总成 100t Hook block	×1
	长L	0.76m
	宽W	0.71m
	高H	1.90m
	重量Weight	3.10t
	50t起重钩总成 (选配) 50t Hook block	×1
	长L	0.76m
	宽W	0.64m
	高H	1.85m
	重量Weight	2.50t
	16t起重钩总成 16t Hook block	×1
	长L	0.60m
	宽W	0.60m
	高H	0.87m
	重量Weight	0.90t

说 明 Notes

- 以上零部件运输形状为示意图，所标尺寸为设计值，不包括包装。
The above parts dimension is only for illustration, the dimension shown is design value, and does not include the package.
- 重量为设计值，由于制造误差，可能稍有不同。
The weight is design value, may have slight difference due to error in manufacture.

详细介绍 Detailed Introduction



上 车

发动机

XGC260采用康明斯QSL9_242kW/2100rpm或潍柴WP10.336N_247 kW/1900rpm，直列、六缸、水冷、增压中冷、电喷、四冲程环保型柴油发动机，符合欧Ⅲ排放标准或国Ⅳ排放标准。
燃料箱容量：650L。

控制系统

智能化计算机集成式可编程控制系统，采用PLC可编程控制器，并与常规电气相结合，完成系统的逻辑控制与液压比例先导控制功能，实现起重机的智能控制；控制器、显示器、发动机和力矩限制器之间采用CAN-Bus进行数据传送，大大提高起重机的作业安全性、可靠性和作业效率。大屏幕显示起重机作业参数及发动机相关参数，可方便的实现人机对话。

液压系统

液压系统由主油路、控制油路、辅助油路组成，使用液压比例先导控制，实现与负载无关的流量分配，速度精准，系统稳定、操作灵敏，微动性好。主起升、副起升、主臂变幅、行走等为开式液压系统，主起升、副起升具有双泵合流功能。回转采用闭式液压系统，无须平衡阀和换向阀即可实现传动平稳无冲击。

液泵泵：变量柱塞泵。
主控制阀：先导液比例控制阀。
主回路控制方式：恒功率阀控系统。
辅助机构控制系统：电磁多路换向阀组。
支腿控制：电控盒操纵的电磁多路换向阀组。
回油过滤器：先导油路精密过滤器。
冷却器：液压马达驱动的铝制散热器。
支腿控制：电控盒操纵的电磁多路换向阀组。
溢流阀：有效防止整个系统或局部系统即使处于过载状态，系统液压系统压力：35MPa。
液压油箱容积：850L。

起升机构

起升机构包括主起升机构和副起升机构，安装在主臂底节臂靠近根部上端处。

主起升、副起升机构由变量马达驱动行星齿轮减速机，通过卷筒及变幅滑轮组实现主钩或副钩起升下降，通过双泵供油功能提高主起升、副起升机构升降速度。

主起升、副起升机构内置行星减速机，采用负制动设计多片湿式叠片式常闭制动器，实现“弹簧制动/液压释放”功能。

起升卷筒采用吸振性良好的球墨铸铁制造，双折线绳槽保证钢丝绳多层卷绕不乱绳，有效地延长了钢丝绳的使用寿命。

主起升机构使用独立钢芯、高破断拉力、高抗挤压性的左旋同向捻抗旋转特种钢丝绳，额定单绳拉力16.7t，钢丝绳直径φ28mm，长度500m。

副起升机构亦采用独立钢芯、高破断拉力、高抗挤压性的抗旋转特种钢丝绳，额定单绳拉力14.8t，钢丝绳直径φ26mm，长度300m。



Crane Superstructure

Engine

XGC260 uses Cummins QSL 9 engine, 242kW/2100rpm; or Weifang Diesel WP10.336N engine, 247kW/1900rpm; six-cylinder in line, water-cooled, turbocharged, electronic injection, diesel engine, omply with Euro III standard or China GB IV standard..
Fuel tank capacity: 650L.

Control System

Intelligent computer integrated programmable control system. PLC programmable controller is used, in combination with conventional electrics, to realize logic control and hydraulic proportional pilot control of the system; CAN-Bus is used for data communication in controller, display, engine and LMI, greatly improve the safety, reliability and efficiency for crane operation. Crane operation data and engine data can be displayed by a larger screen, easy for man-machine interaction.

Hydraulic System

Hydraulic system consists of main circuit, control circuit, and auxiliary circuit, use of hydraulic proportional pilot control to achieve load-independent flow distribution, with accurate velocity, stable system, sensitive operation, and good fine motion.

Main winch, auxiliary winch, boom luffing, crane travel is the open type hydraulic system, and main winch and auxiliary winch has a double- pump combined flow function. Slewing system is closed type hydraulic system, can be realized non- vibration smooth power drive without balance valve and direction change valve.

Hydraulic pump: variable piston pump;
Main control valve: pilot hydraulic proportional control valve;
Main circuit control mode: constant power valve control system;
Auxiliary mechanism control system: solenoid multi-way valve block;
Outtrigger control: solenoid multi-way valve block operated by electric control box;
Return oil filter: pilot circuit precision filter;
Cooler: hydraulic motor driven aluminum radiator;
Overflow valve: not only effectively protect the entire system or partial system even if it is in overload condition.
Hydraulic system pressure: 35MPa;
Hydraulic oil tank capacity: 850L.

Winch System

Hoist winch includes main hoist winch and auxiliary hoist winch, witch are installed near boom base upper root.

Main/auxiliary hoist winch consists of planetary reducer driven by variable motor, through drum and luffing pulley block to achieve main or auxiliary hook block hoisting up/down, and through double-pump oil supply to improve main or auxiliary winch hoisting speed.

Main/auxiliary hoist winch has built-in planetary reducer, with negative brake design of multi-plate wet-type laminated constant closed brake, to achieve “spring braking/hydraulic release” function.

Hoist winch drum is made of ductile iron with double line multilayer winding, with good vibration absorption, to ensure rope rotation- resistance for multilayer rope winding, effectively increasing the wire rope service life.

Main hoist winch adopts separate steel core, high breaking force and high anti-extrusion of L-turn special anti-rotation wire rope, rated single line pull 16.7t, rope diameter φ28mm, rope length 500m.

Auxiliary hoist winch adopts separate steel core, high breaking force and high anti-extrusion of L-turn special anti-rotation wire rope, rated single line pull 14.8t, rope diameter φ26mm, rope length 300m.

详细介绍 Detailed Introduction

变幅机构

变幅机构包括主变幅机构和塔臂变幅机构。

主变幅机构由定量液压马达驱动行星齿轮减速机，通过卷筒及变幅滑轮组来实现主臂变幅，通过双泵供油能够提高变幅升降速度。

主变幅机构内置行星减速机，采用负制动设计多片湿式叠片式常闭制动器，实现“弹簧制动/液压释放”功能。

主变幅卷筒采用球墨铸铁制造的双折线多层卷绕双联卷筒，具有良好的吸振性，可保证钢丝绳多层卷绕不乱绳，有效地延长了钢丝绳的使用寿命。主臂变幅机构为双马达双减速机双出绳结构的卷筒驱动，卷筒中间配有铸造棘轮，由液压油缸驱动棘爪，实现多重锁定保护。

主变幅机构采用独立钢芯、高破断拉力、结构稳定性极佳的左旋交互捻非抗旋转特种钢丝绳，额定单绳拉力2×14.8t，钢丝绳直径φ26mm，长度400m。

塔臂变幅机构与副起升机构为同一装置，通过功能切换实现塔臂变幅。

回转机构

回转机构与回转支承采用外啮合方式驱动，共2套，布置在转台前部，由定量马达驱动行星齿轮减速机通过小齿轮驱动回转支承，实现360°回转。

回转机构内置行星减速机，采用负制动设计的多片湿式叠片式常闭制动器，以实现“弹簧制动/液压释放”功能，确保回转具有极高的制动安全性。回转机构还设有机械式回转锁定装置，以实现回转机构的锁定保护。

回转机构具有自由回转功能，保证起重物起吊时，当起重钩即使不在被吊重物的重心垂直中心线上，也可以消除臂架的侧向力，进而防止作业臂因受到较大侧向力而损坏。

最高回转速度：1.1r/min。

回转支承

采用三排滚柱式齿齿外啮合回转支承或椭圆滚道双列球式回转支承，强度高、承载力矩大，精度高、寿命长、维修保养方便。

操纵室

操纵室采用钢制框架结构，正面配置有整体式夹层玻璃，其余玻璃均为钢化玻璃。装有可调式座椅、按人机工程学布置的全套操纵仪表和控制装置，配置冷暖空调、音响、灭火装置、闭路监视系统等，宽敞舒适。工作时，操纵室可调整俯仰角度20°，扩大视野，方便操作；运输时，操纵室还可以从侧方转到前方转动90°放置在转台前，减小运输宽度。

转台

转台是联系上下车的关键承载结构件，采用高强度钢板焊接而成的双侧“工”字梁箱框式复合结构，通过回转支承与下车进行联接，整体强度高、稳定性好。驾驶室、主变幅机构、发动机系统、主泵、液控阀、电控柜、桅杆、主臂底节、上车配重及其自拆装的顶升油缸等分别与转台在不同部位进行联接。

Luffing Gear

Luffing winch includes main luffing winch and tower jib luffing winch.

Main luffing winch consists of planetary reducer driven by constant motor, through drum and luffing pulley block to achieve boom luffing, and through double-pump oil supply to improve boom luffing speed.

Main luffing winch has built-in planetary reducer, with negative brake design of multi-plate wet-type laminated constant closed brake, to achieve “spring braking/hydraulic release” function.

Main luffing winch drum is made of ductile iron with double line multilayer winding, with good vibration absorption, to ensure rope rotation- resistance for multilayer rope winding, effectively increasing the wire rope service life. Boom luffing winch is dual-motor dual-reducer dual-rope structure driven by rope drum, with a casting ratchet pawl in the middle, and driven by a hydraulic cylinder, to achieve multi-lock protection.

Main luffing winch adopts separate steel core, high breaking force and high anti-extrusion of L-turn special anti-rotation wire rope, rated single line pull 2×14.8t, rope diameter φ26mm, rope length 400m.

Tower jib luffing winch is the same device as the auxiliary hoist winch, through the function switch-over to achieve tower jib luffing.

Slewing Gear

Slewing unit and slewing ring is driven by external meshing of two sets gear bearings, arranged in front of turntable, through a planetary reducer driving a constant motor via pinion to drive slewing ring, so as to achieve 360° rotation.

Slewing unit has a built-in planetary reducer, with negative brake design of multi-plate wet-type laminated constant closed brake, to achieve “spring braking/hydraulic release” function, to ensure a high safety brake. Slewing unit also has a mechanical locking device for locking protection of the slewing unit.

Slewing unit has a free-swing function to ensure a lifting load aligned to the center line of gravity center even when lifting hook is not in the center of vertical center line, and also to eliminate the side load force on the boom, so as to prevent the boom from damage due to a large side loading force.

The max. slewing speed: 1.1r/min.

Slewing Ring

Three-row roller spur internal meshed slewing ring or elliptical outer track double-row ball type slewing ring, with high strength, heavy load moment, high precision, long service life, and easy maintenance

Operator's cab

Operator's cab is steel frame structure, the front is provided with overall sandwich glass, other glass is all hardened glass, equipped with adjustable seat, ergonomic designed instruments and control devices, air-conditioner, CD player, fire extinguisher, closed circuit monitor and etc., spacious and comfortable. When crane is in work, the cab angle can be adjusted upward to 20°, to enlarge the view field; when crane is in transport, the cab can be turned 90° from side to front in order to reduce the transport width.

Turntable

Turntable is a key load bearing structure to connect superstructure and undercarriage, use of high-strength steel plate welded in “工” box-type composite box beam on both sides, through slewing ring coupled with undercarriage, with good overall strength and stability. Cab, main luffing winch, engine system, main pump, hydraulic valve, cabinet, mast, boom base, superstructure counterweight and self-assembly/ disassembly jacking cylinder can be respectively connected with different parts of the turntable.

详细介绍

Detailed Introduction

桅杆

桅杆由箱形双肢结构组成，两肢之间有加强横梁，稳定性好。桅杆顶升油缸可绕油缸中间与转台连接铰点旋转，进行桅杆扳起顶升和降落。桅杆上配有桅杆吊自拆装油缸，用来拆装整机的大型结构件，实现臂架、履带梁、主臂根节、配重块的自拆装等。

桅杆长度9.5m。

 下车

下车包括车架、支腿、履带行走装置和车身配重等。车架和履带行走装置之间采用液压油缸驱动的动力销轴连接；车身配重安装在左履带行走和右履带行走装置上；四个支腿及油缸安装在车架的前后两端。此外下车车架还有回转支承安装连接固定螺孔及中央回转体转接固定架，用以固定中心回转体。

车架

车架采用高强度钢板焊并经精密机加工的箱型放射型结构件，可确保回转支承安装面与回转支承的正确安装。该车架整体刚性好、强度大、精度高。为便于将履带架固定在车架上，本机配有液压动力销，可保证车架上的四个垫块销轴和耳轴挂钩与履带架的精准定位。

车架附属件包括支腿(含支脚盘)及顶升油缸，通过销轴铰接于车架外侧用于起重机的拆装，以便于装配和拆卸履带架。支腿油缸通过遥控盒操控。

履带装置

履带行走装置分为左履带行走装置和右履带行走装置，由履带架、履带板、支重轮、驱动轮、导向轮、托链轮及行走机构、张紧装置等结构件组成。

履带架：左右对称，各1件。采用高强度钢板焊接的箱型结构，与车架安装定位设有平行垫铁，起导向和耐磨作用。

驱动轮：高强度耐磨热处理合金铸钢件，轮径900mm，共2×1=2件。履带驱动轮组件用高强度螺栓连接在行星减速机的外壳上，组成内置液压牵引马达的一部分，马达旋转部分与非旋转部分采用浮动式密封。

支重轮：高强度耐磨热处理合金铸钢件，轮径360mm，共2×13=26件。支重轮采用双法兰设计，内置浮动式密封，终生润滑免维护。

张紧轮：高强度耐磨热处理合金铸钢件，轮径900mm，共2×1=2件。安装带有润滑浮动密封的铜质衬套，润滑耐磨优良。通过液压油千斤顶和调整垫板种类数量，能够调节履带张紧程度，使履带保持最佳工作状态。

拖链轮：高强度耐磨热处理合金铸钢件，轮径280mm，共2×2=4件。拖链轮内置浮动密封，终生润滑免维护。

履带板：履带板宽度1200mm，共2×62=124件。高强度耐磨热处理合金铸钢件，内部空腔带筋，自清洁。履带板之间通过浮动销实现多个履带板铰接闭合。

Mast

Mast is a box-type two-limb structure, with strengthened beam between two limbs for good stability. Mast lifting cylinder can rotate around the cylinder center and turntable connection pivot, to realize mast erection raising and lowering. Mast with mast derrick self-assembly/disassembly cylinder is used for assembly/disassembly of basic machine large structure, and self-assembly/ disassembly of boom, track frame, boom root section, and counterweight slab.

Mast length 9.5m.

 Undercarriage

Undercarriage consists of car-body, outrigger, crawler travel unit, car-body counterweight and so on. Hydraulic cylinder driven power pinning connection is used between car-body and crawler travel unit; car-body counterweight is mounted on left/right crawler travel unit; four outriggers and cylinders are mounted on car-body front/rear ends; Also undercarriage car-body has slewing ring connection holes and central rotary joint bracket for fixing the central rotary joint.

Car-body

Car-body is made of high strength steel and welded in box-type radial structure with precision machining, to ensure a correct mounting surface for slewing ring installation. Car-body has good overall rigidity, high strength, and high precision. In order to facilitate track frame fixing on the car-body, this machine is equipped with hydraulic power pinning device, to ensure precise positioning of four car-body pads on track frame via pins and lug hooks.

Car-body accessories include outrigger (with outrigger pad) and jack-up cylinder, through pin shaft hinged to car-body outside to facilitate track frame assembly and disassembly. Outrigger cylinder can be controlled by remote control box.

Track frame

Crawler travel unit is divided into left/right crawler travel unit, consists of track frame, track shoe, track roller, drive sprocket, guide roller, idle roller, and travel device and tension device.

Track frame: symmetrically arranged, each one, made of high-strength steel plate welded in box- type structure, and a parallel iron is set for car-body installation positioning to play a role of guidance and wear.

Drive roller: high-strength heat resistant alloy steel casting, roller diameter 900mm, total 2×1=2 pieces. Drive roller assy. is connected on planetary reducer housing with high-strength bolts, composed as part of the built-in hydraulic traction motor, and motor rotation part and non-rotation part have floating seals.

Track roller: high-strength wear-resistant heat- treated alloy steel casting, roller diameter 360mm, total 2×13=26 pieces. Track roller is double-flange design, with built-in floating seals for lifetime lubrication and maintenance-free.

Tension roller: high-strength wear-resistant heat-treated alloy steel casting, roller diameter 900mm, total 2×1=2 pieces. The rollers are installed with lubrication floating seal of copper bushing for lubrication and wear. The rollers are used to adjust crawler tension level through hydraulic jack and the number of track shoe so as to keep the crawler in the best working condition.

Idle roller: high-strength heat resistant alloy steel casting, roller diameter 280mm, total 2×2=4 pieces. The rollers have built-in floating seals for lifetime lubrication and maintenance-free.

Track shoe: track shoe width 1200mm, total 2×62=124 pieces. The track shoe is made of high- strength heat resistant alloy steel casting, internal hollow with ribs, and self-cleaning. Between track shoes the floating pins are used to achieve multiple shoe hinged closure.

详细介绍

Detailed Introduction

行走机构

行走机构采用双向柱塞马达驱动，通过螺栓固定在行走减速机的外壳上，当驱动轮驱动驱动履带板时，可实现直线行走、原地转向、单边转向、差速转向及带载行走等动作，有极高的灵活性和机动性。

行走机构内置行星减速机，采用负制动设计多片湿式叠片式常闭制动器，实现“弹簧制动/液压释放”功能，保证即使液压回路中的压力降低也能保持极高的制动安全性。

变量泵及变量马达驱动可以实现高、低速两档无级变速，牵引强劲有力，主臂工况可进行带载100%直线行走及70%转弯行走，塔臂工况和固定副臂工况可实现带载50%转弯行走。

最高速度行走速度：1.2km/h。

爬坡能力：30%。

 配重

配重由车身配重和转台配重组成。

车身配重共30t，车身配重可用桅杆吊实现自拆装，车身配重安装在履带架前后。其组成为：

车身配重2×15t。

转台配重提供80t、90t、100t三种选择方案，并按分级配重提供各自独立的性能表来满足不同吊装需求，因此客户使用工况更为实用、经济、方便、快捷。除此之外，根据使用工况最佳的配重数量，也可为客户节约更多的使用成本、运输成本及购机成本。

转台配重安装在转台后方。可选择的转台配重组成如下：

(1) 转台配重 80t；配重托盘1×10t，转台配重块 6×10t，转台配重块 2×5t。

(2) 转台配重90t；配重托盘1×10t，转台配重块6×10t，转台配重块 4×5t。

(3) 转台配重100t；配重托盘1×10t，转台配重块 6×10t，转台配重块 6×5t。

转台配重根据需要还可选择配重提升自拆装装置，实现转台配重自拆装。

 作业设备

XGC260履带起重机的起重臂作业设备为大截面、薄壁大管径、细精高强无缝钢管作为弦管和腹管，辅以高强度钢板分段焊接成中间等截面，两端变截面的四弦管空间桁架结构。通过对单腰绳技术、双腰绳的精确分析与计算，使该产品的作业臂长度得到空前提高，臂架潜能得到充分发挥，起重能力得到极大提升。

XGC260履带起重机的作业设备包括主臂、塔式副臂、固定副臂及其拉杆组件。可提供六种工况供选择，包括主臂工况、主臂臂端单滑轮工况、轻型主臂工况、固定副臂工况、盾构工况、塔式工况。

Crawler travel unit

Crawler travel unit: two-way piston motor is used for drive, fixed on the travel reducer housing with bolts, when the drive roller driving track shoe, travel unit can walk on a straight line, turning around, one-side steering, differential steering and walk with a suspended load, with a high flexibility and mobility.

Crawler travel unit has a built-in planetary reducer, with negative brake design of multi-plate wet type laminated constant closed brake, to achieve "spring braking/hydraulic release" function, and to ensure high braking safety can be maintained even the pressure reduced in the hydraulic circuit.

Variable pump and variable motor drive can achieve high/low speed of two-shift stepless speed change, with strong traction. Crawler travel unit can travel with boom with 100% load for straightline walk and with 70% load for turning around, and can travel with tower jib and fixed jib with 50% load for turning around.

The max. travel speed: 1.2km/h.

Grade-ability: 30%.

 Counterweight

Counterweight consists of car-body counter- weight and turntable counter-weight.

Car-body counterweight is total 30t, can be used as mast derrick to achieve crane self-assembly/ disassembly, and installed in the front/rear of track frame, the composition is as the follows: car-body counterweight 2×15t.

Turntable counterweight provides three options of 80t, 90t, and 100t. To meet the different needs of lifting, the designs provide independent lifting load charts according to classified counterweight, more practical, economical, convenient and fast for customers working conditions. In addition, according to the counterweight quantity for the most suitable working conditions, customers also can save operation, transport and purchase costs.

Turntable counterweight is installed in rear of turntable, the optional turntable counterweight composition is as the follows:

(1) Turntable counterweight 80t: counterweight tray 1×10t, turntable counterweight 6×10t, turntable counterweight 2×5t.

(2) Turntable counterweight 90t: counterweight tray 1×10t, turntable counterweight 6×10t, turntable counterweight 4×5t.

(3) Turntable counterweight 100t: counterweight tray 1×10t, turntable counterweight 6×10t, turntable counterweight 6×5t.

Turntable counterweight can be configured with self-assembly/disassembly device according to the requirement, to achieve turntable counter-weight self-assembly/disassembly.

 Lifting operation equipment

XGC260 crawler crane lifting equipment is boom and jib with main chord and lacing member of large cross-section, large size and high strength seamless steel tube, assisted high strength steel plate in sectional welding for a four-chord lattice structure of uniform section in the middle and variable section at both ends. Through analysis and calculation of single and double center hitch, boom length is increased, boom potential performance is played, and lifting performance is improved.

XGC260 crawler crane lifting equipment comprises boom, tower jib, fixed jib, and pendants, 6 kinds of working conditions provided for selection, include boom, boom head single top, light boom, fixed jib, TBM, and tower jib.

详细介绍

Detailed Introduction

防过放装置
此保护功能由安装在卷筒上的开关进行检测，当卷筒上的钢丝绳剩下三圈时候，将通过显示器及蜂鸣器进行声光报警，同时力矩限制器自动停止下降动作。
棘爪锁止装置
该功能用于锁定主变幅卷扬，起重臂降落的时候必须打开该装置，否则不能降落，用于保护臂架在非工作时安全停放。当锁止时通过显示屏进行显示，以提示棘轮处于锁止状态。
机械式安全装置
回转锁止装置用于起重机停止时上车的机械限位；防后翻装置用于防止主臂、塔臂、固定副臂及其支撑架的过渡后仰。
起重臂角度限制
主臂仰角在85°时，起重臂被停止起升，由力矩限制器和行程开关双级控制。主臂在仰角小于30°时停止起重臂落，由力矩限制器控制。塔臂由限位开关和力矩限制器双级控制控制上限位和下限位。
起重钩防脱卡
所有起重钩均装有防脱卡板，防止悬挂在起重钩钩头的吊索脱落。
液压系统
配置液压平衡阀、液压溢流阀、液压双向锁等装置，保证系统工作时稳定安全。
力矩限制器
力矩限制器系统由大屏彩色显示器、主机、角度传感器、拉力传感器等组成，通过CAN-bus总线与控制器组成总线网络，通过PLC编程可实现系统安全可靠的控制。该力矩限制器功耗小、功能强、灵敏度高、操作简便。 检测功能：力矩限制器能自动检测出起重臂的角度、起重载荷。 显示功能：采用彩色大屏幕触摸式液晶显示器(10.4寸)，用中文(或英文)和图形方式显示力矩百分比、实际起重量、额定起重量、工作半径、起重臂长度、角度、起升高度、工况代码、倍率、限制角度、信息代码等起重作业参数。 警示功能：具有完整的预先报警、超载停止作业功能。如果检测到实际载荷超过额定载荷，起重臂超过极限角度，力矩限制器发出报警并限制当前动作。 系统具有故障自诊断功能。
监控系统
由摄像头和监视器组成，可监视主卷扬、副卷扬和变幅卷扬排绳情况以及车身后部安全状况。

Winch over-release protection device
This protection function uses the switch on winch drum for inspection. When only three turns of wire rope left on the drum, the display and buzzer will give an over-release warning, at the same time, load moment limiter stops crane hoisting down operation.
Winch ratchet lock
This function is used to lock the main luffing winch to protect the boom for stop work during non-working time, and it must be turned on when lowering boom, otherwise boom cannot be lowered. When it is in locking, the display will give a signal to indicate the winch ratchet is in locking.
Mechanical safety device
Turntable locking device is used for crane superstructure mechanical limit for crane stop work. Backstop device is used for boom, tower jib, jib, tower jib rear strut, jib rear strut to prevent boom, jib and strut from tipping backward.
Boom angle limiter
When boom angle is up to 85 ° , boom raising is stopped, with control of both load moment limiter and hoist limit switch. When boom angle is less than 30°, boom lowering is stopped, with control of load moment limiter. Tower jib upper/lower limit is controlled with both load moment limiter and hoist limit switch.
Hook retainer clamp
All hook blocks are fitted with retainer clamps to prevent the sling on hook head from getting off.
Hydraulic system
Hydraulic system is equipped with hydraulic balance valve, hydraulic overflow valve, two-way hydraulic lock, and etc., to ensure the stability and safety of the system work.
Load moment limiter
The load moment limiter is composed large- sized-screen display, main unit, angle sensor, tension sensor andect., through CAN-Bus to form a network with other controllers, and through PLC program to achieve system safe and reliable control, with features of little power consumption, strong function, high sensitivity and easy operation. Detection function: automatically detect boom angle and lifting load. Display function: large color touch screen LCD display, with the Chinese (or English) and graphically display of the percentage of load moment, actual lifting load, rated lifting load, working radius, boom length, boom angle, lifting height, mode code, parts of line, limit angle and information code. Warning function: with complete pre-warning, and overload stop functions, automatically send out warning and stop crane operation when detecting actual lifting load exceeds total rated lifting load and boom out of limit angle. The system also has self-diagnosis function.
Monitor system
The monitor system contains cameras and monitor displays, can respectively monitor the safety conditions of main, auxiliary and luffing winch rope reeving and backside condition.


详细介绍

Detailed Introduction



整机重心和接地比压显示
通过载荷值、转台配重、臂架状态可适时计算整机重心和接地比压数值，并在显示屏上显示，为操作者提供可靠依据，最大限度提高整机运行安全性。
三色力矩报警灯
三色力矩报警灯由“绿”“黄”“红”三种颜色组成。负载在90%以下时，“绿灯”亮，表示起重机在安全区域运行；负载在90%~100%时，“黄灯”亮，表示起重机在已接近额定载荷范围；负载高于100%时，“红灯”和“黄灯”同时亮，表示起重机已经超载，在危险区域，控制系统自动切断起重机向危险方向运行。
声光报警器
在履带起重机移动或做回转动作的时候灯闪烁并且发出声音报警。
照明灯
装置在转台前方、臂架上和操纵室内，用于夜间工作提供照明。
后视镜
位于司机室外侧，便于司机观察机器后方情况。
示高灯
安装在臂架顶部，作为高空警示。
风速仪
实时检测当前风速，传送到操纵室的显示屏上，提醒司机操作的安全性。
水平仪
配有电子和机械2种水平仪，可显示使用路面的倾斜程度，为操作者提供机器水平度参考。
防雷击保护装置
加强设备雷雨天气下的防雷击能力，有效保证设备的安全性。
远程GPS监控系统
可实现GPS定位及GPRS数据传输，设备使用状态查询、远程故障诊断等功能。

Center of gravity and ground pressure display
The overall center of gravity and ground pressure can be calculated through lifting load, turntable counterweight and boom condition, and displayed on screen to provide reliable data for operator, and maximize the safety for operation.
Tricolor warning lamp
The lamp comprises 3 colors, when crane loading is below 90% of total rated lifting load, "Green Lamp" lights on to indicate that the crane is running in safety; when crane loading is in 90% ~ 100% of total rated lifting load, "Yellow Lamp" lights on to indicate that the crane is close to total rated lifting load; when crane loading is above 100% of total rated lifting load, "Red Lamp" lights on to indicate that the crane is overloaded and in dangerous area, at this time control system automatically cut off the crane movement to dangerous direction.
Audio/Video warning
When crawler crane is moving and slewing, there is light and sound for warning.
Illuminator lamp
There are illuminator lamps at front of turntable, on boom and inside operator's cab for night operation.
Rearview mirror
Rearview mirror is located outside the cab for operator easy observation behind the machine.
Height mark lamp
Boom tip has a height mark lamp for high level operation warning.
Anemometer
Anemometer can detect current wind speed and send signal to a monitor in operator's cab to alert operator for safety.
Level meter
The crane is equipped with 2 kinds of electronic and mechanical level meter, can indicate the road inclination degree, and provide operator with the machine level degree for reference.
Lightning protection device
The device can strengthen the equipment lightning protection ability under thunderstorm, effectively ensure the safety of the equipment.
Remote GPS monitor
The system can achieve GPS positioning and GPRS data transmission, the equipment uses status inquiries, remote fault diagnosis, and other functions.



1.主机卸车




2.履带卸车及组装




3.车身配重卸车及组装




4.转台配重卸车及堆叠




5.吊臂卸车与除主臂底节外的吊臂和拉板组装




6.组装主臂底节





7.拉起主臂底节




8.转台配重自拆装





9.主臂底节与吊臂及拉板连接



10.吊钩穿绳



11.吊臂拉起



主臂工况臂节组合
Boom Combinations

名称及数量	主臂底节臂 10.5m	主臂中间节 3m	主臂中间节 6m	主臂中间节 12mA	主臂中间节 12mB	主臂变径节 12m	主臂连接节 1.5m	主臂臂头 滑轮组
主臂长度								
HB24	1	0	0	0	0	1	1	1
HB27	1	1	0	0	0	1	1	1
HB30	1	0	1	0	0	1	1	1
HB33	1	1	1	0	0	1	1	1
HB36	1	0	0	1	0	1	1	1
HB39	1	1	0	1	0	1	1	1
HB42	1	0	1	1	0	1	1	1
HB45	1	1	1	1	0	1	1	1
HB48	1	0	0	2	0	1	1	1
HB51	1	1	0	2	0	1	1	1
HB54	1	0	1	2	0	1	1	1
HB57	1	1	1	2	0	1	1	1
HB60	1	0	0	3	0	1	1	1
HB63	1	1	0	3	0	1	1	1
HB66	1	0	1	3	0	1	1	1
HB69	1	1	1	3	0	1	1	1
HB72	1	0	0	3	1	1	1	1
HB75	1	1	0	3	1	1	1	1
* HB78	1	0	1	3	1	1	1	1
* HB81	1	1	1	3	1	1	1	1
* HB84	1	0	0	3	2	1	1	1
* HB87	1	1	0	3	2	1	1	1
* HB90	1	0	1	3	2	1	1	1
* HB93	1	1	1	3	2	1	1	1

注释： “*” 主臂长度需要使用1.33m腰绳。

主臂工况起臂表
Boom Raising Table

说明	配置组合(转台配重+车身配重)		
主臂长度	80t+30t	90t+30t	100t+30t
HB24	●	●	●
HB27	●	●	●
HB30	●	●	●
HB33	●	●	●
HB36	●	●	●
HB39	●	●	●
HB42	●	●	●
HB45	●	●	●
HB48	●	●	●
HB51	●	●	●
HB54	●	●	●
HB57	●	●	●
HB60	●	●	●
HB63	●	●	●
HB66	●	●	●
HB69	●	●	●
HB72	●	●	●
HB75	●	●	●
* HB78	●	●	●
* HB81	○	●	●
* HB84	○	○	●
* HB87	x	○	●
* HB90	x	x	○
* HB93	x	x	○

注释： 1. 起臂时，请将履带驱动轮置于车体在后方起臂
2. “*” --主臂长度需要使用1.33m腰绳。
3. “●” --可以起臂。
4. “○” --需要模块起臂。
5. “x” --不可起臂，工况不可使用。

主臂工况(HB)载荷表
Boom Lifting Load Chart

标准：GB/DIN/ISO 360° 回转 转台配重：100t 车身配重：30t 主臂长度：24m~93m

HB 工作半径 (m)	主臂长度Boom length												HB 工作半径 (m)
	HB24 t	HB27 t	HB30 t	HB33 t	HB36 t	HB39 t	HB42 t	HB45 t	HB48 t	HB51 t	HB54 t	HB57 t	
5.3	260.0**												5.3
6	232.0*	232.0*	232.0*	215.0*									6
7	200.0*	200.0*	200.0*	199.0*	199.0*	182.0*	182.0	165.0					7
8	175.0*	175.0*	180.0	180.0	180.0	180.0	179.0	165.0	148.0	148.0	130.0	130.0	8
9	161.0	160.0	160.0	160.0	160.0	160.0	159.0	156.0	148.0	148.0	130.0	130.0	9
10	145.0	144.0	144.0	144.0	144.0	143.0	142.0	139.0	136.0	132.0	129.0	126.0	10
11	131.0	131.0	131.0	131.0	130.0	130.0	128.0	125.0	122.0	120.0	117.0	114.0	11
12	120.0	120.0	120.0	119.0	119.0	119.0	116.0	114.0	111.0	109.0	107.0	104.0	12
13	109.0	109.0	109.0	109.0	109.0	108.0	106.0	104.0	102.0	100.0	98.2	96.3	13
14	99.5	99.5	99.5	99.5	99.5	99.4	98.0	96.0	94.2	92.4	90.6	88.9	14
15	90.0	90.0	90.0	90.0	90.0	89.9	89.8	88.9	87.3	85.6	84.0	82.5	15
16	82.1	82.1	82.1	82.1	82.1	82.0	81.8	81.7	81.2	79.7	78.3	76.8	16
17	75.4	75.4	75.4	75.3	75.3	75.2	75.1	74.9	74.8	74.4	73.1	71.8	17
18	69.6	69.6	69.6	69.5	69.5	69.4	69.2	69.1	68.9	68.8	68.6	67.4	18
19	64.5	64.5	64.5	64.4	64.4	64.3	64.2	64.0	63.8	63.7	63.5	63.3	19
20	60.0	60.0	60.0	60.0	60.0	59.8	59.7	59.5	59.4	59.2	59.0	58.8	20
22	52.5	52.5	52.5	52.5	52.5	52.3	52.2	52.0	51.9	51.7	51.5	51.2	22
24		46.5	46.5	46.5	46.5	46.3	46.2	46.0	45.8	45.6	45.4	45.2	24
26			41.5	41.5	41.5	41.3	41.2	41.0	40.9	40.6	40.4	40.2	26
28			37.4	37.3	37.3	37.2	37.0	36.8	36.7	36.5	36.3	36.0	28
30				33.7	33.7	33.6	33.5	33.3	33.2	32.9	32.7	32.5	30
32					30.7	30.6	30.5	30.2	30.1	29.9	29.7	29.4	32
34						27.9	27.8	27.6	27.5	27.2	27.0	26.8	34
36						25.6	25.5	25.3	25.1	24.9	24.7	24.4	36
38							23.4	23.2	23.1	22.8	22.6	22.4	38
40								21.3	21.2	21.0	20.8	20.5	40
42									19.6	19.3	19.2	18.9	42
44										17.8	17.7	17.4	44
46										16.5	16.3	16.0	46
48											15.0	14.8	48
50												13.7	50
52													52
54													54
56													56
58													58
倍率(Φ28)	18	17	17	15	14	13	13	11	10	10	9	9	倍率(Φ28)

注意： 1、实际起重量必须从本表的额定起重量中减去吊钩、吊具及缠绕在吊钩及臂头上的钢丝绳的重量。
2、表中额定载荷是在水平坚硬地面、重物被缓慢平稳吊起、非行走吊重工作时的值。
3、表中额定载荷基于主臂臂节不含主臂外拉板及臂端单滑轮的计算值。
4、主臂长度超过87m时必须使用斜模块辅助起臂，主臂长度超过75m时必须使用腰绳。
5、“***”处转台配重80t； “**”处转台配重为90t。


主臂工况(HB)载荷表
Boom Lifting Load Chart

标准：GB/DIN/ISO 360° 回转 转台配重：100t 车身配重：30t 主臂长度：24m~93m

HB 工作半径 (m)	主臂长度Boom length												HB 工作半径 (m)
	HB60 t	HB63 t	HB66 t	HB69 t	HB72 t	HB75 t	HB78 t	HB81 t	HB84 t	HB87 t	HB90 t	HB93 t	
9	112.0	112.0	112.0										9
10	112.0	112.0	111.0	94.7	92.9	85.5	83.8						10
11	112.0	109.0	107.0	94.7	91.7	84.4	83.1	76.3	70.3	65.3	60.7		11
12	102.0	100.0	98.5	94.7	90.6	83.3	82.4	76.0	69.7	64.7	60.1	55.9	12
13	94.4	92.5	90.7	89.0	87.4	82.3	81.7	75.3	69.0	64.0	59.5	55.4	13
14	87.2	85.6	84.0	82.4	81.0	79.5	77.9	74.7	68.4	63.4	58.9	54.8	14
15	81.0	79.5	78.0	76.6	75.4	74.0	72.5	71.2	67.7	62.8	58.3	54.2	15
16	75.5	74.1	72.8	71.5	70.4	69.1	67.7	66.5	65.5	62.1	57.7	53.6	16
17	70.6	69.3	68.1	66.9	65.9	64.7	63.5	62.3	61.4	60.3	57.1	53.1	17
18	66.2	65.1	63.9	62.8	61.9	60.8	59.6	58.6	57.7	56.7	55.7	52.5	18
19	62.3	61.2	60.1	59.1	58.3	57.3	56.1	55.1	54.3	53.4	52.4	51.5	19
20	58.6	57.7	56.7	55.7	55.0	54.0	53.0	52.0	51.3	50.4	49.5	48.6	20
22	51.1	50.8	50.6	49.9	49.2	48.4	47.4	46.6	45.9	45.1	44.3	43.5	22
24	45.0	44.8	44.5	44.3	44.3	43.6	42.7	41.9	41.4	40.6	39.9	39.1	24
26	40.0	39.8	39.5	39.3	39.3	39.0	38.7	38.0	37.5	36.8	36.1	35.4	26
28	35.8	35.6	35.4	35.1	35.1	34.8	34.5	34.2	34.1	33.4	32.8	32.1	28
30	32.3	32.0	31.8	31.5	31.5	31.2	30.9	30.6	30.6	30.3	29.9	29.2	30
32	29.2	29.0	28.7	28.5	28.4	28.2	27.8	27.6	27.5	27.2	27.0	26.7	32
34	26.6	26.3	26.1	25.8	25.8	25.5	25.2	24.9	24.8	24.5	24.3	24.0	34
36	24.3	24.0	23.8	23.5	23.4	23.2	22.8	22.6	22.5	22.2	21.9	21.7	36
38	22.2	21.9	21.7	21.4	21.4	21.1	20.8	20.5	20.4	20.1	19.9	19.6	38
40	20.4	20.1	19.9	19.6	19.5	19.3	18.9	18.6	18.6	18.3	18.0	17.7	40
42	18.7	18.4	18.2	17.9	17.9	17.6	17.3	17.0	16.9	16.6	16.4	16.1	42
44	17.2	17.0	16.7	16.4	16.4	16.1	15.8	15.5	15.4	15.1	14.9	14.6	44
46	15.9	15.6	15.4	15.1	15.0	14.8	14.4	14.1	14.1	13.8	13.5	13.2	46
50	13.5	13.2	13.0	12.7	12.7	12.4	12.1	11.8	11.7	11.4	11.1	10.8	50
54	11.5	11.2	11.0	10.7	10.7	10.4	10.1	9.8	9.7	9.4	9.1	8.8	54
56		10.3	10.1	9.8	9.8	9.5	9.2	8.9	8.8	8.5	8.3	8.0	56
58			9.3	9.0	9.0	8.7	8.4	8.1	8.0	7.7	7.4	7.1	58
62				7.5	7.5	7.2	6.9	6.6	6.5	6.2	6.0	5.7	62
64					6.8	6.5	6.2	5.9	5.9	5.6	5.3	5.0	64
66						5.9	5.6	5.3	5.2	4.9	4.7	4.4	66
68							5.0	4.7	4.7	4.4	4.1	3.8	68
72								3.6	3.6	3.3	3.0	2.7	72
74									3.1	2.8	2.5		74
倍率(Φ28)	8	8	8	6	6	6	6	5	5	5	4	4	倍率(Φ28)

- 注意：1、实际起重重量必须从本表的额定起重重量中减去吊钩、吊具及缠绕在吊钩及臂头上的钢丝绳的重量。
2、表中额定载荷是在水平坚硬地面、重物被缓慢平稳吊起、非行走吊重工作时的值。
3、表中额定载荷基于主臂臂节不含主臂外拉板及臂端单滑轮的计算值。
4、主臂长度超过87m必须使用斜模块辅助起臂，主臂长度超过75m时必须使用腰绳。
5、***处转台配重80t；***处转台配重为90t。

主臂臂端单滑轮工况工作范围图
Boom Head Single Top Working Area



主臂臂端单滑轮工况臂节组合
Boom Combinations for Boom Head Single Top

名称及数量	主臂底节臂 10.5m	主臂中间节 3m	主臂中间节 6m	主臂中间节 12mA	主臂中间节 12mB	主臂变径节 12m	主臂连接节 1.5m	主臂臂头 滑轮组	主臂臂端 单滑轮
主臂长度									
HBS24	1	0	0	0	0	1	1	1	1
HBS27	1	1	0	0	0	1	1	1	1
HBS30	1	0	1	0	0	1	1	1	1
HBS33	1	1	1	0	0	1	1	1	1
HBS36	1	0	0	1	0	1	1	1	1
HBS39	1	1	0	1	0	1	1	1	1
HBS42	1	0	1	1	0	1	1	1	1
HBS45	1	1	1	1	0	1	1	1	1
HBS48	1	0	0	2	0	1	1	1	1
HBS51	1	1	0	2	0	1	1	1	1
HBS54	1	0	1	2	0	1	1	1	1
HBS57	1	1	1	2	0	1	1	1	1
HBS60	1	0	0	3	0	1	1	1	1
HBS63	1	1	0	3	0	1	1	1	1
HBS66	1	0	1	3	0	1	1	1	1
HBS69	1	1	1	3	0	1	1	1	1
HBS72	1	0	0	3	1	1	1	1	1
HBS75	1	1	0	3	1	1	1	1	1
* HBS78	1	0	1	3	1	1	1	1	1
* HBS81	1	1	1	3	1	1	1	1	1
* HBS84	1	0	0	3	2	1	1	1	1
* HBS87	1	1	0	3	2	1	1	1	1
* HBS90	1	0	1	3	2	1	1	1	1
* HBS93	1	1	1	3	2	1	1	1	1

注释： 1. “*” 主臂长度需要使用1.33m腰绳。
2.臂端单滑轮长度1.8m。

主臂臂端单滑轮工况起臂表
Boom Raising Table for Boom Head Single Top

说明	配置组合(转台配重+车身体配重)		
主臂长度	80t+30t	90t+30t	100t+30t
HBS24	●	●	●
HBS27	●	●	●
HBS30	●	●	●
HBS33	●	●	●
HBS36	●	●	●
HBS39	●	●	●
HBS42	●	●	●
HBS45	●	●	●
HBS48	●	●	●
HBS51	●	●	●
HBS54	●	●	●
HBS57	●	●	●
HBS60	●	●	●
HBS63	●	●	●
HBS66	●	●	●
HBS69	●	●	●
HBS72	●	●	●
HBS75	●	●	●
* HBS78	●	●	●
* HBS81	○	●	●
* HBS84	○	○	●
* HBS87	×	○	●
* HBS90	×	×	○
* HBS93	×	×	○

注释： 1. 起臂时，请将腰带驱动轮置于车体在后方起臂。
2. “*” --主臂长度需要使用1.33m腰绳。
3. “●” --可以起臂。
4. “○” --需要模块起臂。
5. “×” --不可起臂，工况不可使用。

主臂臂端单滑轮工况(HBS)载荷表
Boom Head Single Top (HBS) Lifting Load Chart

标准：GB/DIN/ISO 360° 回转 转台配重：100t 车身体配重：30t 主臂长度：24m~93m

HB 工作半径 (m)	主臂长度Boom length												HB 工作半径 (m)
	HB24 t	HB27 t	HB30 t	HB33 t	HB36 t	HB39 t	HB42 t	HB45 t	HB48 t	HB51 t	HB54 t	HB57 t	
7	28.0**	28.0**											7
8	28.0*	28.0*	28.0	28.0	28.0								8
9	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0				9
10	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0		10
11	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	11
12	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	12
13	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	13
14	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	14
15	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	15
16	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	16
17	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	17
18	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	18
19	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	19
20	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	20
22	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	22
24		28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	24
26			28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	26
28			28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28
30				27.7	27.8	27.6	27.5	27.3	27.2	26.9	26.7	26.5	30
32					24.7	24.6	24.5	24.2	24.1	23.9	23.7	23.4	32
34						21.9	21.8	21.6	21.5	21.2	21.0	20.8	34
36						19.6	19.5	19.3	19.1	18.9	18.7	18.4	36
38							17.4	17.2	17.1	16.8	16.6	16.4	38
40								15.3	15.2	15.0	14.8	14.5	40
42									13.6	13.3	13.2	12.9	42
44										11.8	11.7	11.4	44
46										10.3	10.3	10.0	46
48											9.0	8.8	48
50												7.7	50
52													52
54													54
倍率(Φ26)	2	2	2	2	2	2	2	2	2	2	2	2	倍率(Φ26)

注意： 1、实际起重量必须从本表的额定起重量减去吊钩、吊具及缠绕在吊钩及臂头上钢丝绳的重量。
2、表中额定载荷是在水平坚硬地面、重物被缓慢平稳吊起、非行走吊重工作时的值。
3、表中额定载荷基于主臂臂节不含主臂外拉板及臂端单滑轮的计算值。
4、主臂长度超过78m必须使用斜模块辅助起臂，主臂长度超过75m时必须使用腰绳。
5、臂端单滑轮钢丝绳直径Φ26，臂端单滑轮吊载；主臂须空钩，严禁吊载。
6、 "****"处转台配重80t;"**"处转台配重为90t。


主臂臂端单滑轮工况(HBS)载荷表
Boom Head Single Top (HBS) Lifting Load Chart

标准：GB/DIN/ISO 360° 回转 转台配重：100t 车身配重：30t 主臂长度：24m~93m

HB 工作半径 (m)	主臂长度Boom length												HB 工作半径 (m)
	HB60 t	HB63 t	HB66 t	HB69 t	HB72 t	HB75 t	HB78 t	HB81 t	HB84 t	HB87 t	HB90 t	HB93 t	
10	28.0												10
11	28.0												11
12	28.0												12
13	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	13
14	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	14
15	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	15
16	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	16
17	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	17
18	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	18
19	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	19
20	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	20
22	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	22
24	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	24
26	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	26
28	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	27.4	26.8	26.1	28
30	26.3	26.0	25.8	25.5	25.5	25.2	24.9	24.6	24.6	24.3	23.9	23.2	30
32	23.2	23.0	22.7	22.5	22.4	22.2	21.8	21.6	21.5	21.2	21.0	20.7	32
34	20.6	20.3	20.1	19.8	19.8	19.5	19.2	18.9	18.8	18.5	18.3	18.0	34
36	18.3	18.0	17.8	17.5	17.4	17.2	16.8	16.6	16.5	16.2	15.9	15.7	36
38	16.2	15.9	15.7	15.4	15.4	15.1	14.8	14.5	14.4	14.1	13.9	13.6	38
40	14.4	14.1	13.9	13.6	13.5	13.3	12.9	12.6	12.6	12.3	12.0	11.7	40
42	12.7	12.4	12.2	11.9	11.9	11.6	11.3	11.0	10.9	10.6	10.4	10.1	42
44	11.2	11.0	10.7	10.4	10.4	10.1	9.8	9.5	9.4	9.1	8.9	8.6	44
46	9.9	9.6	9.4	9.1	9.0	8.8	8.4	8.1	8.1	7.8	7.5	7.2	46
48	8.6	8.4	8.1	7.8	7.8	7.5	7.2	6.9	6.8	6.5	6.3	6.0	48
50	7.5	7.2	7.0	6.7	6.7	6.4	6.1	5.8	5.7	5.4	5.1	4.8	50
52	6.5	6.2	6.0	5.7	5.7	5.4	5.0	4.7	4.7	4.4	4.1	3.8	52
54	5.5	5.2	5.0	4.7	4.7	4.4	4.1	3.8	3.7	3.4	3.1	2.8	54
56		4.3	4.1	3.8	3.8	3.5	3.2	2.9	2.8	2.5			56
58			3.3	3.0	3.0	2.7							58
60													60
倍率(Φ26)	2	2	2	2	2	2	2	2	2	2	2	2	倍率(Φ26)

- 注意：1、实际起重量必须从本表的额定起重量中减去吊钩、吊具及缠绕在吊钩及臂头上的钢丝绳的重量。
2、表中额定载荷是在水平坚硬地面、重物被缓慢平稳吊起、非行走吊重工作时的值。
3、表中额定载荷基于主臂臂节不含主臂外拉板及臂端单滑轮的计算值。
4、主臂长度超过87m时必须使用斜模块辅助起臂，主臂长度超过75m时必须使用腰绳。
5、""处转台配重80t；""处转台配重为90t。

轻型主臂工况工作范围图
Light Boom Working Area



轻型主臂工况臂节组合
Light Boom Combinations

名称及数量 主臂长度	主臂底节臂 10.5m	主臂中间节 3m	主臂中间节 6m	主臂中间节 12mA	主臂变径节 12m	塔臂中间节 6mA	塔臂中间节 6mB	塔臂中间节 12m	塔臂顶节臂 9m
LB67.5	1	0	1	1	1	1	0	1	1
LB70.5	1	1	1	1	1	1	0	1	1
* LB73.5	1	0	0	2	1	1	0	1	1
* LB76.5	1	1	0	2	1	1	0	1	1
* LB79.5	1	0	1	2	1	1	0	1	1
* LB82.5	1	1	1	2	1	1	0	1	1
** LB85.5	1	0	1	2	1	1	1	1	1
** LB88.5	1	1	1	2	1	1	1	1	1
** LB91.5	1	0	1	2	1	1	0	2	1
** LB94.5	1	1	1	2	1	1	0	2	1
** LB97.5	1	0	1	2	1	1	1	2	1
** LB100.5	1	1	1	2	1	1	1	2	1

注释：1. “*” 轻型主臂长度需要使用1.25m单腰绳。
2. “**” 轻型主臂长度需要使用1.25m、 2.62m双腰绳。

轻型主臂工况起臂表
Light Boom Raising Table

说明 主臂长度	配重组合(转台配重+车身配重)	
	90t+30t	100t+30t
LB67.5	●	●
LB70.5	●	●
* LB73.5	●	●
* LB76.5	●	●
* LB79.5	●	●
* LB82.5	●	●
** LB85.5	●	●
** LB88.5	●	●
** LB91.5	●	●
** LB94.5	●	●
** LB97.5	○	●
** LB100.5	○	○

注释：1. 起臂时，请将腰带驱动轮置于车体在后方起臂。
2. “*” 轻型主臂长度需要使用1.25m单腰绳。
3. “**” 轻型主臂长度需要使用1.25m、 2.62m双腰绳。
4. “●” --可以起臂。
5. “○” --需要模块起臂。
6. “×” --不可起臂， 工况不可使用。
7. 配重组合(80t+30t)不配置轻型主臂工况。


轻型主臂工况(LB)载荷表
Light Boom (LB) Lifting Load Chart

标准：GB/DIN/ISO 360° 回转 转台配重：100t 车身配重：30t 轻型主臂：67.5m~100.5m

LB 工作半径 (m)	主臂长度Boom length												LB 工作半径 (m)
	LB67.5 t	LB70.5 t	LB73.5 t	LB76.5 t	LB79.5 t	LB82.5 t	LB85.5 t	LB88.5 t	LB91.5 t	LB94.5 t	LB97.5 t	LB100.5 t	
9	85.0	80.0	73.5										9
10	82.8	78.3	71.6	71.0	70.1	66.8	56.1						10
11	81.8	76.8	69.9	68.6	67.9	66.2	54.8	53.6	45.2	44.1	39.7		11
12	80.3	75.3	68.3	67.3	66.8	65.5	53.7	51.5	44.3	43.0	38.7	38.6	12
13	78.8	73.9	66.6	66.0	65.6	64.9	52.5	50.5	43.4	42.3	37.9	37.2	13
14	76.6	72.6	64.6	63.8	63.5	62.3	51.3	50.4	42.5	41.5	37.1	36.1	14
15	73.0	69.4	62.8	62.0	61.1	60.3	50.2	49.4	40.9	40.2	36.2	35.8	15
16	69.6	66.3	61.1	60.0	59.3	58.8	49.1	48.4	40.0	39.3	35.5	35.0	16
17	66.4	63.2	59.5	61.5	58.8	57.5	48.0	47.5	39.1	38.7	34.7	34.1	17
18	63.5	60.4	57.9	57.5	57.1	56.2	47.0	46.5	38.1	37.6	33.9	33.2	18
19	60.7	57.7	56.5	56.3	56.1	55.1	45.8	45.0	37.0	35.9	33.2	32.6	19
20	57.8	55.3	54.0	53.0	52.2	51.0	44.7	44.2	36.0	35.0	32.5	32.0	20
22	52.2	50.1	49.7	49.3	49.0	48.7	42.6	41.1	34.1	33.8	31.3	31.0	22
24	47.3	45.3	44.5	44.0	43.0	42.0	40.6	39.5	32.4	32.0	30.0	29.5	24
26	42.7	41.2	42.0	41.8	41.6	41.2	38.9	36.0	30.9	30.3	28.8	28.4	26
28	38.6	37.5	38.0	37.7	37.5	37.2	36.9	35.1	29.5	29.1	27.6	27.4	28
30	35.1	34.2	34.0	33.9	33.8	33.7	33.5	32.1	28.3	28.1	26.4	26.1	30
32	32.0	31.3	31.2	31.0	30.8	30.6	30.3	30.0	27.1	26.9	25.4	25.0	32
34	29.4	28.7	28.6	28.5	28.3	28.0	27.9	27.6	26.0	25.5	24.4	24.0	34
36	27.1	26.3	26.2	26.1	26.0	25.7	25.5	25.3	25.1	24.5	23.6	23.3	36
38	25.0	24.2	24.1	24.0	23.9	23.6	23.5	23.3	23.1	22.9	22.7	22.5	38
40	23.2	22.2	22.1	22.0	21.9	21.8	21.6	21.4	21.3	21.1	21.0	20.9	40
42	21.2	20.4	20.2	20.0	19.9	19.8	19.7	19.6	19.5	19.4	19.3	19.2	42
44	19.5	18.8	18.7	18.6	18.5	18.4	18.3	18.2	18.1	18.0	17.9	17.8	44
46	18.0	17.5	17.3	17.2	17.1	17.0	16.9	16.8	16.7	16.6	16.5	16.4	46
48	16.5	16.2	16.1	16.0	15.9	15.8	15.7	15.6	15.5	15.4	15.3	15.2	48
50	15.4	15.1	15.0	14.9	14.8	14.7	14.6	14.5	14.4	14.3	14.2	14.1	50
52	14.2	14.1	14.0	13.9	13.8	13.7	13.6	13.5	13.4	13.3	13.2	13.1	52
54	13.2	13.1	13.0	12.9	12.8	12.7	12.6	12.5	12.4	12.3	12.2	12.1	54
56			13.0	12.7	12.5	12.2	12.1	11.8	11.9	11.6	11.5	11.2	56
60				11.2	10.9	10.6	10.5	10.2	10.3	10.0	10.0	9.7	60
66					8.9	8.6	8.5	8.3	8.2	8.1	8.0	7.7	66
68						8.0	7.9	7.7	7.6	7.5	7.4	7.1	68
72							6.9	6.6	6.5	6.4	6.3	6.1	72
76								5.7	5.6	5.5	5.3	5.1	76
78									5.2	5.1	4.9	4.7	78
80										4.6	4.5	4.3	80
84											3.8	3.5	84
88												2.8	88
倍率(Φ28)	6	5	5	5	5	5	4	4	3	3	3	3	倍率(Φ28)

注意：1、实际起重量必须从本表的额定起重量中减去吊钩、吊具及缠绕在吊钩及臂头上的钢丝绳的重量。
2、表中额定载荷是在水平坚硬地面、重物被缓慢平稳吊起、非行走吊重工作时的值。
3、表中额定载荷基于主臂臂节不含主臂外拉板的计算值。
4、臂架长度超过94.5m必须使用斜模块辅助起臂。
5、臂长超过70.5时必须使用腰绳,且臂架长度超过82.5时必须使用双腰绳。

固定副臂工况工作范围图
Fixed Jib Working Area



固定副臂工况臂节组合
Fixed Jib Combinations

A、固定副臂工况主臂臂节组合

名称及数量 轻型 主臂长度	主臂 底节 10.5m	主臂 中间节 3m	主臂 中间节 6m	主臂 中间节 12mA	主臂 中间节 12mB	主臂 变径节 12m	主臂 连接节 1.5m
H24	1	0	0	0	0	1	1
H27	1	1	0	0	0	1	1
H30	1	0	1	0	0	1	1
H33	1	1	1	0	0	1	1
H36	1	0	0	1	0	1	1
H39	1	1	0	1	0	1	1
H42	1	0	1	1	0	1	1
H45	1	1	1	1	0	1	1
H48	1	0	0	2	0	1	1
H51	1	1	0	2	0	1	1
H54	1	0	1	2	0	1	1
H57	1	1	1	2	0	1	1
H60	1	0	0	3	0	1	1
H63	1	1	0	3	0	1	1
H66	1	0	1	3	0	1	1
H69	1	1	1	3	0	1	1
H72	1	0	0	3	1	1	1
H75	1	1	0	3	1	1	1
* H78	1	0	1	3	1	1	1
* H81	1	1	1	3	1	1	1

注释：1. “*” 主臂长度需要使用1.33m腰绳。

B、固定副臂工况副臂臂节组合

名称及数量 轻型 主臂长度	副臂 底节 4.5m	副臂 中间节 3m	副臂 中间节 6m	副臂 中间节 12m	副臂 顶节 4.5m
F9	1	0	0	0	1
F12	1	1	0	0	1
F18	1	1	1	0	1
F24	1	1	2	0	1
F30	1	1	1	1	1
F36	1	1	2	1	1

注释：1.当使用F9、F12的固定副臂工况组合时，固定副臂须使用重量大于2.5t的吊钩。

固定副臂工况起臂表
Fixed Jib Raising Table

I、配重组合(转台配重+车身配重): 100t+30t II、配重组合(转台配重+车身配重): 90t+30t III、配重组合(转台配重+车身配重):80t+30t

主臂长度	副臂长度	F9	F12	F18	F24	F30	F36
H24		●	●	●	●	●	●
H27		●	●	●	●	●	●
H30		●	●	●	●	●	●
H33		●	●	●	●	●	●
H36		●	●	●	●	●	●
H39		●	●	●	●	●	●
H42		●	●	●	●	●	●
H45		●	●	●	●	●	●
H48		●	●	●	●	●	●
H51		●	●	●	●	●	●
H54		●	●	●	●	●	●
H57		●	●	●	●	●	●
H60		●	●	●	●	●	●
H63		●	●	●	●	●	●
H66		●	●	●	●	●	●
H69		●	●	●	●	●	●
H72		●	●	●	●	●	●
H75		●	●	●	●	●	●
* H78		○	○	○	○	○	○
* H81		○	○	○	○	○	○

主臂长度	副臂长度	F9	F12	F18	F24	F30	F36
H24		●	●	●	●	●	●
H27		●	●	●	●	●	●
H30		●	●	●	●	●	●
H33		●	●	●	●	●	●
H36		●	●	●	●	●	●
H39		●	●	●	●	●	●
H42		●	●	●	●	●	●
H45		●	●	●	●	●	●
H48		●	●	●	●	●	●
H51		●	●	●	●	●	●
H54		●	●	●	●	●	●
H57		●	●	●	●	●	●
H60		●	●	●	●	●	●
H63		●	●	●	●	●	●
H66		●	●	●	●	●	●
H69		●	●	●	●	●	●
H72		●	●	●	●	●	●
H75		●	●	●	●	●	●
* H78		○	○	○	○	○	○
* H81		○	○	○	○	○	○

主臂长度	副臂长度	F9	F12	F18	F24	F30	F36
H24		●	●	●	●	●	●
H27		●	●	●	●	●	●
H30		●	●	●	●	●	●
H33		●	●	●	●	●	●
H36		●	●	●	●	●	●
H39		●	●	●	●	●	●
H42		●	●	●	●	●	●
H45		●	●	●	●	●	●
H48		●	●	●	●	●	●
H51		●	●	●	●	●	●
H54		●	●	●	●	●	●
H57		●	●	●	●	●	●
H60		●	●	●	●	●	●
H63		●	●	●	●	●	●
H66		●	●	●	●	●	●
H69		●	●	●	●	●	●
H72		●	●	●	●	●	●
H75		●	●	●	●	●	●
* H78		○	○	○	○	○	○
* H81		○	○	○	○	○	○

注释：1. 起臂时，请将腰带驱动轮置于车体在后方起臂
2. “*” --主臂长度需要使用1.33m单腰绳。
3. “●” --可以起臂。
4. “○” --需要模块起臂。
5. “×” --不可起臂，工况不可使用。

固定副臂工况(HF)载荷表
Fixed Jib (HF) Lifting Load Chart

标准：GB/DIN/ISO 360° 回转 转台配重：100t 车身配重：30t
固定副臂：9m 主副臂夹角：10° 主臂长度：24m~81m

F9	主臂长度Boom length																				F9
工作半径 (m)	H24 t	H27 t	H30 t	H33 t	H36 t	H39 t	H42 t	H45 t	H48 t	H51 t	H54 t	H57 t	H60 t	H63 t	H66 t	H69 t	H72 t	H75 t	H78 t	H81 t	工作半径 (m)
8	105.0**	105.0*																			8
9	105.0**	105.0*	105.0	105.0	105.0	105.0															9
10	105.0**	105.0*	105.0	105.0	105.0	105.0	105.0	105.0	105.0	105.0											10
11	105.0**	105.0*	105.0	105.0	105.0	105.0	105.0	105.0	105.0	105.0	103.0	97.2	93.4	88.2							11
12	105.0	105.0	105.0	105.0	105.0	105.0	105.0	105.0	105.0	103.0	101.0	96.0	92.1	87.1	81.9	76.1	69.7				12
13	105.0	105.0	105.0	105.0	105.0	103.0	101.0	99.2	97.2	95.3	93.5	91.7	89.9	85.8	80.9	75.5	69.1	64.1	63.8	59.4	13
14	101.0	101.0	100.0	98.9	97.0	95.1	93.3	91.5	89.8	88.1	86.5	84.8	83.2	81.7	80.0	74.9	68.6	63.5	63.4	59.0	14
15	91.7	91.6	91.5	91.3	89.8	88.1	86.5	84.9	83.3	81.8	80.3	78.8	77.4	76.0	74.6	73.3	68.0	63.0	62.7	58.6	15
16	83.7	83.5	83.4	83.3	83.1	82.0	80.5	79.0	77.6	76.2	74.9	73.5	72.2	70.9	69.7	68.4	67.3	62.4	61.6	58.2	16
17	76.8	76.7	76.6	76.4	76.2	76.1	75.2	73.9	72.6	71.3	70.0	68.8	67.6	66.4	65.2	64.1	63.1	61.8	60.6	57.7	17
18	70.9	70.8	70.6	70.4	70.3	70.1	69.9	69.2	68.1	66.9	65.7	64.6	63.4	62.3	61.2	60.2	59.3	58.2	57.1	56.0	18
19	65.8	65.6	65.5	65.3	65.1	64.9	64.8	64.6	64.0	62.9	61.8	60.7	59.7	58.7	57.6	56.6	55.8	54.8	53.7	52.8	19
20	61.3	61.1	60.9	60.7	60.6	60.4	60.2	60.0	59.8	59.3	58.3	57.3	56.3	55.3	54.4	53.4	52.6	51.7	50.7	49.8	20
22	53.7	53.5	53.3	53.1	53.0	52.8	52.6	52.3	52.1	51.9	51.7	51.2	50.4	49.5	48.6	47.8	47.1	46.3	45.3	44.5	22
24	47.6	47.4	47.2	47.0	46.8	46.6	46.4	46.2	46.0	45.7	45.5	45.3	45.1	44.6	43.8	43.0	42.4	41.6	40.8	40.0	24
26	42.5	42.3	42.2	41.9	41.8	41.5	41.3	41.1	40.9	40.6	40.4	40.2	40.0	39.7	39.5	38.9	38.4	37.7	36.9	36.1	26
28	38.3	38.1	37.9	37.7	37.6	37.3	37.1	36.8	36.6	36.4	36.2	35.9	35.7	35.4	35.2	34.9	34.8	34.2	33.4	32.8	28
30	34.6	34.5	34.3	34.1	34.0	33.7	33.5	33.2	33.0	32.8	32.5	32.3	32.0	31.8	31.5	31.3	31.2	30.9	30.4	29.8	30
32	31.5	31.3	31.2	31.0	30.9	30.6	30.4	30.1	29.9	29.7	29.4	29.1	28.9	28.7	28.4	28.1	28.0	27.8	27.4	27.2	32
34		28.6	28.5	28.3	28.1	27.9	27.7	27.4	27.2	27.0	26.7	26.4	26.2	25.9	25.7	25.4	25.3	25.1	24.7	24.4	34
36			26.1	25.9	25.8	25.5	25.3	25.0	24.8	24.6	24.3	24.0	23.8	23.5	23.3	23.0	22.9	22.7	22.3	22.0	36
38				23.7	23.7	23.4	23.2	22.9	22.7	22.5	22.2	21.9	21.7	21.4	21.2	20.9	20.8	20.5	20.2	19.9	38
40				21.8	21.8	21.5	21.3	21.0	20.9	20.6	20.3	20.1	19.8	19.6	19.3	19.0	18.9	18.6	18.3	18.0	40
42				20.0	19.8	19.6	19.4	19.2	18.9	18.7	18.4	18.1	17.9	17.6	17.3	17.2	16.9	16.6	16.3	16.0	42
44					18.3	18.1	17.8	17.7	17.4	17.1	16.8	16.6	16.3	16.1	15.8	15.7	15.4	15.1	14.8	14.4	44
46						16.7	16.4	16.3	16.0	15.7	15.5	15.2	15.0	14.7	14.4	14.3	14.0	13.7	13.4	13.0	46
48							15.2	15.0	14.7	14.5	14.2	14.0	13.7	13.4	13.1	13.0	12.8	12.4	12.1	11.8	48
50							14.0	13.8	13.6	13.3	13.0	12.8	12.5	12.3	12.0	11.9	11.6	11.3	10.9	10.5	50
52								12.7	12.5	12.3	12.0	11.8	11.5	11.2	10.9	10.8	10.5	10.2	9.9	9.5	52
54									11.5	11.3	11.0	10.8	10.5	10.2	9.9	9.8	9.6	9.2	8.9	8.5	54
56										10.3	10.1	9.9	9.6	9.3	9.0	8.9	8.6	8.3	8.0	7.6	56
58										9.5	9.2	9.0	8.7	8.5	8.2	8.1	7.8	7.5	7.1	6.7	58
60											8.4	8.2	7.9	7.7	7.4	7.3	7.0	6.7	6.4	6.0	60
62												7.5	7.2	6.9	6.6	6.6	6.3	6.0	5.6	5.2	62
64													6.5	6.3	6.0	5.9	5.6	5.3	4.9	4.5	64
66														5.8	5.6	5.3	5.2	5.0	4.6	4.3	66
68															5.0	4.7	4.6	4.3	4.0	3.7	68
70																4.1	4.1	3.8	3.4	3.1	70
72																	3.5	3.2	2.9	2.6	72
74																		2.7			74
76																					76
倍率(Φ28)	7	7	7	7	7	7	7	7	7	7	7	7	6	6	6	5	5	4	4	4	倍率(Φ28)

- 注意：1、实际起重重量必须从本表的额定起重重量中减去吊钩、吊具及缠绕在吊钩及臂头上的钢丝绳的重量。
- 2、表中额定载荷是在水平坚硬地面、重物被缓慢平稳吊起、非行走吊重工作时的值。
- 3、表中额定载荷基于主臂臂节不含塔臂后拉板及臂头滑轮组的计算值。
- 4、主臂长度超过75m须使用斜模块辅助起臂，且必须使用腰绳。
- 5、***处转台配重80t， **处转台配重90t。

固定副臂工况(HF)载荷表
Fixed Jib (HF) Lifting Load Chart

标准：GB/DIN/ISO 360° 回转 转台配重：100t 车身配重：30t
固定副臂：36m 主副臂夹角：10° 主臂长度：24m~66m

F36	主臂长度Boom length															F36	
工作半径 (m)	H24 t	H27 t	H30 t	H33 t	H36 t	H39 t	H42 t	H45 t	H48 t	H51 t	H54 t	H57 t	H60 t	H63 t	H66 t	工作半径 (m)	
15	37.6															15	
16	37.2	36.7	36.3	35.8												16	
17	36.7	36.3	35.9	35.4	35.0	34.5	34.1	33.5								17	
18	36.3	35.9	35.5	35.0	34.7	34.2	33.8	33.3	32.8	32.2	31.6	31.0				18	
19	35.9	35.4	35.1	34.7	34.3	33.9	33.5	33.0	32.5	32.0	31.4	30.8	30.2	29.5	28.7	19	
20	35.4	35.0	34.7	34.3	34.0	33.5	33.1	32.7	32.3	31.7	31.2	30.6	30.0	29.3	28.6	20	
22	34.6	34.1	33.8	33.5	33.2	32.8	32.5	32.1	31.7	31.2	30.7	30.2	29.6	29.0	28.3	22	
24	33.7	33.3	33.0	32.7	32.5	32.1	31.8	31.4	31.1	30.7	30.2	29.7	29.2	28.6	28.0	24	
26	32.9	32.5	32.1	31.9	31.7	31.4	31.1	30.8	30.5	30.1	29.7	29.2	28.8	28.2	27.6	26	
28	32.1	31.7	31.4	31.1	31.0	30.6	30.4	30.1	29.9	29.5	29.2	28.7	28.3	27.8	27.3	28	
30	31.3	30.9	30.6	30.3	30.2	29.9	29.7	29.4	29.3	28.9	28.6	28.2	27.9	27.4	26.9	30	
32	30.5	30.1	29.9	29.6	29.5	29.2	29.1	28.8	28.7	28.4	28.1	27.7	27.4	26.9	26.5	32	
34	29.8	29.4	29.2	28.9	28.8	28.6	28.4	28.2	28.1	27.8	27.5	27.2	26.9	26.5	26.0	34	
36	28.7	28.4	28.2	28.0	27.7	27.5	27.3	27.0	26.8	26.6	26.3	26.1	25.9	25.6	25.4	36	
38	26.6	26.3	26.1	25.8	25.6	25.4	25.1	24.9	24.6	24.4	24.2	23.9	23.7	23.4	23.2	38	
40	24.7	24.4	24.2	23.9	23.7	23.4	23.2	22.9	22.7	22.5	22.2	22.0	21.7	21.5	21.2	40	
42	23.0	22.7	22.5	22.2	22.0	21.7	21.5	21.2	21.0	20.7	20.5	20.2	20.0	19.7	19.5	42	
44	21.5	21.2	21.0	20.7	20.5	20.2	19.9	19.7	19.4	19.2	18.9	18.6	18.4	18.1	17.9	44	
46	20.1	19.8	19.6	19.3	19.1	18.8	18.5	18.2	18.0	17.7	17.5	17.2	17.0	16.7	16.5	46	
48	18.8	18.5	18.3	18.0	17.8	17.5	17.2	17.0	16.7	16.4	16.2	15.9	15.7	15.4	15.1	48	
50	17.7	17.4	17.1	16.8	16.6	16.3	16.1	15.8	15.5	15.3	15.0	14.7	14.5	14.2	13.9	50	
52	16.6	16.3	16.0	15.8	15.5	15.2	15.0	14.7	14.5	14.2	13.9	13.6	13.4	13.1	12.8	52	
54	15.6	15.3	15.0	14.8	14.5	14.2	14.0	13.7	13.5	13.2	12.9	12.6	12.4	12.1	11.8	54	
56	14.6	14.4	14.1	13.8	13.6	13.3	13.1	12.8	12.5	12.2	12.0	11.7	11.4	11.1	10.9	56	
58		13.5	13.3	13.0	12.8	12.5	12.2	11.9	11.7	11.4	11.1	10.8	10.6	10.3	10.0	58	
60		12.0	12.7	12.4	12.2	11.9	11.7	11.4	11.1	10.9	10.6	10.3	10.0	9.8	9.5	9.2	60
62			11.7	11.4	11.2	10.9	10.6	10.3	10.1	9.8	9.5	9.3	9.0	8.7	8.4	62	
64				10.7	10.5	10.2	9.9	9.6	9.4	9.1	8.8	8.5	8.3	8.0	7.7	64	
66					9.8	9.5	9.3	9.0	8.7	8.5	8.2	7.9	7.6	7.3	7.1	66	
68					9.2	8.9	8.7	8.4	8.1	7.8	7.6	7.3	7.0	6.7	6.4	68	
70						8.3	8.1	7.8	7.5	7.2	7.0	6.7	6.4	6.1	5.9	70	
72							7.5	7.2	7.0	6.7	6.4	6.1	5.9	5.6	5.3	72	
74								6.7	6.4	6.2	5.9	5.6	5.3	5.0	4.8	74	
76								6.1	5.9	5.6	5.4	5.1	4.8	4.5	4.3	76	
78									5.4	5.2	4.9	4.6	4.4	4.1	3.8	78	
80										4.7	4.4	4.2	3.9	3.6	3.3	80	
82											4.0	3.7	3.5	3.2	2.9	82	
84												3.3	3.1	2.8	2.5	84	
86													2.9	2.7		86	
倍率(Φ28)	3	3	3	3	3	3	3	3	2	2	2	2	2	2	2	倍率(Φ28)	

固定副臂工况(HF)载荷表
Fixed Jib (HF) Lifting Load Chart

标准: GB/DIN/ISO 360° 回转 转台配重: 100t 车身配重: 30t
固定副臂: 9m 主副臂夹角: 30° 主臂长度: 24m~81m

F9	主臂长度Boom length																				F9		
工作半径 (m)	H24 t	H27 t	H30 t	H33 t	H36 t	H39 t	H42 t	H45 t	H48 t	H51 t	H54 t	H57 t	H60 t	H63 t	H66 t	H69 t	H72 t	H75 t	H78 t	H81 t	工作半径 (m)		
11	91.4**	92.4*	93.3																		11		
12	88.0	89.2	90.3	91.3	92.1	92.8	90.9														12		
13	84.9	86.3	87.5	88.6	89.6	90.4	89.0	86.9	85.0	83.3	81.7										13		
14	82.1	83.6	85.0	86.1	87.2	88.1	87.3	85.3	83.5	81.8	80.3	78.7	76.0	72.5	69.2						14		
15	79.5	81.1	82.6	83.8	85.0	86.0	85.6	83.7	82.0	80.4	79.0	77.7	75.0	71.8	68.5	65.1	59.6	57.1	54.9		15		
16	77.2	78.9	80.4	81.7	82.9	83.8	82.3	80.9	79.5	78.2	76.9	75.6	74.3	70.9	67.7	64.5	58.9	56.6	53.7	53.4	16		
17	75.0	76.7	77.8	77.7	77.6	77.5	76.9	75.6	74.3	73.1	71.9	70.7	69.5	68.3	67.0	63.8	58.3	55.9	52.5	52.7	17		
18	71.9	71.8	71.7	71.6	71.6	71.4	71.3	70.8	69.7	68.5	67.4	66.3	65.2	64.1	63.1	62.0	57.7	55.4	51.4	51.7	18		
19	66.7	66.6	66.5	66.4	66.3	66.2	66.0	65.9	65.5	64.4	63.4	62.4	61.3	60.3	59.4	58.4	57.0	54.8	50.3	50.6	19		
20	62.1	62.0	61.9	61.7	61.6	61.5	61.4	61.2	61.1	60.7	59.8	58.8	57.8	56.9	56.0	55.1	54.3	53.4	49.2	49.6	20		
22	54.3	54.2	54.1	54.0	53.9	53.7	53.6	53.4	53.3	53.1	52.9	52.6	51.7	50.9	50.1	49.2	48.6	47.8	46.9	46.1	22		
24	48.1	47.9	47.8	47.7	47.6	47.4	47.3	47.1	46.9	46.8	46.6	46.4	46.2	45.8	45.1	44.3	43.7	43.0	42.2	41.4	24		
26	42.9	42.8	42.7	42.5	42.4	42.2	42.1	41.9	41.7	41.5	41.4	41.2	41.0	40.8	40.6	40.1	39.5	38.9	38.1	37.4	26		
28	38.5	38.4	38.4	38.2	38.1	37.9	37.7	37.5	37.4	37.2	37.0	36.8	36.6	36.4	36.2	36.0	35.9	35.3	34.6	33.9	28		
30	34.8	34.7	34.7	34.5	34.4	34.2	34.0	33.8	33.7	33.5	33.3	33.1	32.9	32.6	32.4	32.2	32.2	31.9	31.5	30.8	30		
32	31.5	31.5	31.5	31.3	31.2	31.0	30.9	30.6	30.5	30.3	30.1	29.8	29.7	29.4	29.2	29.0	28.9	28.7	28.4	28.1	32		
34		28.6		28.5	28.4	28.3	28.1	27.9	27.7	27.5	27.3	27.1	26.9	26.6	26.4	26.2	26.1	25.9	25.6	25.3	34		
36			26.2	26.0	26.0	25.8	25.6	25.4	25.3	25.0	24.8	24.6	24.4	24.2	23.9	23.7	23.6	23.4	23.1	22.8	36		
38				23.8	23.8	23.6	23.5	23.3	23.1	22.9	22.7	22.4	22.2	22.0	21.8	21.5	21.5	21.2	20.9	20.6	38		
40				21.8	21.8	21.7	21.5	21.3	21.2	20.9	20.7	20.5	20.3	20.1	19.8	19.6	19.5	19.3	18.9	18.7	40		
42					20.0	19.9	19.8	19.6	19.4	19.2	19.0	18.7	18.6	18.3	18.1	17.8	17.8	17.5	17.2	16.9	42		
44						18.3	18.2	18.0	17.9	17.6	17.4	17.2	17.0	16.7	16.5	16.2	16.2	15.9	15.6	15.3	44		
46							16.7	16.5	16.4	16.2	16.0	15.7	15.6	15.3	15.1	14.8	14.7	14.5	14.2	13.9	46		
48								15.2	15.1	14.9	14.7	14.4	14.3	14.0	13.8	13.5	13.4	13.2	12.9	12.6	48		
50								14.0	13.9	13.7	13.5	13.2	13.1	12.8	12.6	12.3	12.2	12.0	11.7	11.4	50		
52									12.7	12.6	12.4	12.1	12.0	11.7	11.5	11.2	11.1	10.9	10.6	10.3	52		
54										11.5	11.3	11.1	10.9	10.7	10.4	10.2	10.1	9.9	9.5	9.3	54		
56											10.5	10.4	10.1	10.0	9.7	9.5	9.2	9.2	8.9	8.6	8.3	56	
58												9.5	9.2	9.1	8.8	8.6	8.4	8.3	8.0	7.7	7.4	58	
60													8.3	8.0	7.8	7.5	7.5	7.2	6.9	6.6	6.0	60	
62														7.5	7.2	7.0	6.8	6.7	6.5	6.2	5.9	62	
64															6.5	6.3	6.0	6.0	5.7	5.4	5.1	64	
66																5.8	5.6	5.4	5.3	5.1	4.8	4.5	66
68																	5.0	4.7	4.7	4.4	4.1	3.8	68
70																		4.1	4.1	3.8	3.5	3.2	70
72																			3.5	3.3	3.0	2.7	72
74																				3.0	2.7		74
倍率(Φ28)	6	6	6	6	6	6	6	6	6	6	6	5	5	5	5	5	5	4	4	4	4	倍率(Φ28)	

- 注意: 1、实际起重重量必须从本表的额定起重重量中减去吊钩、吊具及缠绕在吊钩及臂头上的钢丝绳的重量。
- 2、表中额定载荷是在水平坚硬地面、重物被缓慢平稳吊起、非行走吊重工作时的值。
- 3、表中额定载荷基于主臂臂节不含塔臂后拉板及臂头滑轮组的计算值。
- 4、主臂长度超过75m须使用斜模块辅助起臂, 且必须使用腰绳。
- 5、****处转台配重80t, ***处转台配重90t。


固定副臂工况(HF)载荷表
Fixed Jib (HF) Lifting Load Chart

标准: GB/DIN/ISO 360° 回转 转台配重: 100t 车身配重: 30t
固定副臂: 36m 主副臂夹角: 30° 主臂长度: 24m~66m

F36	主臂长度Boom length																		F36
工作半径 (m)	H24 t	H27 t	H30 t	H33 t	H36 t	H39 t	H42 t	H45 t	H48 t	H51 t	H54 t	H57 t	H60 t	H63 t	H66 t				工作半径 (m)
26	28.4																		26
28	27.0	27.2	27.4	27.6	27.8	28.0	28.1	28.3	28.1										28
30	25.6	25.9	26.2	26.4	26.6	26.8	27.0	27.2	27.3	26.7	26.1	25.7	25.2	24.8	23.8	30			30
32	24.4	24.7	25.0	25.3	25.5	25.8	26.0	26.1	26.3	25.9	25.4	25.0	24.5	24.2	23.8	32			32
34	23.3	23.7	24.0	24.3	24.5	24.8	25.0	25.2	25.4	25.2	24.8	24.3	23.9	23.6	23.2	34			34
36	22.3	22.7	23.0	23.3	23.6	23.9	24.1	24.3	24.6	24.6	24.1	23.7	23.4	23.0	22.7	36			36
38	21.4	21.8	22.1	22.5	22.8	23.0	23.3	23.5	23.8	23.9	23.5	23.2	22.8	22.5	22.2	38			38
40	20.6	21.0	21.3	21.7	22.0	22.3	22.5	22.8	23.0	23.2	23.0	22.6	22.3	22.0	21.7	40			40
42	19.8	20.2	20.6	20.9	21.2	21.5	21.8	22.1	22.3	22.5	22.5	22.1	21.8	21.5	21.3	42			42
44	19.1	19.5	19.9	20.2	20.6	20.9	21.2	21.3	21.2	21.0	20.9	20.7	20.6	20.4	20.2	44			44
46	18.4	18.8	19.2	19.6	19.9	20.1	20.0	19.8	19.6	19.5	19.3	19.1	19.0	18.8	18.7	46			46
48	17.8	18.2	18.6	19.0	18.9	18.8	18.6	18.4	18.2	18.1	17.9	17.7	17.6	17.4	17.2	48			48
50	17.3	17.7	18.0	17.8	17.7	17.5	17.3	17.1	17.0	16.8	16.6	16.4	16.2	16.1	15.9	50			50
52	16.8	17.0	16.8	16.7	16.5	16.3	16.1	15.9	15.8	15.6	15.4	15.2	15.0	14.9	14.7	52			52
54	16.1	15.9	15.8	15.6	15.4	15.2	15.1	14.9	14.7	14.5	14.3	14.1	13.9	13.7	13.6	54			54
56	15.1	14.9	14.8	14.6	14.4	14.2	14.0	13.8	13.7	13.5	13.3	13.1	12.9	12.7	12.5	56			56
58	14.1	13.9	13.8	13.6	13.5	13.3	13.1	12.9	12.7	12.5	12.3	12.1	11.9	11.7	11.5	58			58
60		13.0	12.9	12.7	12.6	12.4	12.2	12.0	11.8	11.6	11.4	11.2	11.1	10.8	10.6	60			60
62		12.1	12.0	11.9	11.8	11.6	11.4	11.2	11.0	10.8	10.6	10.4	10.2	10.0	9.8	62			62
64			11.2	11.1	11.0	10.8	10.6	10.4	10.2	10.0	9.8	9.6	9.4	9.2	9.0	64			64
66				10.3	10.2	10.0	9.9	9.7	9.5	9.3	9.1	8.9	8.7	8.5	8.3	66			66
68					9.5	9.3	9.2	9.0	8.8	8.6	8.4	8.2	8.0	7.8	7.6	68			68
70					8.7	8.6	8.5	8.3	8.1	7.9	7.7	7.5	7.3	7.1	6.9	70			70
72						7.9	7.8	7.7	7.5	7.3	7.1	6.9	6.7	6.5	6.3	72			72
74							7.2	7.0	6.9	6.7	6.5	6.3	6.1	5.9	5.7	74			74
76								6.4	6.3	6.1	5.9	5.7	5.5	5.3	5.1	76			76
78									5.7	5.6	5.4	5.2	5.0	4.8	4.6	78			78
80										5.2	5.0	4.9	4.7	4.5	4.3	80			80
82											4.5	4.3	4.1	4.0	3.8	82			82
84												3.8	3.6	3.5	3.3	84			84
86													3.2	3.0	2.8	86			86
88														2.7	2.6	88			88
90																90			90
倍率(Φ28)	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	倍率(Φ28)			

- 注意: 1、实际起重重量必须从本表的额定起重重量中减去吊钩、吊具及缠绕在吊钩及臂头上的钢丝绳的重量。
- 2、表中额定载荷是在水平坚硬地面、重物被缓慢平稳吊起、非行走吊重工作时的值。
- 3、表中额定载荷基于主臂臂节不含塔臂后拉板及臂头滑轮组的计算值。
- 4、主臂长度超过63m须使用斜模块辅助起臂。

盾构工况工作范围图
TBM Working Area



盾构工况臂节组合
TBM Combination

A、盾构工况主臂臂节组合

名称及数量	主臂底节臂 10.5m	主臂中间节 3m	主臂中间节 6m	主臂变径节 12m	主臂连接节 1.5m	主臂臂头滑轮组
主臂长度						
HB24	1	0	0	1	1	1
HB27	1	1	0	1	1	1
HB30	1	0	1	1	1	1

B、盾构工况副臂臂节组合

名称及数量	副臂底节臂 4.5m	副臂中间节 3m	副臂顶节臂 4.5m
副臂长度			
F9	1	0	1
F12	1	1	1

注释：为防止事故的发生，当使用盾构工况时，主臂必须使用重量大于3.9t的起重钩，固定副臂必须使用重量大于2.5t的起重钩。

盾构工况起臂表
TBM Boom Raising Table

I、配重组合(转台配重+车身配重): 100t+30t

固定副臂长度	F9	F12
主臂长度		
HB24	●	●
HB27	●	●
HB30	●	●

II、配重组合(转台配重+车身配重): 90t+30t

固定副臂长度	F9	F12
主臂长度		
HB24	●	●
HB27	●	●
HB30	●	●

III、配重组合(转台配重+车身配重): 80t+30t

固定副臂长度	F9	F12
主臂长度		
HB24	●	●
HB27	●	●
HB30	●	●

注释：1. 起臂时，请将履带驱动轮置于车体在后方起臂
2. “●” --可以起臂。

盾构工况(HBF)载荷表
TBM Combination

A、盾构工况(HBF_100t+30t_10°)主钩单独吊装载荷表

标准：GB/DIN/ISO 360° 回转 转台配重：100t 中央配重：30t
副臂长度:9m ~ 12m 主副臂夹角:10° 主臂长度:24m ~ 30m(副臂空钩)

Table with 5 columns: 副臂长度(m), 主臂长度(m), 副臂长度(m), 主臂长度(m), 副臂长度(m). Rows include load capacity data for various configurations.

Table with 5 columns: 副臂长度(m), 主臂长度(m), 副臂长度(m), 主臂长度(m), 副臂长度(m). Rows include load capacity data for various configurations.

B、盾构工况(HBF_100t+30t_10°)副钩单独吊装载荷表

标准：GB/DIN/ISO 360° 回转 转台配重：100t 中央配重：30t
副臂长度:9m ~ 12m 主副臂夹角:10° 主臂长度:24m ~ 30m(主臂空钩)

Table with 5 columns: 副臂长度(m), 主臂长度(m), 副臂长度(m), 主臂长度(m), 副臂长度(m). Rows include load capacity data for various configurations.

Table with 5 columns: 副臂长度(m), 主臂长度(m), 副臂长度(m), 主臂长度(m), 副臂长度(m). Rows include load capacity data for various configurations.

- 注意： 1、实际起重重量须从表中额定起重重量减去主副吊钩、吊具及缠绕在二吊钩及臂头上的钢丝绳的重量。
- 2、表中额定载荷是在水平坚硬地面、重物被缓慢平稳吊起、非行走吊重工作时的值。
- 3、表中额定载荷基于主臂臂节不含塔臂后拉板的计算值。
- 4、主钩钢丝绳直径Φ28，副钩钢丝绳直径Φ26。
- 5、副钩吊载，主臂必须带吊钩且保证主臂载荷（5~10）t。

盾构工况(HBF)主副钩复合吊装载荷表
TBM Combination

C、盾构工况(HBF_100t+30t_10°)主副钩复合动作载荷表

标准：GB/DIN/ISO 360° 回转 转台配重：100t 车身配重：30t
副臂长度:9m ~ 12m 主副臂夹角:10° 主臂长度:24m ~ 30m

1.主臂长度24m，主副臂带钩复合吊装

Table with 10 columns: 主臂角度, 主钩半径, 主钩载荷, 副钩半径, 副钩载荷, 主钩加副钩总载荷, 主臂角度, 主钩半径, 主钩载荷, 副钩半径, 副钩载荷, 主钩加副钩总载荷. Rows include load capacity data for various configurations.


标准：GB/DIN/ISO 360° 回转 转台配重：100t 车身配重：30t
副臂长度:9m ~ 12m 主副臂夹角:10° 主臂长度:24m ~ 30m

3.主臂长度30m，主副臂带钩复合吊装

Table with 10 columns: 主臂角度, 主钩半径, 主钩载荷, 副钩半径, 副钩载荷, 主钩加副钩总载荷, 主臂角度, 主钩半径, 主钩载荷, 副钩半径, 副钩载荷, 主钩加副钩总载荷. Rows include load capacity data for various configurations.

- 注意： 1、实际起重重量须从表中额定起重重量减去吊钩、吊具及缠绕在吊钩及臂头上的钢丝绳的重量。
- 2、表中额定载荷是在水平坚硬地面、重物被缓慢平稳吊起、非行走吊重工作时的值。
- 3、表中额定载荷基于主臂臂节不含塔臂后拉板的计算值。
- 4、当主钩加副钩实际吊装载荷大于副钩载荷的60%时，严禁向副钩方向做翻身动作。
- 5、主钩钢丝绳直径Φ28，副钩钢丝绳直径Φ26。

塔式工况工作范围图
Tower Jib Working Area



塔式工况臂节组合
Tower Jib Combinations

A、塔式工况主臂臂节组合

名称及数量	主臂底节臂 10.5m	主臂中间节 3m	主臂中间节 6m	主臂中间节 12mA	主臂变径节 12m	主臂连接节 1.5m
H24	1	0	0	0	1	1
H27	1	1	0	0	1	1
H30	1	0	1	0	1	1
H33	1	1	1	0	1	1
H36	1	0	0	1	1	1
H39	1	1	0	1	1	1
H42	1	0	1	1	1	1
H45	1	1	1	1	1	1
H48	1	0	0	2	1	1
H51	1	1	0	2	1	1
H54	1	0	1	2	1	1
H57	1	1	1	2	1	1
H60	1	0	0	3	1	1
H63	1	1	0	3	1	1

B、塔式工况副臂臂节组合

名称及数量	塔式副臂底节臂 9m	塔式副臂中间节 6mA	塔式副臂中间节 6mB	塔式副臂中间节 12m	塔式副臂顶节臂 9m
W24	1	1	0	0	1
W30	1	1	1	0	1
W36	1	1	0	1	1
W42	1	1	1	1	1
W48	1	1	0	2	1
W54	1	1	1	2	1
W60	1	1	0	3	1
W66	1	1	1	3	1

I、配重组合(转台配重+车身配重): 100t+30t

主臂长度	H24	H27	H30	H33	H36	H39	H42	H45	H48	H51	H54	H57	H60	H63
固定副臂长度														
W24	●	●	●	●	●	●	●	●	●	●	●	●	○	○
W30	●	●	●	●	●	●	●	●	●	●	●	●	○	○
W36	●	●	●	●	●	●	●	●	●	●	●	●	○	○
W42	●	●	●	●	●	●	●	●	●	●	●	●	○	○
W48	●	●	●	●	●	●	●	●	●	●	●	●	○	○
W54	●	●	●	●	●	●	●	●	●	●	●	●	○	○
W60	●	●	●	●	●	●	●	●	●	●	●	●	○	○
W66	●	●	●	●	●	●	●	●	●	●	●	●	○	○

II、配重组合(转台配重+车身配重): 90t+30t

主臂长度	H24	H27	H30	H33	H36	H39	H42	H45	H48	H51	H54	H57	H60	H63
固定副臂长度														
W24	●	●	●	●	●	●	●	●	●	●	●	○	○	×
W30	●	●	●	●	●	●	●	●	●	●	●	○	○	×
W36	●	●	●	●	●	●	●	●	●	●	●	○	○	×
W42	●	●	●	●	●	●	●	●	●	●	●	○	○	×
W48	●	●	●	●	●	●	●	●	●	●	●	○	○	×
W54	●	●	●	●	●	●	●	●	●	●	●	○	○	×
W60	●	●	●	●	●	●	●	●	●	●	●	○	○	×
W66	●	●	●	●	●	●	●	●	●	●	●	○	○	×

III、配重组合(转台配重+车身配重): 80t+30t

主臂长度	H24	H27	H30	H33	H36	H39	H42	H45	H48	H51	H54	H57	H60	H63
固定副臂长度														
W24	●	●	●	●	●	●	●	●	●	●	○	○	×	×
W30	●	●	●	●	●	●	●	●	●	●	○	○	×	×
W36	●	●	●	●	●	●	●	●	●	●	○	○	×	×
W42	●	●	●	●	●	●	●	●	●	●	○	○	×	×
W48	●	●	●	●	●	●	●	●	●	●	○	○	×	×
W54	●	●	●	●	●	●	●	●	●	●	○	○	×	×
W60	●	●	●	●	●	●	●	●	●	●	○	○	×	×
W66	●	●	●	●	●	●	●	●	●	●	○	○	×	×

注释: 1. 起臂时, 请将履带驱动轮置于车体后方。
2. “●” --可以起臂。 “○” --需要模块起臂。 “×” --不可起臂, 工况不可使用。

塔式工况(HW)载荷表
Tower Jib (HW) Lifting Load Chart

标准：GB/DIN/ISO 360° 回转 转台配重：100t 车身配重：30t
主臂长度：24m 塔臂长度：24m~66m

Table with 13 columns: H24, 主臂长度24m Boom length 24m, H24. Rows include tower jib length (m), tower jib angle (°), working radius (m), and capacity (t) for various configurations.

Table with 13 columns: H24, 主臂长度24m Boom length 24m, H24. Rows include tower jib length (m), tower jib angle (°), working radius (m), and capacity (t) for various configurations.

注意：1、实际起重重量必须从本表的额定起重重量中减去吊钩、吊具及缠绕在吊钩及臂头上的钢丝绳的重量。
2、表中额定载荷是在水平坚硬地面、重物被缓慢平稳吊起、非行走吊重工作时的值。
3、表中额定载荷基于主臂臂节不含臂头滑轮组的计算值。

塔式工况(HW)载荷表
Tower Jib (HW) Lifting Load Chart

标准：GB/DIN/ISO 360° 回转 转台配重：100t 车身配重：30t
主臂长度：36m 塔臂长度：24m~66m

Table with 13 columns: H36, 主臂长度36m Boom length 36m, H36. Rows include tower jib length (m), tower jib angle (°), working radius (m), and capacity (t) for various configurations.

Table with 13 columns: H36, 主臂长度36m Boom length 36m, H36. Rows include tower jib length (m), tower jib angle (°), working radius (m), and capacity (t) for various configurations.

注意：1、实际起重重量必须从本表的额定起重重量中减去吊钩、吊具及缠绕在吊钩及臂头上的钢丝绳的重量。
2、表中额定载荷是在水平坚硬地面、重物被缓慢平稳吊起、非行走吊重工作时的值。
3、表中额定载荷基于主臂臂节不含臂头滑轮组的计算值。

塔式工况(HW)载荷表
Tower Jib (HW) Lifting Load Chart

标准：GB/DIN/ISO 360° 回转 转台配重：100t 车身配重：30t
主臂长度：48m 塔臂长度：24m~66m

Table with 13 columns: H48, 主臂长度48m Boom length 48m, H48. Rows include tower jib length (m), main jib angle (°), working radius (m), and capacity (t) for various configurations.

Table with 13 columns: H48, 主臂长度48m Boom length 48m, H48. Rows include tower jib length (m), main jib angle (°), working radius (m), and capacity (t) for various configurations.

注意：1、实际起重重量必须从本表的额定起重重量中减去吊钩、吊具及缠绕在吊钩及臂头上的钢丝绳的重量。
2、表中额定载荷是在水平坚硬地面、重物被缓慢平稳吊起、非行走吊重工作时的值。
3、表中额定载荷基于主臂臂节不含臂头滑轮组的计算值。

塔式工况(HW)载荷表
Tower Jib (HW) Lifting Load Chart

标准：GB/DIN/ISO 360° 回转 转台配重：100t 车身配重：30t
主臂长度：60m 塔臂长度：24m~66m

Table with 13 columns: H60, 主臂长度60m Boom length 60m, H60. Rows include tower jib length (m), main jib angle (°), working radius (m), and capacity (t) for various configurations.

Table with 13 columns: H60, 主臂长度60m Boom length 60m, H60. Rows include tower jib length (m), main jib angle (°), working radius (m), and capacity (t) for various configurations.

注意：1、实际起重重量必须从本表的额定起重重量中减去吊钩、吊具及缠绕在吊钩及臂头上的钢丝绳的重量。
2、表中额定载荷是在水平坚硬地面、重物被缓慢平稳吊起、非行走吊重工作时的值。
3、表中额定载荷基于主臂臂节不含臂头滑轮组的计算值。
4、起臂必须使用斜楔块。

塔式工况(HW)载荷表
Tower Jib (HW) Lifting Load Chart

标准：GB/DIN/ISO 360° 回转 转台配重：100t 车身配重：30t
主臂长度：63m 塔臂长度：24m~48m

H63	主臂长度63m Boom length 63m												H63
塔臂长度 (m)	W24			W30			W36			W42			塔臂长度 (m)
主臂角度 (°)	85°	75°	65°	85°	75°	65°	85°	75°	65°	85°	75°	65°	主臂角度 (°)
工作半径 (m)	t	t	t	t	t	t	t	t	t	t	t	t	工作半径 (m)
16	60.2												16
17	58.8			51.9									17
18	57.4			51.1									18
19	55.3			50.1			44.2						19
20	52.7			48.5			43.6			37.9			20
22	47.7			44.5			40.9			36.9			22
24	42.9			40.6			37.8			34.5			24
26	38.6			36.9			34.8			32.1			26
28	34.6			33.4			31.8			29.7			28
30	31.0			30.1			29.0			27.3			30
32		28.5		27.2			26.4			25.1			32
34		26.5		24.5	25.6		23.9			22.9			34
36		24.6		22.1	24.0		21.7	23.1		20.9			36
38		22.9			22.4		19.6	21.8		19.1	20.8		38
40		21.4			20.9		17.7	20.5		17.3	19.6		40
44			14.5		18.4			18.0		14.2	17.4		44
46			13.6		17.3			16.9		12.8	16.4		46
48			12.8			12.1		16.0			15.4		48
50			12.1			11.4		15.1			14.5		50
52			11.3			10.8		14.2	10.3		13.7		52
56					9.6				9.2		12.3	8.5	56
58									8.6		11.6	8.0	58
62									7.7			7.1	62
64												6.7	64
68												5.9	68
倍率(Φ28)	4	2	1	4	2	1	3	2	1	3	2	1	倍率(Φ28)

H63	主臂长度63m Boom length 63m			H63
副臂长度 (m)	W48			副臂长度 (m)
主臂角度 (°)	85°	75°	65°	主臂角度 (°)
工作半径 (m)	t	t	t	工作半径 (m)
22	32.2			22
24	31.0			24
26	29.2			26
28	27.3			28
30	25.4			30
32	23.5			32
34	21.7			34
36	19.9			36
38	18.3			38
40	16.7			40
42	15.2	17.7		42
44	13.9	16.8		44
46	12.6	15.9		46
48	11.4	14.9		48
50	10.3	14.1		50
52	9.2	13.3		52
54		12.6		54
56		11.9		56
58		11.2	7.5	58
60		10.6	7.0	60
62		10.1	6.6	62
64		9.6	6.2	64
66			5.8	66
70			5.2	70
74			4.5	74
倍率(Φ28)	2	2	1	倍率(Φ28)

注意：1、实际起重量必须从本表的额定起重量中减去吊钩、吊具及缠绕在吊钩及臂头上的钢丝绳的重量。
2、表中额定载荷是在水平坚硬地面、重物被缓慢平稳吊起、非行走吊重工作时的值。
3、表中额定载荷基于主臂臂节不含臂头滑轮组的计算值。
4、起臂必须使用斜楔块。

说明：

- 表中额定起重量，指在给定的臂架长度、工作幅度条件下，重物自由悬挂，在坚实、平坦地面作业所能保证的最大起重量。作业者须视各种不良条件（如地面松软或不平、风力、侧面负荷、摆动作用、多台起重合力起吊）限制或降低起重机的起重量。
- 表中额定起重量包括吊钩、钢丝绳、和其它所有吊具的重量。
- 表中没有列出额定值的空白区，不允许将起重机用于该区所对应的起重作业。

Notes：

- The total rated lifting loads shown in above tables are the max. lifting capacity based on the condition that crane set up on firm and level ground with given boom length, radius and load, crane operator shall limit or reduce lifting loads according to variable working conditions (soft or uneven ground, wind, side loading, slewing action, lifting with one more cranes).
- The total rated lifting loads include the weight of hook block, wire rope and other slings.
- The blank area in above tables means crane operation is not allowed corresponding to these areas.