



混凝土泵车HB30K

Truck mounted concrete Boom Pump HB30K

Specifications

类别 Category	项目 Item	单位 Unit	HB30K
整车参数 Overall parameter	外形尺寸 Outline dimension	mm	10190×2500×3700
	整机重量 Overall weight	kg	20000
底盘 Chassis	型号 Model		ZZ5207M521GC1 / ZZ5207M521GD1
	生产厂家 Manufacturer		Sinotruk
	最高速度 Max. speed	km/h	90
	最大爬坡度 Max. grade-ability	%	35
	轴距 Wheelbase	mm	5200
	轮胎规格 Tire		11.00R20
发动机 Engine	型号 Model		MC07.28-30 / MC07.28-40
	最大功率 Max. power	kw	203
	最大扭矩 Max. torque	N·m/(r/min)	1100/1200-1800
	排量 Displacement	L	6.87
	排放标准 Emission standard		Euro III / Euro IV
泵送系统 Pumping system	理论输送量 Theoretical output	m ³ /h	100
	泵送压力 Concrete pumping pressure	MPa	8
	理论泵送次数 Theoretical pumping times	Time/min	25
	输送缸内径 × 行程 Delivery cylinder diameter × stroke	mm	φ230×1600
	泵送混凝土骨料最大直径 Max. diameter of pumping concrete aggregate	mm	40
	上料高度 Filling height	mm	1550
	泵送混凝土塌落度范围 Concrete slump range	cm	8 ~ 23
布料杆 Placing boom	布料杆可达高度 Reach height	m	29.6
	布料杆可达深度 Reach depth	m	18
	布料杆回转半径 Slewing radius	m	25.7
	布料杆回转角度 Slewing angle	°	±270
	第一节臂伸展角度 Unfolding angle of the 1st section	°	90
	第二节臂伸展角度 Unfolding angle of the 2nd section	°	180
	第三节臂伸展角度 Unfolding angle of the 3rd section	°	250
	第四节臂伸展角度 Unfolding angle of the 4th section	°	235
支腿跨距 Stabilizer span	支腿纵向跨距 Longitudinal span of stabilizer	mm	6100
	前支腿横跨距 Transverse span of front stabilizer	mm	5555
	后支腿横跨距 Transverse span of rear stabilizer	mm	4810
其它 Others	配料型式 Transfer tube		裙阀 Rock valve
	润滑方式 Lubrication method		自动润滑 Automatic lubrication
	控制方式 Control method		手动 / 遥控 Manual/remote control
	水箱容积 Volume of water box	L	400

Specifications subject to change without prior notice. Photos for illustrative purpose only.

