

## **BAOJI XUAN TAI PIGMENT TECHNOLOGY CO., LTD.**

ADD: ROOM, NO. 1608, BUILDING B, WEILAN INTERNATIONAL MANSION, DAQING 3RD ROAD, LIANHU DISTRICT, XI'AN, SHAANXI, CHINA.

# Tel/Fax: +86-029-88888558 Email: info@xtpigment.com

# **Material Safety Data Sheet (MSDS)**

# 1. Identification of the Product and the Company

Trade Name:. IRON OXIDE BLACK

BAOJI XUAN TAI PIGMENT TECHNOLOGY CO., LTD.

Add: ROOM, NO. 1608, BUILDING B, WEILAN INTERNATIONAL MANSION, DAQING 3RD

ROAD, LIANHU DISTRICT, XI'AN, SHAANXI, CHINA.

Tel.: +86 +86-029- 88888558

### 2. Composition / Information on Ingredients

CAS NO: 1309-38-2

Synthetic Iron Oxide Fe3O4.

OSHA's Hazard Communication Standard (29 CFR 1910.1200):

This substance is not considered to be a hazardous substance as defined under OSHA's hazard communication standard.

#### 3. Hazards Identification

Not classified as dangerous for supply or conveyance under EEC directives 67/548, 77/728, 88/379, 91/155.

This product is in compliance with CONEG Model legislation for packaging and packaging ink components.

#### 4. First Aid Measures:

Eye Contact: In case the pigment comes into contact with eyes, it may cause irritation. In this case flush eyes thoroughly with water for at least 15 minutes. If irritation persists, consult your physician.

Skin Contact: In case pigment comes into contact with skin, it may cause irritation. In which case wash skin with soap and water. Remove severely contaminated clothing and clean before reuse. Seek medical attention if irritation persists.

Inhalation: In case the pigment is inhaled and causes respiratory difficulty proceed to area of fresh air. Get medical attention if necessary.

Ingestion: In case the pigment is ingested, it is not considered to be taxte. If swallowed, dilute with water and induce vomiting. Never give fluids or induce vomiting to an unconscious person or person having convulsions. Seek medical attention immediately this case.

# **5. Fire Fighting Measures**

Flammability Class: Not flammable

Extinguishing Medium: Carbon Dioxide, dry chemical or foam. Special Fire Fighting Procedures: Wear self-contained breathing apparatus and full protective equipment

#### 6. Accidental Release Measures



## **BAOJI XUAN TAI PIGMENT TECHNOLOGY CO., LTD.**

ADD: ROOM, NO. 1608, BUILDING B, WEILAN INTERNATIONAL MANSION, DAQING 3RD ROAD, LIANHU DISTRICT, XI'AN, SHAANXI, CHINA.

Tel/Fax: +86-029-88888558 Email: info@xtpigment.com

Environmental Precautions: Airborne inorganic pigment dust may be an explosion hazard. Secure source of ignition and avoid raising dust. Ventilate area.

Methods of Cleaning Up: Take up mechanically, place in a bag and hold for disposal. Wash spill site after material pick-up.

### 7. Handling and Storage

Handling: Avoid dust formation. If dust formation occurs, take precautionary measures against discharges.

Storage: Keep packaging tightly closed and store in a dry and cool place with adequate ventilation.

### 8. Exposure Controls and Personal Protection

Respiratory Protection: Use dust mask when package is opened.

Ventilation: Local exhaust or containment

Hand protection: Rubber Hand Gloves recommended

Eye Protection: Avoid Eye Contact, Safety Goggles recommended

Body Protection: Impervious clothing

Recommendation for personal protection in accordance with good industrial hygiene and

safety practices.

#### 9. Physical and Chemical Properties

Appearance: Powder

Color: Black Odor: Odorless

pH: 3-7

Boiling point: N/A Melting Point: N/A Ignition Temp: No Data Solubility in Water: Insoluble

Vapor Pressure: Not Applicable

#### 10. Stability and Reactivity

This product is a stable compound under normal storage conditions polymerization will not occur.

### 11. Toxicological Information

Toxicological Test Data: Based upon industry-wide experience and published toxicological studies, inorganic pigments in general are considered to be practically non-toxic. No published data available.



# **BAOJI XUAN TAI PIGMENT TECHNOLOGY CO., LTD.**

ADD: ROOM, NO. 1608, BUILDING B, WEILAN INTERNATIONAL MANSION, DAQING 3RD ROAD, LIANHU DISTRICT, XI'AN, SHAANXI, CHINA.

**Tel/Fax:** +86-029-88888558 Email: info@xtpigment.com

### 12. Ecological Information

Being chemically inert and practically insoluble in water, inorganic pigments are not environmentally hazardous. They may be virtually removed from wastewater mechanically in suitable effluent treatment plants.

### 13. Waste Disposal

Dispose (dump or incinerate) in accordance with applicable federal, state and local regulations.

### 14. Transport information

D.O.T. Shipping Name (49 CFR 172.101-102): None

D.O.T. Hazard Class (49 CFR 172.101-102): None

D.O.T. Label: None

Land transport

ADR/RID/GGVS/GGVE UN – No : None / Not Regulated

Sea transport

IMDG/GGVSee UN – No: None / Not Regulated

Air transport

TCAO/TATA UN-ID No: None / Not Regulated

This product is not classified as dangerous under the relevant EU directives and DOT regulations. Thus, it is not hazardous under transport regulations

#### 15. Regulatory information

OSHA Hazard Communication Standard:

This product is not considered to be a hazardous substance under OSHA's Federal Hazard Communication Standard 29 CFR 1910.1200.

Toxic Substance Control Act (TSCA):

All of the ingredients of this material have been reported to the U.S. EPA and are included in the TSCA Chemical inventory.

SARA Title III:

Section 302 (EHS): None

Section 311/312 (Acute): None

Section 313: None

CONEG:

This product is certified to be in full compliance with CONEG legislation for packaging and packaging Ink components regarding hexavalent chromium, cadming that and forcury.

#### 16. Other information

This information contained is provided in good faith. Although its based on data from sources deemed to be reliable, Baoji Xuan Tai cannot guarantee to conditions resulting from its use.