

Suitcase-style Outdoor Power Station S3900 Specification Sheet

Customer Name	
Product Name	Suitcase-style Outdoor Power Station
Product Model	S3900
Product Code	
Specification Version	V1
Release Date	2024.5.20

Customer Confirmation		
Prepared	Reviewed	Approved

Prepared By	Reviewed	Approved

Change History

[illegible]

	Outdoor Power Supply S3900 Technical Specification Sheet	Version Number	V0
--	--	----------------	----

Table of Contents

1	Introduction.....	2
1.1	About This Product	3
1.2	About This Specification.....	3
2	Product Overview.....	3
3	Application Scenarios.....	3
4	Technical Parameters.....	4
5	Transportation.....	5
6	Dimensions & Mounting Hole Positions.....	5

	Outdoor Power Supply S3900 Technical Specification Sheet	Version Number	V0
--	--	----------------	----

1 Introduction

1.1 About This Product

This Product: Outdoor Power Station

Product Version: This version is for use in Mainland China and Europe.

1.2 About This Specification

This document serves as the baseline for the outdoor power station, specifying and defining the requirements for the product. It is the technical document to be followed during product development and serves as the primary reference for testing, production, marketing, and service. This document primarily describes and defines the product in terms of technical parameters and dimensions.

2 Product Overview

The outdoor power station converts AC power through a charger or bidirectional inverter into DC power, or charges via solar panel DC power, storing energy in the internal battery pack. When needed, the stored power is supplied externally, offering outputs of 48V, 24V, 12V, and 5V. It features a built-in bidirectional inverter.

Product Components: The main components include the battery pack (with BMS) and the bidirectional inverter.

3 Application Scenarios

The bidirectional inverter allows users to power appliances and tools during outdoor work or travel. Compatible devices include: mobile phones, laptops, drones, digital cameras, cameras, lighting, electric shavers, gaming consoles, handheld devices, electric tools, car refrigerators, and various emergency, travel, camping, and medical devices.

Typical scenarios: firefighting, outdoor live streaming, outdoor camping, outdoor air conditioning, refrigerators, etc.

	Outdoor Power Supply S3900 Technical Specification Sheet	Version Number	V0
--	--	----------------	----

4 Technical Parameters				
	Project	S3900		Notes
4.1 Basic Performance				
1	Appearance	No obvious cracks, scratches, or stains		
2	Dimensions (mm)	(636±10)(442±3)(205±10)		
3	Product Weight	(36.5±1) Kg		
4	Protection Level	IP31		
5	Rated Power	3000W		
6	Output Methods	AC: 220V		
7		DC: 12V and 5V		
8	Battery Module Nominal Voltage	25.6V		
9	Battery Module Rated Capacity	156Ah		
10	Battery Energy	3996Wh		
11	AC Output Minimum Energy	3400Wh		(25±2)°C, 1000W charging, 1000W discharging
12	220VAC Output Power	3000W		continuous (overheating triggers automatic protection)
13		6000W		instantaneous
14	USB Charging Port Output	QC3.0: 5V2A; PD: 5V2A		total 30W when used simultaneously
15	DC12V Output (Car Charger Output)	10A		
16	DC 24V Output	Not available by default (can be added)		
17	AC Input (Charging)	220VAC 8A		battery module charging power approx. 2000W
18	Solar Input (Charging)	Voltage: 30-400V, Maximum Power: 1500W		
19	Supports Simultaneous Charging and Discharging	Yes		
20	Cycle Life	1000 cycles		(25±2)°C, 1200W charging, 1200W discharging
21	Warranty	12 months or 1000 cycles		whichever comes first
22	Recommended SOC Usage Range	10% ~ 90%		
23	Charging Operating Temperature	0°C ~ 40°C		
24	Discharge Operating Temperature	-10°C ~ 40°C		
25	Storage Temperature	Short-term (within 1 month)	-10°C ~ 40°C	
		Long-term (within 1 year)	0°C ~ 35°C	
26	Storage Humidity	≤95%		
27	Monthly Self-Discharge Rate	≤3%/month		(25±2)°C, stored at 30% ~ 50% SOC

	Outdoor Power Supply S3900 Technical Specification Sheet	Version Number	V0
--	--	----------------	----

5 Transportation

The product should be packaged and transported at a state of charge (30% ~ 60% SOC). During transportation, avoid severe vibration, impact, or compression, and protect from direct sunlight and rain.

6 Outline Diagram

Product 2D Diagram

