




|   |            |                       |
|---|------------|-----------------------|
| 6 | Cushion    | Low density polythene |
| 5 | Glass part | Toughened glass       |
| 4 | Pin        | Forged steel          |
| 3 | Cement     | High strength cement  |
| 2 | Cotter pin | Stainless steel       |
| 1 | Cap        | Malleable cast iron   |

Mark on the cap and the glass shell

- Mechanical failing load:160 (on the cap)
- Trade mark of the manufacture:QX(on the cap)
- Year of the manufacture(on the glass shell)



### Technical parameters

|                                        |         |
|----------------------------------------|---------|
| Mechanical failing load                | 160kN   |
| Nominal creepage distance              | 380mm   |
| Standard coupling                      | 20R     |
| Dry lighting impulse withstand voltage | 95kV    |
| Power frequency withstand voltage wet  | 50kV    |
| Power frequency puncture voltage       | 130kV   |
| Impulse puncture voltage               | 2.8 p.u |
| Radio interference voltage(10kV,1MHz)  | 50μV    |
| Corona visual test                     | 18/22kV |

### Jiangxi QOCI Electric CO.,LTD.

Click to visit the official website

|        |          |              |
|--------|----------|--------------|
| Design | Standard | Marker       |
| Num    | Sigh     |              |
| Audit  | Date     | Weight 7.3kg |
| Notes  | Approved | Scale 1:1    |



OPEN PROFILE  
TOUGHENED DISC  
GLASS INSULATOR

U160BLA/170