




|   |            |                       |
|---|------------|-----------------------|
| 6 | Cushion    | Low density polythene |
| 5 | Glass part | Toughened glass       |
| 4 | Pin        | Forged steel          |
| 3 | Cement     | High strength cement  |
| 2 | Cotter pin | Stainless steel       |
| 1 | Cap        | Malleable cast iron   |

Mark on the cap and the glass shell

-Mechanical failing load:40 (on the cap)

-Trade mark of the manufacture QX(on the cap)

-Year of the manufacture(on the glass shell)



### Technical parameters

|                                        |         |
|----------------------------------------|---------|
| Mechanical failing load                | 40kN    |
| Nominal creepage distance              | 190mm   |
| Standard coupling                      | 11R     |
| Dry lighting impulse withstand voltage | 50kV    |
| Power frequency withstand voltage wet  | 25kV    |
| Power frequency puncture voltage       | 90kV    |
| Impulse puncture voltage               | 2.8 p.u |
| Radio interference voltage(10kV,1MHz)  | 50μV    |
| Corona visual test                     | 18/22kV |

### Jiangxi QOCI Electric CO.,LTD.

Click to visit the official website

|        |          |           |
|--------|----------|-----------|
| Design | Standard | Marker    |
| Num    | Sigh     |           |
| Audit  | Date     | Weight    |
| Notes  | Approved | Scale 1:1 |



STANDARD PROFILE  
TOUGHENED DISC  
GLASS INSULATOR

**U40B/175**