tesa® 88661 MP PET

Product Information



50µm double coated PET tape

Product Features

- Good initial tack and adhesion to a wide variety surfaces
- Medium shear strength
- Excellent temperature resistance
- Wrinkle resistant PE-coated liner

tesa® 88661 is a transparent, double coated self-adhesive tape consisting of a PET backing and a tackified acrylic adhesive. it is the ideal solution for multi-purpose mounting applications specifically in general industry market and is extremely converting friendly.

<span style="color: var(--attrpanel-color-text, #1a2028); background-color: var(--palette-white, #ffffff)

Application Fields

- Name plate mounting
- Membrane switch mounting
- Foam lamination
- Light strips mounting

Product Construction

Type of liner	PE-coated paper	Color of liner	white/blue logo
Weight of liner	128 g/m²	Total thickness	50 µm
Backing material	PET	Color	transparent
Type of adhesive	tackified acrylic		

Product Properties/Performance Values

Elongation at break	50 %	Tack	good
Static shear resistance at 23°C	medium	Tensile strength	20 N/cm
Temperature resistance long term	100 °C		medium
Temperature resistance short term	200 °C		

For latest information on this product please visit
http://l.tesa.com/?ip=NaN

tesa® 88661 MP PET

Product Information

Adhesion to Values

- Steel (initial) 5.5 N/cm
- PE (initial) 2 N/cm
- PC (after 14 days) 6.6 N/cm
- ABS (initial) 5.1 N/cm
- PP (after 14 days) 5.5 N/cm
- PET (after 14 days) 6 N/cm
- PE (after 14 days) 3.1 N/cm
- ABS (after 14 days) 6.2 N/cm
- PC (initial) 5.6 N/cm
- PET (initial) 5.2 N/cm
- PP (initial) 2 N/cm
- Steel (after 14 days) 7.2 N/cm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit
http://l.tesa.com/?ip=NaN