



# 150AH 12V LiFePO4 Battery

## Technology

Lithium Iron Phosphate (LiFePO4)	
Nominal Voltage	12.8V
Rated Capacity	150Ah
Charge Method	CC/CV
Charge Voltage	14.6V
Bulk/Absorption Voltage	14.6V
BMS Balancing Voltage	Any cell voltage $\geq 3.45V$ Max Voltage difference between cells $> 30mV$ In Charging
Equalize Voltage	Not applicable
Float Voltage *	Not applicable
Temperature Compensation	No/Disable
Charge Cut-off Voltage	14.6V
Discharge Cut-off Voltage	10V
Recommended Charge Current	75A
Recommended Discharge Current	75A
Maximum Continuous Charge Current	120A
Maximum Continuous Discharge Current	120A
Peak Current	180A(10s)
WiFi	No
Bluetooth	Yes
Communication	No
Self Heating	No
Protection Rating	IP65
BMS Protection	<ul style="list-style-type: none"> <li>• Over and Low voltage</li> <li>• Charge and Discharge Over current</li> <li>• Short circuit</li> <li>• High and Low temperature</li> </ul>
Internal Resistance	$\leq 10m\Omega$
BMS Leakage Current	$\leq 10mA$
Charge Temperature Range	32°F (0°C) to 131°F (55°C)
Discharge Temperature Range	-4°F (-20°C) to 131°F (55°C)
Storage Temperature 1 week	-4°F (-20°C) to 149°F (65°C)
Storage Temperature 1 month	-4°F (-20°C) to 113°F(40°C)
Storage Temperature 1 year	-4°F (-20°C) to 77°F (25°C)
Humidity Operating:	5% to 90 % RH
Humidity Storage:	35% to 85% RH
Certifications: MSDS; UN38.3; CE; PSE	
Cycle Life	4000 cycles

## FEATURES:

- Smart BMS(Battery Management System)**  
 Built-in BMS to protect the battery from overcharge, over temperature, over discharge, over current, low temperature and short circuit.
- Superior Thermal Stability & Safety**  
 LiFePO4 chemistry resists thermal runaway and combustion risks, even under extreme conditions, ensuring unmatched operational safety for high-stress environments.
- Extended Cycle Life**  
 With over 3,000-5,000 charge-discharge cycles (80% capacity retention), these batteries deliver long-term reliability, drastically reducing replacement frequency and lifecycle costs.
- High Energy Density**  
 Compact and lightweight design maximizes energy storage capacity per unit, ideal for space-constrained applications
- Eco-Friendly Composition**  
 Free from toxic heavy metals (e.g., cobalt, lead), LiFePO4 batteries align with global sustainability standards (RoHS compliant) and enable easier recycling.
- Low Self-Discharge Rate**  
 Minimizing energy waste and ensuring readiness for seasonal or emergency use.
- Wide Temperature Tolerance**  
 Performs reliably in extreme climates (-20°C to 55°C / -4°F to 131°F), making it adaptable for outdoor solar storage, marine, and automotive applications.
- Maintenance-Free Operation**  
 No memory effect or routine upkeep required, reducing user intervention and total ownership costs.
- BCI Group 31 Size, Universal Fit**  
 ECO-WORTHY 12V 150Ah is crafted to meet the BCI battery size standard "Group 31". It's also a perfect replacement for Group 31 lead-acid and AGM, SLA batteries. Just simply replace your Group31 battery without the hassle of modifying your existing electrical system or wiring.

-Max connected in series and parallel **8 PCs-**

Max connected  
in Parallel  
**4 units**

Max connected  
in Series  
**4 units**

# Unit Dimensions







## Mechanical

Length	13.03 in / 331 mm
Width	6.81 in / 173 mm
Height	8.66 in / 220 mm
Weight	34.6 lbs / 15.7 kg
Terminals	M8 insert

## Materials

Case and Cover	ABS
Color	BLACK



## PLEASE NOTE

- ★ Lithium batteries ship under Class 9 Dangerous Goods PI 965 Section IA. Please contact your carrier company to determine their requirements for shipping. MSDS Sheets are available upon request.
- ★ Float charging is not applicable to lithium iron phosphate batteries, long-term float charging will accelerate battery aging or damage. If you have to set the float voltage for MPPT/PWM charge controller in solar system, we suggest to set it to (12V Battery)13.2V-13.6V, (24V Battery)26.4V-27.2V, (36V Battery)39.6V-40.8V, (48V Battery)52.8V-54.4V.