
NYLON-INSULATED FEMALE TERMINALS (OVAL LUG)

Terminals body:Brass
Plating:Tin plated
Insulation:Nylon
Temperature:105°C







WIRING RANGE mm² (A.W.G.)	ITEM NO.	TAB SIZE	DIMENSIONS (mm)						
			W	L	øD	ød	B	F	T
22-16 A.W.G. 0.5-1.5 mm²	FDFN 1.25-250-T-PS	0.8*6.35	7.6	22.0	3.6	1.7	10.8	7.6	0.4
16-14 A.W.G. 1.5-2.5 mm²	FDFN 2-250-T-PS	0.8*6.35	7.6	21.9	4.8	2.3	10.0	7.6	0.4

NYLON-INSULATED FEMALE TERMINALS(SQUARE HOLE)

Terminals body:Brass
Plating:Tin plated
Insulation:Nylon
Temperature:105°C






WIRING RANGE mm² (A.W.G.)	ITEM NO.	TAB SIZE	DIMENSIONS (mm)						
			W	L	øD	ød	B	F	T
22-16 A.W.G. 0.5-1.5 mm²	FDFN 1.25-110(5)-PS	0.5*2.8	3.8	18.0	3.1	1.7	9.0	6.3	0.3
	FDFN 1.25-110(8)-PS	0.8*2.8	4.0	18.7	3.1	1.7	9.0	6.4	0.3
	FDFN 1.25-187(5)-PS	0.5*4.75	5.8	21.0	3.5	1.7	9.8	6.6	0.35
	FDFN 1.25-187(8)-PS	0.8*4.75	5.9	21.0	3.5	1.7	9.8	6.6	0.35
	FDFN 1.25-250-PS	0.8*6.35	7.6	21.2	3.6	1.7	10.0	7.6	0.4
16-14 A.W.G. 1.5-2.5 mm²	FDFN 2-110(5)-PS	0.5*2.8	4.0	18.7	4.2	2.3	9.0	6.4	0.3
	FDFN 2-110(8)-PS	0.8*2.8	4.0	18.7	4.2	2.3	9.0	6.4	0.3
	FDFN 2-187(5)-PS	0.5*4.75	5.8	21.2	4.3	2.3	9.8	6.6	0.35
	FDFN 2-187(8)-PS	0.8*4.75	5.9	21.2	4.2	2.3	9.8	6.6	0.35
	FDFN 2-250-PS	0.8*6.35	7.6	21.2	4.5	2.3	10.0	7.6	0.4
12-10 A.W.G. 4-6 mm²	FDFN 5.5-250-PS	0.8*6.35	7.6	23.2	8.5	3.4	12.6	7.6	0.45

NYLON-INSULATED FEMALE TERMINALS(TWO CABLES)

Terminals body:Brass
Plating:Tin plated
Insulation:Nylon
Temperature:105°C





WIRING RANGE mm² (A.W.G.)	ITEM NO.	TAB SIZE	DIMENSIONS (mm)						
			W	L	øD	ød	B	F	T
22-16 A.W.G. 0.5-1.5 mm²	FDFN 1.25-110(5)-2-PS	0.5*2.8	4.0	19.0	6.1	1.7	12.0	6.4	0.3
	FDFN 1.25-110(8)-2-PS	0.8*2.8	4.0	19.0	6.1	1.7	12.0	6.4	0.3
	FDFN 1.25-187(5)-2-PS	0.5*4.75	5.9	23.8	6.1	1.7	12.0	6.4	0.35
	FDFN 1.25-187(8)-2-PS	0.8*4.75	5.9	23.8	6.1	1.7	12.0	6.4	0.35
	FDFN 1.25-250-2-PS	0.8*6.35	7.6	24.0	6.0	1.7	13.0	7.6	0.4
16-14 A.W.G. 1.5-2.5 mm²	FDFN 2-187(5)-2-PS	0.5*4.75	5.9	23.8	6.8	2.3	12.0	6.4	0.35
	FDFN 2-187(8)-2-PS	0.8*4.75	5.9	23.8	6.8	2.3	12.0	6.4	0.35
	FDFN 2-250-2-PS	0.8*6.35	7.6	21.2	6.7	2.3	10.0	7.6	0.4