
INSULATED MALE BULLET RECEPTACLE

Terminals body:Brass
Plating:Tin plated
Insulation:Nylon / PC
Temperature:105°C / 115°C







WIRING RANGE mm² (A.W.G.)	ITEM NO.	DIMENSIONS (mm)						
		W	L	øD	ød	B	F	T
22-16 A.W.G. 0.5-1.5 mm²	MPD 1.25-156-PS	4.0	23.0	4.3	1.8	11.6	11.5	0.4
16-14 A.W.G. 1.5-2.5 mm²	MPD 2-156-PS	4.0	23.6	4.3	2.3	11.6	12.0	0.4

NYLON-FULLY INSULATED FEMALE BULLET RECEPTACLE

Terminals body:Brass
Plating:Tin plated
Insulation:Nylon
Temperature:105°C






WIRING RANGE mm² (A.W.G.)	ITEM NO.	DIMENSIONS (mm)						
		øW	L	øD	ød	øb	F	T
22-16 A.W.G. 0.5-1.5 mm²	FRFNY 1.25-156-PS	5.9	24.5	4.2	1.7	3.9	14.0	0.4
16-14 A.W.G. 1.5-2.5 mm²	FRFNY 2-156-PS	5.6	24.5	4.2	2.4	3.9	14.0	0.4

NYLON-FULLY INSULATED MALE BULLET RECEPTACLE

Terminals body:Brass
Plating:Tin plated
Insulation:Nylon
Temperature:105°C





WIRING RANGE mm² (A.W.G.)	ITEM NO.	DIMENSIONS (mm)						
		øD	L	øD1	ød	ød1	F	T
22-16 A.W.G. 0.5-1.5 mm²	MRFNY 1.25-156-PS	7.5	25.5	4.3	1.8	4.0	9.6	0.4
16-14 A.W.G. 1.5-2.5 mm²	MRFNY 2-156-PS	7.6	25.5	4.3	2.3	4.0	9.2	0.4