
NYLON-FULLY INSULATED FEMALE DISCONNECTS(AL SERIES)

Terminals material:Brass
Plating:Tin plated
Insulation:Nylon
Acceptable customization






FUNNEL ENTRY

WIRING RANGE mm² (A.W.G.)	ITEM NO.	DIMENSIONS (mm)				
		TAB SIZE	D	B	L	T
22-16 A.W.G. 0.5-1.5 mm²	FDFNY1.25-250	6.4*0.8	4.4	6.7	22.5	0.4
16-14 A.W.G. 1.5-2.5 mm²	FDFNY2-250	6.4*0.8			21.8	
12-10 A.W.G. 4-6 mm²	FDFNY5.5-250	6.4*0.8	6.65		26	

NYLON-FULLY INSULATED FLAG FEMALE DISCONNECTS

Terminals material:Brass
Plating:Tin plated
Insulation:Nylon
Acceptable customization





FUNNEL ENTRY

WIRING RANGE mm² (A.W.G.)	ITEM NO.	DIMENSIONS (mm)			
		F	B	L	d
22-16 A.W.G. 0.5-1.5 mm²	FLDNY1.25-250	7.9	6.6	16.1	1.7
16-14 A.W.G. 1.5-2.5 mm²	FLDNY2-250	7.9	6.6	16.1	2.3
12-10 A.W.G. 4-6 mm²	FLDNY5.5-250	7.6	6.6	16.9	3.4