


NYLON-FULLY INSULATED MALE DISCONNECTS(AL SERIES)

Terminals material:Brass
Plating:Tin plated
Insulation:Nylon
Acceptable customization

FUNNEL ENTRY

WIRING RANGE mm² (A.W.G.)	ITEM NO.	DIMENSIONS (mm)				
		TAB SIZE	D	B	L	T
22-16 A.W.G. 0.5-1.5 mm²	MDFNY1.25-250	6.4*0.8	3.9	6.4	25	0.8
16-14 A.W.G. 1.5-2.5 mm²	MDFNY2-250	6.4*0.8	4.4			
12-10 A.W.G. 4-6 mm²	MDFNY5.5-250	6.4*0.8	6.7		28.8	





VINYL-FULLY INSULATED BULLET RECEPTACLES

Terminals material:Brass
Plating:Tin plated
Insulation:PVC
Acceptable customization

WIRING RANGE mm² (A.W.G.)	ITEM NO.	DIMENSIONS (mm)			
		D	B	L	T
22-16 A.W.G. 0.5-1.5 mm²	FRV1.25-156	3.3	4.65	23	0.4
16-14 A.W.G. 1.5-2.5 mm²	FRV2-156	4	4.65	24.5	
	FRV2-195		5.65	23.5	
12-10 A.W.G. 4-6 mm²	FRV5.5-156	6	4.65	27.5	
	FRV5.5-195	5.3	5.65	23.5	