
VINYL-INSULATED MALE BULLETS

Terminals material:Brass
Plating:Tin plated
Insulation:PVC
Acceptable customization






WIRING RANGE mm² (A.W.G.)	ITEM NO.	DIMENSIONS (mm)			
		D	B	L	T
22-16 A.W.G. 0.5-1.5 mm²	MPV1.25-156	3.6	4	22	0.4
16-14 A.W.G. 1.5-2.5 mm²	MPV2-156	4.4	4	21.5	
	MPV2-195		5	22	
12-10 A.W.G. 4-6 mm²	MPV5.5-156	5.4	4	25	
	MPV5.5-195		5		

VINYL-INSULATED MALE BULLETS
DOUBLE CRIMP

Terminals material:Brass
Metallic sleeve:Copper
Plating:Tin plated
Insulation:PVC

FUNNEL ENTRY






WIRING RANGE mm² (A.W.G.)	ITEM NO.	DIMENSIONS (mm)			
		D	B	L	T
22-16 A.W.G. 0.5-1.5 mm²	MPD1.25-156	4.3	4	22.5	0.4
16-14 A.W.G. 1.5-2.5 mm²	MPD2-156	4.9	4		
	MPD2-195		5		
12-10 A.W.G. 4-6 mm²	MPD5.5-156	6.5	4	26	
	MPD5.5-195		5		

NYLON-INSULATED MALE BULLETS

Terminals material:Brass
Plating:Tin plated
Insulation:Nylon
Acceptable customization





WIRING RANGE mm² (A.W.G.)	ITEM NO.	DIMENSIONS (mm)			
		D	B	L	T
22-16 A.W.G. 0.5-1.5 mm²	MPNY1.25-156	4.1	4	22	0.4
16-14 A.W.G. 1.5-2.5 mm²	MPNY2-156	4.5	4	22.5	
	MPNY2-195		5		
12-10 A.W.G. 4-6 mm²	MPNY5.5-156	6.6	4	25.7	
	MPNY5.5-195		5		