



## NYLON-INSULATED MALE BULLETS DOUBLE CRIMP

Terminals material:Brass
Metallic sleeve:Copper
Plating:Tin plated
Insulation:Nylon

FUNNEL ENTRY

| WIRING RANGE mm² (A.W.G.) | ITEM NO. | DIMENSIONS (mm) | | | |
|---|---|---|---|---|---|
| | | D | B | L | T |
| 22-16 A.W.G. 0.5-1.5 mm² | MPNYD1.25-156 | 4.1 | 4 | 22 | 0.4 |
| 16-14 A.W.G. 1.5-2.5 mm² | MPNYD2-156 | 5 | 4 | 22.5 | |
| | MPNYD2-195 | | 5 | | |
| 12-10 A.W.G. 4-6 mm² | MPNYD5.5-156 | 6.6 | 4 | 26 | |
| | MPNYD5.5-195 | | 5 | | |







## NYLON-FULLY INSULATED MALE BULLETS

Terminals material:Brass
Plating:Tin plated
Insulation:Nylon
Acceptable customization

FUNNEL ENTRY

| WIRING RANGE mm² (A.W.G.) | ITEM NO. | DIMENSIONS (mm) | | | |
|---|---|---|---|---|---|
| | | D | B | L | T |
| 22-16 A.W.G. 0.5-1.5 mm² | MPFNY1.25-156 | 4.3 | 4 | 25 | 0.4 |
| 16-14 A.W.G. 1.5-2.5 mm² | MPFNY2-156 | 5 | 4 | | |
| | MPFNY2-195 | | 5 | | |
| 12-10 A.W.G. 4-6 mm² | MPFNY5.5-156 | 6.6 | 4 | 27.5 | |
| | MPFNY5.5-195 | | 5 | | |






## NYLON-FULLY INSULATED MALE BULLETS DOUBLE CRIMP

Terminals material:Brass
Metallic sleeve:Copper
Plating:Tin plated
Insulation:Nylon

FUNNEL ENTRY

| WIRING RANGE mm² (A.W.G.) | ITEM NO. | DIMENSIONS (mm) | | | |
|---|---|---|---|---|---|
| | | D | B | L | T |
| 22-16 A.W.G. 0.5-1.5 mm² | MPFNYD1.25-156 | 4.3 | 4 | 25 | 0.4 |
| 16-14 A.W.G. 1.5-2.5 mm² | MPFNYD2-156 | 5 | 4 | | |
| | MPFNYD2-195 | | 5 | | |
| 12-10 A.W.G. 4-6 mm² | MPFNYD5.5-156 | 6.6 | 4 | 27.5 | |
| | MPFNYD5.5-195 | | 5 | | |