


NYLON-INSULATED PIGGYBACK DISCONNECTS

Terminals material:Brass
Plating:Tin plated
Insulation:Nylon
Acceptable customization

FUNNEL ENTRY

WIRING RANGE mm² (A.W.G.)	ITEM NO.	DIMENSIONS (mm)					
		TAB SIZE	D	B	L	b	T
22-16 A.W.G. 0.5-1.5 mm²	PBDNY1.25-250	6.4*0.8	4.1	6.7	22.5	6.35	0.4
16-14 A.W.G. 1.5-2.5 mm²	PBDNY2-250	6.4*0.8	4.5		23		
12-10 A.W.G. 4-6 mm²	PBDNY5.5-250	6.4*0.8	6.6		26		





NYLON-INSULATED PIGGYBACK DISCONNECTS DOUBLE CRIMP

Terminals material:Brass
Metallic sleeve:Copper
Plating:Tin plated
Insulation:Nylon

FUNNEL ENTRY

WIRING RANGE mm² (A.W.G.)	ITEM NO.	DIMENSIONS (mm)					
		TAB SIZE	D	B	L	b	T
22-16 A.W.G. 0.5-1.5 mm²	PBDNYD1.25-250	6.4*0.8	4.1	6.7	22.5	6.35	0.4
16-14 A.W.G. 1.5-2.5 mm²	PBDNYD2-250	6.4*0.8	5		23		
12-10 A.W.G. 4-6 mm²	PBDNYD5.5-250	6.4*0.8	6.6		26		