www.ledespecial.com

Energia solar led S. L
calle Rio Tormes 13 Fuenlabrada 28947 Madrid Spain
Email: energiasolarled2008@gmail.com
0034 916426626

Model: **ESL-A10**

A10 IP65 AWB Aluminum Waterproof Batten

3 versions available: standard, microwave sensor & emergency for industrial & commercial lighting.



Energy-efficient & long lifetime

Max efficacy up to 140lm/W, L75 lifespan ≥50,000hrs

Rich specification options

Available 600/1200/1500mm, max output up to over 11200lm, CCT 2700K~6500K adjustable

Upgraded structural & electrical design

Aerospace-grade aluminum housing, reinforced IP65 multi-seal protection, IK10 impact resistance, optional microwave sensor & emergency backup

Global Certifications & Flexible Warranty

CE approved; standard 5-year full fixture warranty, emergency battery 4-year warranty

Rugged, efficient luminaire for warehouses, cold storage, car parks & industrial lighting. Direct fluorescent replacement.

- Aerospace-grade aluminum body: Compared with traditional plastic vapor-tight fixtures, the integrated aluminum housing delivers over 40% higher heat dissipation efficiency, rapidly drawing away heat generated by the LEDs. This effectively suppresses lumen depreciation, significantly extends the light source lifespan, and ensures the fixture remains cool and distortion-free under high-load industrial conditions.
- IP65 full protection seal: Multi-layer sealing technology, from end caps to all joints, provides complete protection against dust ingress and resistance to water splashes and humid environments. It is ideal for demanding locations such as parking garages, cold storage facilities, slaughterhouses, and tunnels where dust, moisture, and corrosion are common challenges.
- High impact resistance: With an IK10 impact rating, the fixture withstands accidental knocks and vibrations, making it suitable for high-risk environments like heavy industrial workshops and logistics warehouses. This reduces the risk of physical damage and lowers long-term maintenance costs

Product Versions

Standard Version (N)
Basic model without sensor or emergency function, for general industrial and commercial lighting.

Microwave Sensor Version (S)
Built-in 5.8GHz microwave sensor with adjustable parameters, delivering intelligent energy-saving performance.

Emergency Version (E)
Equipped with emergency power module, automatically activates backup lighting when power cuts off, compliant with fire safety regulations.

www.ledespecial.com

Energia solar led S. L
calle Rio Tormes 13 Fuenlabrada 28947 Madrid Spain
Email: energiasolarled2008@gmail.com
0034 916426626

Model: **ESL-A10**

A10 IP65 AWB Aluminum Waterproof Batten

3 versions available: standard, microwave sensor & emergency for industrial & commercial lighting.

Warnings and Safety

- UV radiation will damage the material over time resulting in loss of waterproof sealing and IP65 rating.
- Do not install the luminaire in locations where it will be exposed to direct sunlight.

Specifications

Mounting type	Surface
	Suspended
Operating Temperature range	-30 to +50°C
Light Source	SMD2835
Mains Voltage	220-240Vac or 120-277Vac / 50-60Hz
Control system input	ON/OFF | RF | DALI | 0-10V
Material	PC+Alu.6063
Main color of the luminaire	RAL9016
Lumen maintenance at median useful life	L90B10, 50,000hr
Flicker free	Yes
Luminous flux	Up to 10000lm
Luminaire efficacy	Up to 160lm/W
Correlated color temperature - CCT	4000K
	6500K
Color Rendering index -	81

Risk Group	RG0
Optical cover/lens material	PC
Optical cover/lens finisha	Opal
	Clear
Protection Class	Class I
Driver replaceable	No
Installation	Suspension
	Surface

General Information

Light Technical	
Color rendering index (CRI)	80
Operating and Electrical	
Protection class IEC	Safety class I
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Mechanical and Housing	
Mech. impact protection code	IK08
Approval and Application	
CE mark	Yes
CB mark	Yes
Flammability mark	-

Dimensional (mm)



Type	Dimension(mm)						No. of cips	N.W/PCS
	A	B	C	D	Emin	F		
Trilamp A10 2FT	82	600	98	\	260-420	\	6	1.6kg
Trilamp A10 4FT		1200			700-980		12	2.2kg
Trilamp A10 5FT		1500			940-1300		14	2.9kg

Order Code

Specifications using 4000K and subject to change. All parameters +/- 5%.

Version	Item No.	Full Product Datasheet	Function	Sales Aera
	A10-2FTZZ-MMK-X	A10 600mm 40W 4000K 140LPW	Constant On	European
EXTRA	A10-4FTZZ-MMK-X	A10 1200mm 60W 4000K 140LPW	Constant On	European
	A10-5FTZZ-MMK-X	A10 1500mm 80W 4000K 140LPW	Constant On	European

Fanxstar is committed to continuously improve our products. All features and specifications are subject to change without prior notice. All rights reserved.