www.ledespecial.com

Energia solar led S. L
calle Rio Tormes 13 Fuenlabrada 28947 Madrid Spain
Email: energiasolarled2008@gmail.com
0034 916426626

Model: **ESL-GD21F10E**

Track Spotlight

Clothing stores, jewelry boutiques, supermarket fresh counters, art galleries, cosmetic shops & retail showrooms.

Appearance & Installation

2-wire track mounting, cylinder housing available in black & white. 10W size: Φ55×150mm. 355° horizontal rotation + 90° vertical tilt for flexible aiming, perfect for boutiques, fresh stores and galleries.

Optical Performance

COB/CSP LED chip, CRI Ra90, MacAdam ≤5, true color reproduction. 36° narrow beam direct lighting, UGR<19 anti-glare, no harsh reflection on displays.
Multiple CCT options: 3000K / 4000K / 5000K / 3CCT tunable, for clothes, jewelry, produce and art exhibits.





MOUNTING	
Mounting location	Track
Type	2 wire

ELECTRICAL	
Voltage	220V-240V
Frequency	50/60Hz
Dimming	Depending on driver


DIMENSION	
Dimension	10W:Ø55x150mm
Height	NO
Cut out	NO


LIGHT	
Adjustibility	355°/90°
Light distribution	Direct
Unified glare rating (UGR)	<19

LAMP DESCRIPTION	
Lamp type	COB/CSP
Colour rendering index (CRI)	Ra≥90
MacAdam	<5

OTHERS	
LED life Time	5 YEARS (Ta 25°C)
Environment temperature	-20°C~40°C
Ingress protection	IP20

Dimensions (mm)





Product Code	LED Power	Ingress Protection	Light Sour ce Code	CRI>	CCT	Lumen (Ra90)	Beam Angle (BA°)	Driver Options	Housing Color	Ring Color
GD21F10E	10W	IP20	COB	90	3000K 4000K 5000K 3CCT	900lm 950lm 980lm	Reflector 36°	Non-dim	Black Whit e	Black Whit e

Warning: The test data is for reference only. The test data should be based on the actual test report.

www.ledespecial.com

Energia solar led S. L
calle Rio Tormes 13 Fuenlabrada 28947 Madrid Spain
Email: energiasolarled2008@gmail.com
0034 916426626

Model: **ESL-GD21F20E**

Track Spotlight

Clothing stores, jewelry boutiques, supermarket fresh counters, art galleries, cosmetic shops & retail showrooms.

Appearance & Installation

2-wire track mounting, cylinder housing available in black & white. 10W size: Φ55×150mm. 355° horizontal rotation + 90° vertical tilt for flexible aiming, perfect for boutiques, fresh stores and galleries.


Optical Performance


COB/CSP LED chip, CRI Ra90, MacAdam ≤5, true color reproduction. 36° narrow beam direct lighting, UGR<19 anti-glare, no harsh reflection on displays.
Multiple CCT options: 3000K / 4000K / 5000K / 3CCT tunable, for clothes, jewelry, produce and art exhibits.



MOUNTING	
Mounting location	Track
Type	2 wire
ELECTRICAL	
Voltage	220V-240V
Frequency	50/60Hz
Dimming	Depending on driver
DIMENSION	
Dimension	20W:Ø60x165mm
Height	NO
Cut out	NO
LIGHT	
Adjustibility	355°/90°
Light distribution	Direct
Unified glare rating (UGR)	<19
LAMP DESCRIPTION	
Lamp type	COB/CSP
Colour rendering index (CRI)	Ra≥90
MacAdam	<5
OTHERS	
LED life Time	5 YEARS (Ta 25°C)
Environment temperature	-20°C~40°C
Ingress protection	IP20

Dimensions (mm)





Product Code	LED Power	Ingress Protection	Light Sour ce Code	CRI>	CCT	Lumen (Ra90)	Beam Angle (BA°)	Driver Options	Housing Color	Ring Color
GD21F20E	20W	IP20	COB	90	3000K 4000K 5000K 3CCT	1900 lm 1950 lm 1980 lm	Reflector 36°	Non-dim	Black Whit e	Black Whit e

Warning: The test data is for reference only. The test data should be based on the actual test report.