SPRT

Specialized, Pioneer, Revolution, Technology

https://www.sprt-printer.com

Smarter, more conveient

SP-TL28

- Easy label positioning
- Zero waste for the first order
- Compact design

- Easy startup and shutdown
- Sensitive Calibration
- Support BT multi mode & BT dual mode
- More compact and modern design
- Easy label positioning
- Suitable for a variety of usage scenarios

Printer Technical Specifications

Printing Performance

Printing Method: Thermal line
Printing Speed (Max): 60mm/s(label)
Resolution: 8dots/mm （203dpi）

Paper Specifications

Effective Printing Width: 48mm
Thickness of Paper: 0.12~0.14mm
Width of Paper: 25mm-60mm(Lining paper)

Printing Characters and Barcodes

GB18030 all Chinese characters and characters
1D Barcode: UPCA, EAN13, CODE39, etc
2D Barcode: QRcode

Connectivity

Interfaces: USB/Serial/ Bluetooth (Bluetooth multimode & Bluetooth single mode)
Cash drawer interface (reserved)

Environmental Parameters

Working temperature: 0°C~50°C
Working humidity: 10%~85%
Storage temperature: -20°C~60°C
Storage humidity: 10%~90%

Physical Specifications

Paper Roll Diameter: ⩽80mm
Weight: 550g (without paper)
Dimension: 154(L)×116(W)×130(H)mm

Application Scenarios

Logistics

Storage

Retail

Beverages

Garment

SPRT

Beijing Spirit Technology Development Co.,Ltd.
TEL : +86-10-82781467
Email : export@sprinter.com.cn
www.sprt-printer.com

NO.26 Ave.4,Chuangye Middle Road,
Shangdi Information Industy Park,
Beijing 100085 China